



- Push-pull latching system
- Chrome plated Brass
- IP68
- 360° Screening for full EMC shielding

# **RS PRO Industrial Circular Connectors**

RS Stock No.: 2406513



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.



#### **Product Description**

RS Pro's range of waterproof Chrome plated Brass push-pull locking connectors offer exceptional quality that is found in many cutting-edge connectors, including an IP68 rating and full 360° EMC shielding with a high mating life. As has become standard within the RS Pro brand you can expect high quality products but at a reasonable price. These connectors are ideal for use in medical devices, testing equipment, audio equipment and other high-end applications.

#### **General Specifications**

Number of Contacts	4
Housing Material	Chrome Plated Brass
Contact Material	Brass
Contact Plating	Gold
Contact Gender	Female
Mating Type	Cable Mount
Body Orientation	Straight
Contact Carrier	PPS
Mating Cycles	>5,000
Colour	Natural
Application	Instrumentation, Process control, Robotics, Assembly lines and manufacturing, Factory automation, Industrial production and automation, Medical devices

### **Electrical Specifications**

Plug/Socket	Socket
Current Rating	12A
Test Voltage Contact-Shell k/vAC	1.80
Test Voltage Contact – Contact k/v AC	2.20



Mechanical Specifications	
Connector Size	
Termination Method	

Connector Size	2F
Termination Method	Solder
Mounting Type	Panel Mount
Cable Outer Diameter	6.7

# **Operation Environment Specifications**

35 C to 250 C	Operating Temperature	-55 <sup>0</sup> C to +250 <sup>0</sup> C
---------------	-----------------------	---

### **Protection Category**

IP Rating	

# **Approvals**

Compliance/Certific	ations

RoHS, CE

IP68

# FOR MATING PARTS, SEE MATRIX:



## **RM-F Series 2F**

	Cable End Panel Mount				In-Line Cable End				
No. of Contacts	Gender	33.3	RS Stock No.	No. of Contacts	Gender		RS Stock No.	No. of Contacts	Gender
2	Male		2406427	2	Female	Or	2406511	2	Female
3	Male		2406428	3	Female		2406512	3	Female
4	Male		2406429	4	Female		2406513	4	Female
6	Male		2406430	6	Female		2406514	6	Female
8	Male		2406431	8	Female		2406515	8	Female
1+8	Male		2406432	1+8	Female		2406516	1+8	Femal
16	Male		2406433	16	Female		2406518	16	Femal
19	Male	1.040	2406434	19	Female		2406519	19	Femal
	2 3 4 6 8 1+8 16	2 Male 3 Male 4 Male 6 Male 8 Male 1+8 Male 16 Male	2 Male Mates   3 Male "   4 Male "   6 Male "   8 Male "   1+8 Male "   16 Male "	2 Male Mates With 2406427   3 Male " 2406428   4 Male " 2406429   6 Male " 2406430   8 Male " 2406431   1+8 Male " 2406432   16 Male " 2406433	2 Male Mates With 2406427 2   3 Male " 2406428 3   4 Male " 2406429 4   6 Male " 2406430 6   8 Male " 2406431 8   1+8 Male " 2406432 1+8   16 Male " 2406433 16	2 Male With Mates With 2406427 2 Female   3 Male " 2406428 3 Female   4 Male " 2406429 4 Female   6 Male " 2406430 6 Female   8 Male " 2406431 8 Female   1+8 Male " 2406432 1+8 Female   16 Male " 2406433 16 Female	2 Male With 2406427 2 Female Or   3 Male " 2406428 3 Female "   4 Male " 2406429 4 Female "   6 Male " 2406430 6 Female "   8 Male " 2406431 8 Female "   1+8 Male " 2406432 1+8 Female "   16 Male " 2406433 16 Female "	2 Male With 2406427 2 Female Or 2406511   3 Male " 2406428 3 Female " 2406512   4 Male " 2406429 4 Female " 2406513   6 Male " 2406430 6 Female " 2406514   8 Male " 2406431 8 Female " 2406515   1+8 Male " 2406432 1+8 Female " 2406516   16 Male " 2406433 16 Female " 2406518	2 Male With 2406427 2 Female Or 2406511 2   3 Male " 2406428 3 Female " 2406512 3   4 Male " 2406429 4 Female " 2406513 4   6 Male " 2406430 6 Female " 2406514 6   8 Male " 2406431 8 Female " 2406515 8   1+8 Male " 2406432 1+8 Female " 2406516 1+8   16 Male " 2406433 16 Female " 2406518 16

The RS PRO Seal of Approval is only awarded after a rigorous quality process to demanding international standards.







