



ENGLISH

Datasheet

**RS Pro Clear Heat Shrink Tubing sleeve diameter 50.8mm
length 30cm ratio 2:1**

RS Stock No: **443-4996**



Product Details

RS Pro heat shrink tubing sleeve in clear colour, has 50.8 mm diameter and 30 cm length with a ratio of 2:1. This pre-cut heat sheet sleeve is made from flexible irradiated polyolefin. This tubing sleeve meets UL224 125°C 600V VW-1 E48762, CSA C22.2 No198.1, Mil SAE-AMS-DTL 23053/5 class 1 except clear, IEC 60684-3-212 A&B, BS3G 198 part 3 11b and VG 95343 part5 A&B standards.

Features and Benefits

- High mechanical and electrical strength, corrosion resistant
- Supplied in pre-cut lengths of 300 mm for easy use and storage
- Irradiated polyolefin construction

**Specifications:**

Adhesive Lined	No
Angle	Straight
Colour	Clear
Dielectric Strength	30 kV/mm
Flame Retardant	Yes
Halogen Free	Yes
Material	Polyolefin
Maximum Operating Temperature	+135°C
Minimum Operating Temperature	-55°C
Operating Temperature Range	-55 to +135°C
Shrink Ratio	2:1
Shrunk Diameter	25.4 mm
Sleeve Diameter	50.8 mm
Sleeve Length	30 cm
Sleeve Type	Heat Shrink
Standards Met	UL 224 VW-1 E48762, CSA C22.2 No. 198.1, MIL SAE-AMS-DTL 23053/5 Class 1, IEC 60684-3-212 A&B, BS3G 198 Part 3 11B, VG 95343 Part 5 A&B, RoHS Compliant