

DC PULSE TIG/MMA

VT-300P

TIG / MMA
Power Source

Quick Specs

Light Industrial Applications

Maintenance Repair
Shipboard Installation
Fabrication
Process Piping

Power Voltage

1 Phase AC240V ±15%
50/60Hz

Input Current

35A/8.4kVA

Output Current

3-250A
Max. OCV: 67.5VDC

Output Voltage

10V~20V

Duty Cycle

70%

Weight

18.5KG

Dimensions

D550×H375×W210MM

Portable. Professional. Rugged. Affordable.

The inverter **VT-300P** offers much more than you would expect from a welder this size. Weighing in at just under 18.5kg the Inverter **VT-300P** is no lightweight contender. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It can operate from a portable generator.

FEATURES

- DC inverter for TIG with advanced inverter technology to optimize arc performance.
- Improved TIG Starting. Now starts DC(-) to maintain a sharp tungsten.
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- 250 amps @ 70% duty cycle is the highest output rating in this machine class.
- Inverter-based, DC power source has a **simple-to-use operator interface** providing only the necessary controls in a compact machine.
- **Built-in pulsing functions** 0.5~300Hz

PROCESSES

DC TIG (GTAW)
MMA

INCLUDED

VT-300P Machine Only Includes:

- VT-300P
- 7M WP26F-1 TIG TORCH.
- 3M work cable and clamp.

INPUT



OUTPUT



**Please note that the specification may vary within each country. Specifications are subjected to change without notice.*

AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3

TAMAN BATU GAJAH PERDANA

31550 PUSING PERAK MALAYSIA

TEL: (605)3632 115 FAX: (605)3632 111

E-mail: austcorp@welding.com.my

WEB: www.welding.com.my



Welding Technology