

## FEATURES

- Flexible - can be wrapped around pipes
- Various lengths available
- Constant wattage heating cables

## RS PRO 20W/m Trace Heating Kit Constant Wattage, Parallel Circuit, 240 V, 20m

RS Stock No.: 379-744



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

RS PRO range of parallel circuit heating tape, with a constant wattage output for process temperature maintenance applications. This tape is flexible enough to allow it to be spiralled around a suitable pipe or vessel.

Trace heating cable options include:

[703-3114](#) - 20W/m, 110 V, 20m cable

[703-3120](#) - 40W/m, 110 V, 20m cable

[703-3123](#) - 40W/m, 110 V, 50m cable

[379-744](#) - 20W/m, 240 V, 20m cable

[665-7422](#) - 20W/m, 240 V, 50m cable

[665-7425](#) - 20W/m, 240 V, 100m cable

[379-750](#) - 40W/m, 240 V, 20m cable

[665-7429](#) - 40W/m, 240 V, 50m cable

[665-7438](#) - 40W/m, 240 V, 100m cable

[665-7431](#) - Trace Heating Kit Frost Protection, Parallel Circuit

## General Specifications

<b>Cable Type</b>	Constant Wattage, Parallel Circuit
<b>Self-Regulating</b>	No
<b>Sheath Material</b>	Silicone Rubber
<b>Hazardous Area Certification</b>	No
<b>Standard Met</b>	BS EN 62395-1:2006, RoHS Compliant
<b>Applications</b>	Frost protection; Water, oil and chemical lines; Sprinkler system mains; Supply piping; Not for use in hazardous areas

## Electrical Specifications

<b>Output Per Metre</b>	20W
<b>Voltage Rating</b>	240V

## Mechanical Specifications

<b>Length</b>	20m
---------------	-----

## Operation Environment Specifications

Operating Temperature Rating	-60 to 200°C
------------------------------	--------------





