

# AP4423A

## APC NetShelter Rack Automatic Transfer Switch, 1U, 16A, 230V, 2 C20 IN, 8 C13, 1 C19 OUT, 50/60Hz



### Overview

Lead time	Usually in Stock
-----------	------------------



### Main

Main Input Voltage	230 V AC 1 phase
Product or component type	Automatic transfer switch
Main Output Voltage	230 V AC 1 phase
Input Connection Type	IEC 60320 C20 16 A 2P + E
Number of rack unit	1U
Provided equipment	Mounting hardware Rack mounting brackets

### Physical

Colour	Black
Height	4.4 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	3.74 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Horizontal

### Input

Network frequency	50/60 Hz
[In] rated current	16 A
Permissible voltage	207...253 V
Max line current	20 A
Input current limits	20 A
Load capacity	3700 VA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Output

Number of power socket outlets	8 IEC 60320 C13 10 A 2P + E 1 IEC 60320 C19 16 A 2P + E
Number of power socket outlets	9
Protection type	Without circuit breaker
Power cable length	2.44 m

## Conformance

Product certifications	cUL listed[RETURN]CE[RETURN]UL listed
Standards	EN 55022 class A FCC part 15 class A

## Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	35.500 cm
Package 1 Length	60.000 cm
Package 1 Weight	5.492 kg
Unit Type of Package 2	P12
Number of Units in Package 2	40
Package 2 Height	126.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	233.000 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Lead free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------