



### Main

Range	Acti 9
Device short name	ISW
Product or component type	Switch
Switch application	Control
Poles description	2P
Utilisation category	AC-22A
Suitability for isolation	Yes

### Complementary

[Ie] rated operational current	32 A 415 V AC 50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60669-2-4
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Colour	White
Mechanical durability	300000 cycles
Electrical durability	30000 cycles
Connections - terminals	Tunnel type terminals: 1 cable(s) 1.5...10 mm <sup>2</sup> flexible Tunnel type terminals: 1 cable(s) 1.5...10 mm <sup>2</sup> rigid Tunnel type terminals: 2 cable(s) 2.5 mm <sup>2</sup> flexible Tunnel type terminals: 2 cable(s) 2.5 mm <sup>2</sup> rigid Tunnel type terminals: 2 cable(s) 4 mm <sup>2</sup> flexible Tunnel type terminals: 2 cable(s) 4 mm <sup>2</sup> rigid
Wire stripping length	9 mm
Tightening torque	1.2 N.m

### Environment

standards	EN/IEC 60669-2-4
IP degree of protection	IP4
pollution degree	2
tropicalisation	2

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

