

Datasheet

Product Name: UL3239 28AWG
Product Discription: UL3239 28AWG
Specification No.: SPEC-UL3239-28AWG
Customer's Name:

Description						Construction					
Rated Voltage: 6KVDC					Conductor S		Stranded Tinned Copper		/11		
	emperature:		105℃		Size(AWG)		28				
	ce Standard:		58,UL1581		Construction(±0.008mm)		7/0.127				
Cross Section					Stranded Dia.(mm)Ref.		0.38				
					Insulation	<u> </u>	XLPE				
					Insulation	n Color	ANY COLOR				
					Ave Thickness(mm)		0.41				
						(ness(mm)	0.36				
					Insulation	Dia.(±0.05mm)	1.20				
						· ·					
Marking					Remark:			Ш			
						8738873 Red	8738882 Blu	8738882 Blue 8738891 Oran		ge 8738905 Violet	
E254881Ŋ AWM STYLE 3239 28AWG 105℃ 6KV-DC VW						8738876 Black	8738885 White		8738895 Grey		
CAU AWM I A 105°C 6KV-DC FT1 -LF- ELETECK					8738879 Brown 8738889 Gr			een	8738898 Yello	W	
					Characteristic			cs		Customer Approve	
Applications					Test Item			Standard Value			
For internal wiring of electronic and electrical equipment					Test Material			XLPE(RoHS)			
					Before	e Tensile Strength(Mpa)		≥10.3		1	
					Aging Elongation(%)		≥150		Seal & Stamp		
					Aging Condiction			136±2℃*168hrs			
Revisions					After Tensile Strength(Mpa)		≥70% of original				
Version	Description	Drawn by	Approved by	Date	Aging	Elongation(%)		≥45% of original			
0	New document is:	sue YanBin	David Lin	14/04/2015	Max.DC F	esistance(20℃ Ω/km)			239		
					Flammab	Flammability Test			VW-1		
										Signature:	
	-										
										Date:	

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.