

## FEATURES

- Made of polyamide, in green
- Dimensions of 7.62 (L) x 6.2 mm (D)
- Pitch of 2.54 mm
- Three contacts
- Single row
- Through hole mounting
- Female
- Straight body orientation
- Screw type termination method
- Current rating of 6 A
- Voltage rating of 125 V
- Operating temperature range of -40°C and +105°C

## RS PRO 2.54mm Pitch, 3 Way PCB Terminal Strip

RS Stock No.: 790-1092



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

Link wires quickly and efficiently across printed circuit boards with this 3-way PCB (printed circuit board) terminal strip. This modular, insulated device can be mounted directly onto PCBs.

## General Specifications

<b>Number Of Contact</b>	3
<b>Number Of Rows</b>	1
<b>Mounting Type</b>	Through Hole
<b>Gender</b>	Female
<b>Termination Method</b>	Screw
<b>Type</b>	PCB Terminal Block
<b>Body Orientation</b>	Straight
<b>Colour</b>	Green
<b>Material</b>	Polyamide
<b>Flammability Rating</b>	UL 94 V-0
<b>Applications</b>	PCB

## Electrical Specifications

<b>Current Rating</b>	6A
<b>Voltage Rating</b>	125V
<b>Insulation Resistance</b>	>2000M $\Omega$
<b>Insulation Withstand Voltage</b>	2000V ac

## Mechanical Specifications

Pitch	2.54mm
Depth	6.2mm
Width	5.54mm
Length	7.62mm

## Operation Environment Specifications

Operating Temperature Range	-40°C to 105°C
-----------------------------	----------------

## Approvals

Compliance/Certifications	EN61340
---------------------------	---------



