



Datasheet

RS PRO UNCOATED BALL-LOCK STAINLESS STEEL CABLE TIES

RS Stock no. 1834223,1834224,1834225,1834226

EN



Technical Information:

Material: Stainless Steel Grade 304

304 grade stainless steel, for standard applications

Working Temp.: -80° C to $+500^{\circ}$ C Description: Metallic band and buckle

Flammability: Fireproof

Other Properties: UV-resistant

Product Feature: Uncoated version, for high temperature applications, quick installation.

Applications: Ideal for petrochemical, food industry, industries, power stations, mining, ship-building,

offshore and any other aggressive environments.

Specification

RS CODE	EASE CODE	LENGTH		WIDTH		TICKNESS		MAX. BUNDLE DIAMETER		MIN. TENSILE STRENGTH	
		mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
183-4223	CT-SS-BL125/4.6UC- 304	125	4.9	4.6	0.18	0.26	0.010	31	1.23	1100	250
183-4224	CT-SS-BL-200/4.6UC- 304	200	7.9					50	1.97		
183-4225	CT-SS-BL-360/4.6UC- 304	360	14.2					90	3.55		
183-4226	CT-SS-BL-360/7.9UC- 304	360	14.2	7.9	0.31	0.26	0.010	90	3.55	1500	340



