

Datasheet

RS Pro Disconnect Terminal Block, 17150.4 Series, 500 (IEC) V, 600 (cUL) V, 600 (UL) V

RS Stock No: **872-4827**



Product Details

RS Pro 12-way power distribution block in clear colour, has a screw down terminal for easy termination. This power distribution block is suitable for accepting flexible cables from 6 mm² to 50 mm², with access from two sides. It has halogen free PC body construction for self extinguishing to UL94V-0 specification. The block supports 12-way connection with the CSA of 6 x 16 mm², 4 x 25 mm² and 2 x 50 mm². This power distribution block comes with DIN rail mounting brackets, fixings and identification labels for easy installation. It measures 70 x 58 x 6.1 mm.

Features and Benefits

- DIN rail mounting brackets, fixings and identification labels included
- Instructions, detailing connection details, are included
- Dimensions: 70 mm x 58 mm x 6.1 mm

**Specifications:**

Colour	Black
Current Rating	10 A (IEC), 16 A (cUL), 16 A (UL)
Fuse Size	5 x 20 mm, 5 x 25 mm, 5 x 30 mm
Maximum Operating Temperature	+140°C
Minimum Operating Temperature	-40°C
Number of Connectors	2
Number of Levels	1
Termination Method	Screw
Voltage Rating	500 V (IEC), 600 V (cUL), 600 V (UL)
Wire Size	22 to 11 AWG