

## FEATURES

- **Black Neoprene Rubber**
- **Flexible**
- **Durable**
- **Customisable**
- **Resistant to ozone, sunlight and atmospheric ageing**

## RS PRO Black Rubber Sheet, 1m x 600mm x 6mm

RS Stock No.: 506-3141



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

Introducing a series of neoprene rubber sheets from RS PRO. These black neoprene rubber sheets are suitable for use, both indoor & outdoor, offer moderate resistance to atmospheric ageing, sunlight, oils, and greases.

### RS PRO Rubber Sheet Options

- 1 m x 600 mm x 1.5mm - RS Stock no: 506-3163
- 1 m x 600 mm x 3mm - RS Stock no: 506-3157
- 1 m x 600 mm x 6mm - RS Stock no: 506-3141
- 1m x 600mm x 12mm - RS Stock no: 506-3113
- 1 m x 600 mm x 10mm - RS Stock no: 506-3135
- 1 m x 1.2 m x 1.5mm - RS Stock no: 506-3107
- 1 m x 1.2 m x 3mm - RS Stock no: 506-3208
- 1m x 1.2m x 6mm - RS Stock no: 506-3191
- 1m x 1.2m x 10mm - RS Stock no: 506-3185
- 1m x 1.2m x 12mm - RS Stock no: 506-3179

## General Specifications

<b>Colour</b>	Black
<b>Suitability</b>	Animal Oil; Cold Water; Dilute Acid; Dilute Alkali
<b>Elongation</b>	300%
<b>Hardness</b>	60+/-7
<b>Finish</b>	Smooth
<b>Durometer</b>	Shore A
<b>Density (Gram/cm<sup>3</sup>)</b>	1.35
<b>Application</b>	Sound-proofing, Noise and Heat insulation

## Mechanical Specifications

<b>Length</b>	1m
<b>Thickness</b>	6mm
<b>Width</b>	600mm
<b>Tensile Strength</b>	5N/mm <sup>2</sup>

## Operation Environment Specifications

<b>Maximum Operating Temperature</b>	70°C
<b>Minimum Operating Temperature</b>	-10°C