

**RoHS
Compliant**



Description:

MLCC consists of a conducting material and electrodes. To manufacture a chip-type SMT and achieve miniaturization, high density and high efficiency, ceramic condensers are used. The MLCC is made by NP0, X7R, X6S, X5R and Y5V dielectric material and which provides product with high electrical precision, stability and reliability.

Features:

- A wide selection of sizes is available (0201 to 1812).
- High capacitance in given case size.
- Capacitor with lead-free termination (pure Tin).


Applications:

- For general digital circuit.
- For power supply bypass capacitors.
- For consumer electronics.
- For telecommunication.

How To Order:

| MC | 1206 | B | 104 | K | 500 | C | T |
|-----------|--|--|---|---|---|-------------|--|
| | Size | Dielectric | Capacitance | Tolerance | Rated Voltage | Termination | Packaging style |
| Multicomp | Inch (mm) 0201 (0603) 0402 (1005) 0603 (1608) 0805 (2012) 1206 (3216) 1210 (3225) 1812 (4532) | N=NP0 (C0G) B=X7R F=Y5V X=X5R S=X6S | Two significant digits followed by no. of zeros. And R is in place of decimal point. Eg.: 0R5=0.5pF 1R0=1.0pF 104 = 10×10 ⁴ = 100nF | A=±0.05pF B=±0.1pF C=±0.25pF D=±0.5pF F=±1% G=±2% J=±5% K=±10% M=±20% Z=-20/+80% | Two significant digits followed by no. of zeros. And R is in place of decimal point. 4R0=4V DC 6R3=6.3V DC 100=10V DC 160=16V DC 250=25V DC 500=50V DC 101=100V DC | C=Cu/Ni/Sn | T=7" reeled R=7" reeled (2mm pitch for 0603 size; paper tape) G=13" reeled |

External Dimensions:



The outline of MLCC

| Size Inch (mm) | L (mm) | W (mm) | T (mm)/Symbol | | Soldering Method * | M _B (mm) |
|-------------------|------------|-------------|-----------------|---|-----------------------|---------------------|
| 01R5 (0402) | 0.4 ±0.02 | 0.2 ±0.02 | 0.2 ±0.02 | V | R | 0.1 ±0.03 |
| 0201 (0603) | 0.6±0.03 | 0.3 ±0.03 | 0.3 ±0.03 | L | R | 0.15 ±0.05 |
| | 0.6±0.05#2 | 0.3 ±0.05#2 | 0.3 ±0.05#2 | | | 0.15 +0.1/-0.05 |
| | 0.6±0.09#3 | 0.3 ±0.09#3 | 0.3 ±0.09#3 | | | |
| 0402 (1005) | 1 ±0.05 | 0.5 ±0.05 | 0.5 ±0.05 | N | R | 0.25 +0.05/-0.1 |
| | | | 0.5 +0.02/-0.05 | Q | | |
| | 1 ±0.2 | 0.5 ±0.2 | 0.5 ±0.2 | E | | |

**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**

multicomp PRO

| Size Inch (mm) | L (mm) | W (mm) | T (mm)/Symbol | | Soldering Method * | M _B (mm) |
|-------------------|--|------------------------|------------------------|---|-----------------------|---|
| 0603 (1608) | 1.6 ±0.1 | 0.8 ±0.1 | 0.8 ±0.07 | S | R / W | 0.4 ±0.15 |
| | 1.6 +0.15/- 0.1 | 0.8 +0.15/-0.1 | 0.5 ±0.1 | H | R / W | |
| | | | 0.8 +0.15/-0.1 | X | R / W | |
| | 1.6 ±0.2* ¹ | 0.8 ±0.2* ¹ | 0.8 ±0.2* ¹ | | | |
| 0805 (2012) | 2 ±0.15 | 1.25 ±0.1 | 0.5 ±0.1 | H | R / W | 0.5 ±0.2 |
| | | | 0.6 ±0.1 | A | R / W | |
| | | | 0.8 ±0.1 | B | R / W | |
| | 1.25 ±0.1 | D | R | | | |
| | 2 ±0.2 | 1.25 ±0.2 | 0.85 ±0.1 | T | R / W | |
| 1.25 ±0.2 | | | I | R | | |
| 1206 (3216) | 3.2 ±0.15 | 1.6 ±0.15 | 0.8 ±0.1 | B | R / W | 0.6 ±0.2 (0.5±0.25) ^{***} |
| | | | 0.95 ±0.1 | C | R | |
| | | | 1.25 ±0.1 | D | R | |
| | 3.2 ±0.2 | 1.6 ±0.2 | 1.15 ±0.15 | J | R | |
| | | | 1.6 ±0.2 | G | R | |
| | | | 0.85 ±0.1 | T | R / W | |
| 3.2 +0.3/-0.1 | 1.6 +0.30/-0.1 | 1.6 +0.3/-0.1 | P | R | | |
| 1210 (3225) | 3.2 ±0.3 | 2.5±0.2 | 0.95 ±0.1 | C | R | 0.75 ±0.25 |
| | | | 0.85 ±0.1 | T | R | |
| | | | 1.25 ±0.1 | D | R | |
| | 3.2±0.4 | 2.5±0.3 | 1.6 ±0.2 | G | R | |
| | | | 2 ±0.2 | K | R | |
| | | 2.5 ±0.3 | M | R | | |
| 1808 (4520) | 4.5 ±0.4 (4.5+0.5/- 0.3) ^{**} | 2.03 ±0.25 | 1.25 ±0.1 | D | R | 0.75 ±0.25 (0.5±0.25) ^{***} |
| | | | 1.4 ±0.15 | F | R | |
| | | | 1.6 ±0.2 | G | R | |
| | | | 2 ±0.2 | K | R | |
| 1812 (4532) | 4.5 ±0.4 4.5+0.5/- 0.3) ^{**} | 3.2 ±0.3 | 1.25 ±0.1 | D | R | 0.75 ±0.25 0.5±0.25) ^{***} |
| | | | 1.6 ±0.2 | G | R | |
| | | | 2 ±0.2 | K | R | |
| | | 3.2 ±0.4 | 2.5 ±0.3 | M | R | |
| | | | 2.8 ±0.3 | U | R | |

* R = Reflow soldering process; W = Wave soldering process.

** For 1808_200V~3kV, 1812_200V~3kV and safety certificated products.

*** For 1206_1000V~3kV, 1808_200V~3kV, 1812_200V~3kV and safety certificated products.

#1: For 0603/Cap≥10µF or 0603(>10V)/Cap>1µF products.

#2: For 0201/Cap≥0.68µF products.

#3: For 0201/Cap >1µF products.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO

General Electrical Data:

| Dielectric | NP0 | X7R | Y5V | X5R | X6S |
|----------------------------|--|-----------------------------------|---------------------------|------------------------------|-----------------------|
| Size | 0402, 0603, 0805, 1206, 1210, 1812 | | | | |
| Capacitance range* | 0.1pF to 0.1μF | 100pF to 47μF | 0.01μF to 100μF | 100pF to 220μF | 0.1μF to 100μF |
| Capacitance tolerance** | Cap≤5pF#1: A (±0.05pF), B (±0.1pF), C (±0.25pF) 5pF<Cap<10pF: C (±0.25pF), D (±0.5pF) Cap≥10pF: F (±1%), G (±2%), J (±5%), K (±10%) | J (±5%), K (±10%), M (±20%) | M (±20%), Z (-20/+80%) | K (±10%), M (±20%) | K (±10%), M (±20%) |
| Rated voltage (WVDC) | 10V, 16V, 25V, 50V,100V | 6.3V, 10V, 16V, 25V, 50V, 100V | | 4V, 6.3V, 10V, 16V, 25V, 50V | |
| DF(Tan δ)* | Cap<30pF: Q≥400+20C Cap≥30pF: Q≥1000 | Note 1 | | | |
| Operating temperature | -55 to +125°C | | -25°C to +85°C | -55°C to +85°C | -55°C to +105°C |
| Capacitance characteristic | ±30ppm | ±15% | +30/-80% | ±15% | ±22% |
| Termination | Ni/Sn (lead-free termination) | | | | |

#1: NP0, 0.1pF product only provide B tolerance

* Measured at the condition of 30~70% related humidity.

NP0: Apply 1.0±0.2Vrms, 1.0MHz±10% for Cap≤1000pF and 1.0±0.2Vrms, 1.0kHz±10% for Cap>1000pF, 25°C at ambient temperature

X7R/X6S/X5R: Apply 1.0±0.2Vrms, 1.0kHz±10%, at 25°C ambient temperature.

Y5V: Apply 1.0±0.2Vrms, 1.0kHz±10%, at 20°C ambient temperature.

** Preconditioning for Class II MLCC: Perform a heat treatment at 150±10°C for 1 hour, then leave in ambient condition for 24±2 hours before measurement.

Note 1:

X7R/X5R/X6S

| Rated Vol. | D.F. \leq | Exception of D.F. \leq | |
|-------------|--------------|--------------------------|---|
| $\geq 100V$ | $\leq 2.5\%$ | $\leq 3\%$ | 1206 $\geq 0.47\mu F$ |
| | | $\leq 5\%$ | 0805 $> 0.1\mu F$; 0603 $\geq 0.068\mu F$; 1206 $> 1\mu F$; TT series |
| 50V | $\leq 2.5\%$ | $\leq 3\%$ | 0201(50V); 0603 $\geq 0.047\mu F$; 0805 $\geq 0.18\mu F$; 1206 $\geq 0.47\mu F$ |
| | | $\leq 5\%$ | 1210 $\geq 4.7\mu F$ |
| | | $\leq 10\%$ | 0402 $\geq 0.1\mu F$; 0603 $\geq 1\mu F$; 0805 $\geq 1\mu F$; 1206 $\geq 2.2\mu F$; 1210 $\geq 10\mu F$; TT series |
| 35V | $\leq 3.5\%$ | $\leq 10\%$ | 0603 $\geq 1\mu F$; 0805 $\geq 2.2\mu F$; 1210 $\geq 10\mu F$ |
| 25V | $\leq 3.5\%$ | $\leq 5\%$ | 0201 $\geq 0.01\mu F$; 0805 $\geq 1\mu F$; 1210 $\geq 10\mu F$ |
| | | $\leq 7\%$ | 0603 $\geq 0.33\mu F$; 1206 $\geq 4.7\mu F$ |
| | | $\leq 10\%$ | 0402 $\geq 0.10\mu F$; 0603 $\geq 0.47\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 6.8\mu F$; 1210 $\geq 22\mu F$; TT series |
| | | $\leq 12.5\%$ | 0402 $\geq 1\mu F$ |
| 16V | $\leq 3.5\%$ | $\leq 5\%$ | 0201 $\geq 0.01\mu F$; 0402 $\geq 0.033\mu F$; 0603 $\geq 0.15\mu F$; 0805 $\geq 0.68\mu F$; 1206 $\geq 2.2\mu F$; 1210 $\geq 4.7\mu F$ |
| | | $\leq 10\%$ | 0201 $\geq 0.1\mu F$; 0402 $\geq 0.22\mu F$; 0603 $\geq 0.68\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 4.7\mu F$; 1210 $\geq 22\mu F$; TT series |
| 10V | $\leq 5\%$ | $\leq 10\%$ | 0201 $\geq 0.012\mu F$; 0402 $\geq 0.33\mu F$ (0402/X7R $\geq 0.22\mu F$); TT series 0603 $\geq 0.33\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 2.2\mu F$; 1210 $\geq 22\mu F$ |
| | | $\leq 15\%$ | 0201 $\geq 0.1\mu F$; 0402 $\geq 1\mu F$ |
| 6.3V | $\leq 10\%$ | $\leq 15\%$ | 0201 $\geq 0.1\mu F$; 0402 $\geq 1\mu F$; 0603 $\geq 10\mu F$; 0805 $\geq 4.7\mu F$; 1206 $\geq 47\mu F$; 1210 $\geq 100\mu F$; TT series |
| | | $\leq 20\%$ | 0402 $\geq 2.2\mu F$ |
| 4V | $\leq 15\%$ | --- | --- |

Y5V

| Rated vol. | D.F. \leq | Exception of D.F. \leq | |
|--------------------------|-------------|--------------------------|---|
| $\geq 50V$ | 5% | 7% | 0603 $\geq 0.1\mu F$; 0805 $\geq 0.47\mu F$; 1206 $\geq 4.7\mu F$ |
| 35V | 7% | --- | --- |
| 25V | 5% | 7% | 0402 $\geq 0.047\mu F$; 0603 $\geq 0.1\mu F$; 0805 $\geq 0.33\mu F$; 1206 $\geq 1\mu F$; 1210 $\geq 4.7\mu F$ |
| | | 9% | 0402 $\geq 0.068\mu F$; 0603 $\geq 0.47\mu F$; 1206 $\geq 4.7\mu F$; 1210 $\geq 22\mu F$ |
| 16V (C < 1.0 μF) | 7% | 9% | 0402 $\geq 0.068\mu F$; 0603 $\geq 0.68\mu F$ |
| | | 12.5% | 0402 $\geq 0.22\mu F$ |
| 16V (C $\geq 1.0\mu F$) | 9% | 12.5% | 0603 $\geq 2.2\mu F$; 0805 $\geq 3.3\mu F$; 1206 $\geq 10\mu F$; 1210 $\geq 22\mu F$; 1812 $\geq 47\mu F$ |
| 10V | 12.5% | 20% | 0402 $\geq 0.47\mu F$ |
| 6.3V | 20% | --- | --- |

**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NP0, X5R, X7R & Y5V Dielectrics)**



Capacitance Range

NP0 Dielectric 0201, 0402, 0603, 0805 Sizes

| Dielectric | | NP0 | | | | | | | | | | | | | | | | | |
|----------------------|-------------|------|----|----|------|----|----|----|-----|------|----|----|----|-----|------|----|----|----|-----|
| Size | | 0201 | | | 0402 | | | | | 0603 | | | | | 0805 | | | | |
| Rated Voltage (V DC) | | 16 | 25 | 50 | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 0.1pF (0R1) | L | L | L | N | N | N | N | | | | | | | | | | | |
| | 0.2pF (0R2) | L | L | L | N | N | N | N | | | | | | | | | | | |
| | 0.3pF (0R3) | L | L | L | N | N | N | N | | | | | | | | | | | |
| | 0.4pF (0R4) | L | L | L | N | N | N | N | | | | | | | | | | | |
| | 0.5pF (0R5) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 0.6pF (0R6) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 0.7pF (0R7) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 0.8pF (0R8) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 0.9pF (0R9) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 1.0pF (1R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 1.2pF (1R2) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 1.5pF (1R5) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 1.8pF (1R8) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 2.0pF (2R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 2.2pF (2R2) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 2.7pF (2R7) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 3.0pF (3R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 3.3pF (3R3) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 3.9pF (3R9) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 4.0pF (4R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 4.7pF (4R7) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 5.0pF (5R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 5.6pF (5R6) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 6.0pF (6R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 6.8pF (6R8) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 7.0pF (7R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 8.0pF (8R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 8.2pF (8R2) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| 9.0pF (9R0) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 10pF (100) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 12pF (120) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 15pF (150) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 18pF (180) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 22pF (220) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 27pF (270) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 33pF (330) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 39pF (390) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 47pF (470) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |
| 56pF (560) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A | |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| Dielectric | | NPO | | | | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|------|----|----|----|-----|------|----|----|----|-----|------|----|----|----|-----|
| Size | | 0201 | | | 0402 | | | | | 0603 | | | | | 0805 | | | | |
| Rated Voltage (V DC) | | 16 | 25 | 50 | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 68pF (680) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 82pF (820) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 100pF (101) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 120pF (121) | L | L | L | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 150pF (151) | | | | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 180pF (181) | | | | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 220pF (221) | | | | N | N | N | N | N | S | S | S | S | S | A | A | A | A | A |
| | 270pF (271) | | | | N | N | N | N | | S | S | S | S | S | A | A | A | A | A |
| | 330pF (331) | | | | N | N | N | N | | S | S | S | S | S | A | A | A | A | A |
| | 390pF (391) | | | | N | N | N | N | | S | S | S | S | S | B | B | B | B | B |
| | 470pF (471) | | | | N | N | N | N | | S | S | S | S | S | B | B | B | B | B |
| | 560pF (561) | | | | N | N | N | N | | S | S | S | S | S | B | B | B | B | B |
| | 680pF (681) | | | | N | N | N | N | | S | S | S | S | S | B | B | B | B | B |
| | 820pF (821) | | | | N | N | N | N | | S | S | S | S | S | B | B | B | B | B |
| | 1,000pF (102) | | | | N | N | N | N | | S | S | S | S | S | B | B | B | B | B |
| | 1,200pF (122) | | | | | | | | | X | X | X | X | X | B | B | B | B | B |
| | 1,500pF (152) | | | | | | | | | X | X | X | X | X | B | B | B | B | B |
| | 1,800pF (182) | | | | | | | | | X | X | X | X | | B | B | B | B | B |
| | 2,200pF (222) | | | | | | | | | X | X | X | X | | B | B | B | B | B |
| | 2,700pF (272) | | | | | | | | | X | X | X | X | | D | D | D | D | D |
| | 3,300pF (332) | | | | | | | | | X | X | X | X | | D | D | D | D | D |
| | 3,900pF (392) | | | | | | | | | X | X | X | X | | D | D | D | D | D |
| | 4,700pF (472) | | | | | | | | | X | X | X | X | | D | D | D | D | D |
| | 5,600pF (562) | | | | | | | | | X | X | X | X | | D | D | D | D | D |
| | 6,800pF (682) | | | | | | | | | X | X | X | X | | D | D | D | D | D |
| | 8,200pF (822) | | | | | | | | | X | X | X | X | | D | D | D | D | |
| 0.010uF (103) | | | | | | | | | X | X | X | X | | D | D | D | D | | |
| 0.012uF (123) | | | | | | | | | | | | | | T | T | T | T | | |
| 0.018uF (183) | | | | | | | | | | | | | | D | D | D | D | | |
| 0.022uF (223) | | | | | | | | | | | | | | D | D | D | D | | |

1. The letter in cell is expressed the symbol of product thickness.

NPO Dielectric 1206, 1210, 1812 Sizes

| Dielectric | | NPO | | | | | | | | | | | | |
|----------------------|-------------|------|----|----|----|-----|------|----|----|----|-----|------|----|-----|
| Size | | 1206 | | | | | 1210 | | | | | 1812 | | |
| Rated Voltage (V DC) | | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 | 16 | 50 | 100 |
| Capacitance | 1.0pF (1R0) | | | | | | | | | | | | | |
| | 1.2pF (1R2) | B | B | B | B | B | | | | | | | | |
| | 1.5pF (1R5) | B | B | B | B | B | | | | | | | | |
| | 1.8pF (1R8) | B | B | B | B | B | | | | | | | | |
| | 2.2pF (2R2) | B | B | B | B | B | | | | | | | | |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| Dielectric | | NPO | | | | | | | | | | | | |
|----------------------|-------------|------|----|----|----|-----|------|----|----|----|-----|------|----|-----|
| Size | | 1206 | | | | | 1210 | | | | | 1812 | | |
| Rated Voltage (V DC) | | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 | 16 | 50 | 100 |
| Capacitance | 2.7pF (2R7) | B | B | B | B | B | | | | | | | | |
| | 3.3pF (3R3) | B | B | B | B | B | | | | | | | | |
| | 3.9pF (3R9) | B | B | B | B | B | | | | | | | | |
| | 4.7pF (4R7) | B | B | B | B | B | | | | | | | | |
| | 5.6pF (5R6) | B | B | B | B | B | | | | | | | | |
| | 6.8pF (6R8) | B | B | B | B | B | | | | | | | | |
| | 8.2pF (8R2) | B | B | B | B | B | | | | | | | | |
| | 10pF (100) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 12pF (120) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 15pF (150) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 18pF (180) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 22pF (220) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 27pF (270) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 33pF (330) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 39pF (390) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 47pF (470) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 56pF (560) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 68pF (680) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 82pF (820) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 100pF (101) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 120pF (121) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 150pF (151) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 180pF (181) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 220pF (221) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 270pF (271) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 330pF (331) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 390pF (391) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 470pF (471) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 560pF (561) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| | 680pF (681) | B | B | B | B | B | C | C | C | C | C | D | D | D |
| 820pF (821) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 1,000pF (102) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 1,200pF (122) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 1,500pF (152) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 1,800pF (182) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 2,200pF (222) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 2,700pF (272) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 3,300pF (332) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 3,900pF (392) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 4,700pF (472) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 5,600pF (562) | B | B | B | B | B | C | C | C | C | C | D | D | D | |
| 6,800pF (682) | C | C | C | C | C | C | C | C | C | C | D | D | D | |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| Dielectric | | NPO | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|----|-----|------|----|----|----|-----|------|----|-----|---|--|
| Size | | 1206 | | | | | 1210 | | | | | 1812 | | | | |
| Rated Voltage (V DC) | | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 | 16 | 50 | 100 | | |
| Capacitance | 8,200pF (822) | D | D | D | D | D | C | C | C | C | C | C | D | D | D | |
| | 0.010µF (103) | D | D | D | D | D | C | C | C | C | C | C | D | D | D | |
| | 0.012µF (123) | T | T | T | T | T | D | D | D | D | D | D | D | D | D | |
| | 0.015µF (153) | T | T | T | T | T | D | D | D | D | D | D | D | D | D | |
| | 0.018µF (183) | T | T | T | T | T | | | | | | D | D | D | | |
| | 0.022µF (223) | T | T | T | T | T | | | | | | D | D | D | | |
| | 0.027µF (273) | T | T | T | T | | | | | | | D | D | D | | |
| | 0.033µF (333) | T | T | T | T | | | | | | | D | D | D | | |
| | 0.039µF (393) | J | J | J | J | | | | | | | | | | | |
| | 0.047µF (473) | J | J | J | J | | | | | | | | | | | |
| | 0.056µF (563) | J | J | J | J | | | | | | | | | | | |
| | 0.068µF (683) | G | G | G | G | | | | | | | | | | | |
| | 0.082µF (823) | G | G | G | G | | | | | | | | | | | |
| | 0.1µF (104) | G | G | G | G | | | | | | | | | | | |

1. The letter in cell is expressed the symbol of product thickness.

X7R Dielectric 0201, 0402, 0603, 0805 Sizes

| Dielectric | | X7R | | | | | | | | | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|----|----|------|----|----|----|----|------|-----|----|----|----|------|-----|-----|----|----|----|----|-----|
| Size | | 0201 | | | | | 0402 | | | | | 0603 | | | | | 0805 | | | | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 100 | 6.3 | 10 | 16 | 25 | 50 | 100 | 6.3 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 100pF (101) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 120pF (121) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 150pF (151) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 180pF (181) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 220pF (221) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 270pF (271) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 330pF (331) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 390pF (391) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 470pF (471) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 560pF (561) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 680pF (681) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 820pF (821) | | | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 1,000pF (102) | L | L | L | L | L | | N | N | N | N | N | | S | S | S | S | S | | B | B | B | B | B |
| | 1,200pF (122) | L | L | L | L | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B |
| | 1,500pF (152) | L | L | L | L | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B |
| | 1,800pF (182) | L | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B |
| | 2,200pF (222) | L | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B |
| | 2,700pF (272) | L | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B |
| 3,300pF (332) | L | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B | |
| 3,900pF (392) | L | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B | |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| Dielectric | | X7R | | | | | | | | | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|----|----|------|----|----|----|----|------|-----|----|----|----|------|-----|-----|----|----|----|----|-----|
| Size | | 0201 | | | | | 0402 | | | | | 0603 | | | | | 0805 | | | | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 100 | 6.3 | 10 | 16 | 25 | 50 | 100 | 6.3 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 4,700pF (472) | L | L | L | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B | |
| | 5,600pF (562) | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B | |
| | 6,800pF (682) | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B | |
| | 8,200pF (822) | L | L | | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B | |
| | 0.010µF (103) | L | L | L | | | N | N | N | N | | | S | S | S | S | S | | B | B | B | B | B | |
| | 0.012µF (123) | | | | | | N | N | N | | | | S | S | S | S | X | | B | B | B | B | B | |
| | 0.015µF (153) | | | | | | N | N | N | | | | S | S | S | S | X | | B | B | B | B | B | |
| | 0.018µF (183) | | | | | | N | N | N | | | | S | S | S | S | X | | B | B | B | B | B | |
| | 0.022µF (223) | | | | | | N | N | N | N | | | S | S | S | S | X | | B | B | B | B | B | |
| | 0.027µF (273) | | | | | | N | N | N | | | | S | S | S | S | X | | B | B | B | B | D | |
| | 0.033µF (333) | | | | | | N | N | N | N | | | S | S | S | X | X | | B | B | B | B | D | |
| | 0.039µF (393) | | | | | | N | N | N | | | | S | S | S | X | X | | B | B | B | B | D | |
| | 0.047µF (473) | | | | | | N | N | N | N | | | S | S | S | X | X | | B | B | B | B | D | |
| | 0.056µF (563) | | | | | | N | N | | | | | S | S | S | X | X | | B | B | B | B | D | |
| | 0.068µF (683) | | | | | | N | N | | N | | | S | S | S | X | X | | B | B | B | B | D | |
| | 0.082µF (823) | | | | | | N | N | | | | | S | S | S | X | X | | B | B | B | B | D | |
| | 0.10µF (104) | | | | | | N | N | N | N | N | | S | S | S | X | X | | B | B | B | B | D | |
| | 0.12µF (124) | | | | | | | | | | | | S | S | X | | | | B | B | B | D | | |
| | 0.15µF (154) | | | | | | | | | | | | S | S | X | | | | D | D | D | D | | |
| | 0.18µF (184) | | | | | | | | | | | | S | S | X | | | | D | D | D | D | | |
| | 0.22µF (224) | | | | | | N | N | N | N | | | S | S | X | X | | | D | D | D | D | T | |
| | 0.27µF (274) | | | | | | | | | | | | X | X | X | X | | | D | D | D | I | | |
| | 0.33µF (334) | | | | | | | | | | | | X | X | X | X | | | D | D | D | I | | |
| | 0.39µF (394) | | | | | | | | | | | | X | X | X | X | | | D | D | D | I | | |
| | 0.47µF (474) | | | | | | N | N | | | | | X | X | X | X | X | | D | D | D | I | I | |
| | 0.56µF (564) | | | | | | | | | | | | X | X | X | | | | D | D | D | | | |
| | 0.68µF (684) | | | | | | | | | | | | X | X | X | | | | D | D | D | | | |
| | 0.82µF (824) | | | | | | | | | | | | X | X | X | | | | D | D | D | | | |
| | 1.0µF (105) | | | | | | N | | | | | | X | X | X | X | X | | D | D | D | I | | |
| | 1.5µF (155) | | | | | | | | | | | | | | | | | | I | I | I | | | |
| 2.2µF (225) | | | | | | | | | | | | X | X | | | | | I | I | I | I | I | | |
| 3.3µF (335) | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7µF (475) | | | | | | | | | | | | | | | | | | I | I | I | I | | | |
| 6.8µF (685) | | | | | | | | | | | | | | | | | | | | | | | | |
| 10µF (106) | | | | | | | | | | | | | | | | | | I | I | I* | | | | |
| 22µF (226) | | | | | | | | | | | | | | | | | | | | | | | | |

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with " * " mark is expressed product not in 10% (code "K") tolerance.



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



X7R Dielectric 1206, 1210, 1812 Sizes

| Dielectric | | X7R | | | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|----|----|------|-----|----|----|----|------|-----|----|----|----|----|-----|
| Size | | 1206 | | | | | 1210 | | | | | 1812 | | | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 100 | 6.3 | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 100pF (101) | | | | | | | | | | | | | | | | | |
| | 120pF (121) | | | | | | | | | | | | | | | | | |
| | 150pF (151) | | B | B | B | B | B | | | | | | | | | | | |
| | 180pF (181) | | B | B | B | B | B | | | | | | | | | | | |
| | 220pF (221) | | B | B | B | B | B | | | | | | | | | | | |
| | 270pF (271) | | B | B | B | B | B | | | | | | | | | | | |
| | 330pF (331) | | B | B | B | B | B | | | | | | | | | | | |
| | 390pF (391) | | B | B | B | B | B | | | | | | | | | | | |
| | 470pF (471) | | B | B | B | B | B | | | | | | | | | | | |
| | 560pF (561) | | B | B | B | B | B | | | | | | | | | | | |
| | 680pF (681) | | B | B | B | B | B | | | | | | | | | | | |
| | 820pF (821) | | B | B | B | B | B | | | | | | | | | | | |
| | 1,000pF (102) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 1,200pF (122) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 1,500pF (152) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 1,800pF (182) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 2,200pF (222) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 2,700pF (272) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 3,300pF (332) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 3,900pF (392) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 4,700pF (472) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 5,600pF (562) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 6,800pF (682) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 8,200pF (822) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.010µF (103) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.012µF (123) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.015µF (153) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.018µF (183) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.022µF (223) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.027µF (273) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.033µF (333) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.039µF (393) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.047µF (473) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| 0.056µF (563) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D | |
| 0.068µF (683) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D | |
| 0.082µF (823) | | B | B | B | B | D | | C | C | C | C | C | D | D | D | D | D | |
| 0.10µF (104) | | B | B | B | B | D | | C | C | C | C | C | D | D | D | D | D | |
| 0.12µF (124) | | B | B | B | B | D | | C | C | C | C | C | D | D | D | D | D | |
| 0.15µF (154) | | C | C | C | C | G | | C | C | C | C | D | D | D | D | D | D | |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| Dielectric | | X7R | | | | | | | | | | | | | | | | |
|----------------------|--------------|------|----|----|----|----|------|-----|----|----|----|------|-----|----|----|----|----|-----|
| Size | | 1206 | | | | | 1210 | | | | | 1812 | | | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 100 | 6.3 | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 0.18µF (184) | | C | C | C | C | G | | C | C | C | C | D | D | D | D | D | D |
| | 0.22µF (224) | | C | C | C | C | G | | C | C | C | C | D | D | D | D | D | D |
| | 0.27µF (274) | | C | C | C | D | G | | C | C | C | C | G | D | D | D | D | D |
| | 0.33µF (334) | | C | C | C | D | G | | C | C | C | D | G | D | D | D | D | D |
| | 0.39µF (394) | | C | C | J | P | G | | C | C | C | D | M | D | D | D | D | D |
| | 0.47µF (474) | | J | J | J | P | G | | C | C | C | D | M | D | D | D | D | K |
| | 0.56µF (564) | | J | J | J | P | P | | D | D | D | D | M | D | D | D | D | K |
| | 0.68µF (684) | | J | J | J | P | P | | D | D | D | D | K | D | D | D | K | K |
| | 0.82µF (824) | | J | J | J | P | P | | D | D | D | D | K | D | D | D | K | K |
| | 1.0µF (105) | | J | J | J | P | P | | D | D | D | D | K | D | D | D | K | K |
| | 1.5µF (155) | J | J | J | P | | | | | K | G | M | M | | | | | K |
| | 2.2µF (225) | J | J | J | P | P | P | | | K | G | M | M | | | | M | M |
| | 3.3µF (335) | | P | P | P | | | | | K | G | | | | | | | |
| | 4.7µF (475) | P | P | P | P | P | | | | K | K | K | M | | | | | |
| | 6.8µF (685) | | | | | | | | | | | | | | | | | |
| | 10µF (106) | P | P | P | P | | | | | K | K | K | M | | | | | |
| | 22µF (226) | P | P | P* | | | | | | M | M | M | | | | | | |
| | 47µF (476) | | | | | | | | M | M | | | | | | | | |
| 100µF (107) | | | | | | | | | | | | | | | | | | |

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with “ * ” mark is expressed product not in 10% (code “K”) tolerance.

Y5V Dielectric 0402, 0603, 0805 Sizes

| Dielectric | | Y5V | | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|----|------|-----|----|----|----|------|-----|----|----|----|----|-----|
| Size | | 0402 | | | | 0603 | | | | | 0805 | | | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 0.010µF (103) | | N | N | N | N | | S | S | S | S | | A | A | A | A | B |
| | 0.015µF (153) | | N | N | N | N | | S | S | S | S | | A | A | A | A | B |
| | 0.022µF (223) | | N | N | N | N | | S | S | S | S | | A | A | A | A | B |
| | 0.033µF (333) | | N | N | N | N | | S | S | S | S | | A | A | A | A | B |
| | 0.047µF (473) | | N | N | N | | | S | S | S | S | | A | A | A | A | B |
| | 0.068µF (683) | | N | N | N | | | S | S | S | S | | A | A | A | A | B |
| | 0.10µF (104) | | N | N | N | | | S | S | S | S | | A | A | A | A | B |
| | 0.15µF (154) | | N | N | | | | S | S | S | S | | A | A | A | A | |
| | 0.22µF (224) | N | N | N | | | | S | S | S | S | | A | A | A | A | |
| | 0.33µF (334) | N | N | N | | | | S | S | S | X | | B | B | B | B | |
| | 0.47µF (474) | N | N | N | | | | S | S | X | X | | B | B | B | B | |
| | 0.68µF (684) | N | | | | | | S | X | X | | | B | B | D | D | |
| | 1.0µF (105) | N | N | | | | | S | X | X | | | B | B | D | D | |
| | 1.5µF (155) | | | | | | | S | | | | | D | D | | | |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| Dielectric | | Y5V | | | | | | | | | | | | | | | |
|----------------------|-------------|------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|-----|
| Size | | 0402 | | | | | 0603 | | | | | 0805 | | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 2.2μF (225) | | | | | | S | S | X | | | | D | D | I | | |
| | 3.3μF (335) | | | | | | | | | | | | D | D | | | |
| | 4.7μF (475) | | | | | | X | X | | | | | D | D | I | | |
| | 6.8μF (685) | | | | | | | | | | | | I | | | | |
| | 10μF (106) | | | | | | | | | | | I | I | I | | | |
| | 22μF (226) | | | | | | | | | | | I | I | | | | |

1. The letter in cell is expressed the symbol of product thickness.

Y5V Dielectric 1206, 1210, 1812 Sizes

| Dielectric | | Y5V | | | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|----|----|------|-----|----|----|----|------|-----|----|----|----|----|-----|
| Size | | 1206 | | | | | 1210 | | | | | 1812 | | | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 100 | 6.3 | 10 | 16 | 25 | 50 | 100 | 10 | 16 | 25 | 50 | 100 |
| Capacitance | 0.010μF (103) | | B | B | B | B | B | | | | | | | | | | | D |
| | 0.015μF (153) | | B | B | B | B | B | | | | | | | | | | | D |
| | 0.022μF (223) | | B | B | B | B | B | | | | | | | | | | | D |
| | 0.033μF (333) | | B | B | B | B | B | | | | | | | | | | | D |
| | 0.047μF (473) | | B | B | B | B | B | | | | | | | | | | | D |
| | 0.068μF (683) | | B | B | B | B | B | | | | | | | | | | | D |
| | 0.10μF (104) | | B | B | B | B | B | | C | C | C | C | C | D | D | D | D | D |
| | 0.15μF (154) | | B | B | B | B | C | | C | C | C | C | C | D | D | D | D | D |
| | 0.22μF (224) | | B | B | B | B | C | | C | C | C | C | C | D | D | D | D | D |
| | 0.33μF (334) | | B | B | B | B | | | C | C | C | C | C | D | D | D | D | D |
| | 0.47μF (474) | | B | B | B | B | | | C | C | C | C | | D | D | D | D | D |
| | 0.68μF (684) | | B | B | B | B | | | C | C | C | C | | D | D | D | D | D |
| | 1.0μF (105) | | C | C | C | C | | | C | C | C | C | | D | D | D | D | D |
| | 1.5μF (155) | | C | C | C | | | | C | C | C | | | D | D | D | D | |
| | 2.2μF (225) | | C | C | C | J | | | C | C | C | G | | D | D | D | D | |
| | 3.3μF (335) | | J | J | J | | | | C | C | C | | | D | D | D | D | |
| | 4.7μF (475) | | J | J | J | P | | | C | C | D | G | | D | D | D | D | |
| | 6.8μF (685) | | J | J | | | | | C | C | D | | | D | D | D | D | |
| | 10μF (106) | | J | J | P | | | | D | D | G | | | D | D | D | K | |
| | 22μF (226) | | P | P | | | | | K | K | | | | | | | | |
| 47μF (476) | P | | | | | | K | K | | | | | | M | | | | |
| 100μF (107) | | | | | | | M | | | | | | | | | | | |

1. The letter in cell is expressed the symbol of product thickness.



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



X5R Dielectric 0201, 0402, 0603, 0805, 1206, 1210 Sizes

| Dielectric | | X5R | | | | | | | | | | | | | | |
|----------------------|---------------|------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|
| Size | | 0201 | | | | | 0402 | | | | | 0603 | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 |
| Capacitance | 100pF (101) | | | L | L | L | | | | | | | | | | |
| | 120pF (121) | | | L | L | L | | | | | | | | | | |
| | 150pF (151) | | | L | L | L | | | | | | | | | | |
| | 180pF (181) | | | L | L | L | | | | | | | | | | |
| | 220pF (221) | | | L | L | L | | | | | | | | | | |
| | 270pF (271) | | | L | L | L | | | | | | | | | | |
| | 330pF (331) | | | L | L | L | | | | | | | | | | |
| | 390pF (391) | | | L | L | L | | | | | | | | | | |
| | 470pF (471) | | | L | L | L | | | | | | | | | | |
| | 560pF (561) | | | L | L | L | | | | | | | | | | |
| | 680pF (681) | | | L | L | L | | | | | | | | | | |
| | 820pF (821) | | | L | L | L | | | | | | | | | | |
| | 1,000pF (102) | | L | L | L | L | | | | | | | | | | |
| | 1,500pF (152) | | L | L | | | | | | | | | | | | |
| | 2,200pF (222) | | L | L | | | | | | | | | | | | |
| | 2,700pF (272) | | L | L | | | | | | | | | | | | |
| | 3,300pF (332) | | L | L | | | | | | | | | | | | |
| | 4,700pF (472) | | L | L | | | | | | | | | | | | |
| | 6,800pF (682) | | L | | | | | | | | | | | | | |
| | 0.010µF (103) | L | L | L | L | | | | | | | | | | | |
| | 0.015µF (153) | L | L | | | | | | | | | | | | | |
| | 0.022µF (223) | L | L | | | | | | | | | | | | | |
| | 0.027µF (273) | L | L | | | | | | N | | | | | | | |
| | 0.033µF (333) | L | L | | | | | | N | | | | | | | |
| | 0.039µF (393) | L | L | | | | | | N | | | | | | | |
| | 0.047µF (473) | L | L | | | | | | N | | | | | | | |
| | 0.056µF (563) | L | L | | | | | N | N | | | | | | | |
| | 0.068µF (683) | L | L | | | | | N | N | | | | | | | |
| | 0.082µF (823) | L | L | | | | N | N | N | | | | | | | |
| | 0.10µF (104) | L | L | L | L | | N | N | N | N | N | | | | | |
| | 0.15µF (154) | | | | | | N | N | N | N | | | | | | |
| | 0.22µF (224) | L | L | | | | N | N | N | N | N | | | X | X | |
| | 0.27µF (274) | | | | | | | | | | | X | X | X | X | |
| | 0.33µF (334) | | | | | | N | N | | | | X | X | X | X | |
| | 0.39µF (394) | | | | | | | | | | | X | X | X | | |
| 0.47µF (474) | L | | | | | N | N | E | E | E | X | X | X | X | X | |
| 0.68µF (684) | | | | | | N | N | | | | X | X | X | X | | |
| 0.82µF (824) | | | | | | | | | | | X | X | X | | | |
| 1.0µF (105) | L | L* | | | | N | N | N | N | | X | X | X | | X | |
| 1.5µF (155) | | | | | | | | | | | X | | | | | |
| 2.2µF (225) | L* | | | | | N | N | E* | E | | X | X | X | X | X | |
| 3.3µF (335) | | | | | | | | | | | X | X | | | | |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| Dielectric | | X5R | | | | | | | | | | | | | | |
|----------------------|-------------|------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|
| Size | | 0201 | | | | | 0402 | | | | | 0603 | | | | |
| Rated Voltage (V DC) | | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 |
| Capacitance | 4.7µF (475) | | | | | | E* | E* | | | | X | X | X | X | |
| | 6.8µF (685) | | | | | | | | | | | | | | | |
| | 10µF (106) | | | | | | E* | E* | | | | X | X | X | X* | |
| | 22µF (226) | | | | | | | | | | | X* | X* | | | |

| Dielectric | | X5R | | | | | | | | | | | | | | | | |
|----------------------|-------------|------|-----|----|----|----|------|-----|----|----|----|------|----|-----|----|----|----|----|
| Size | | 1206 | | | | | 1210 | | | | | 1812 | | | | | | |
| Rated Voltage (V DC) | | 4 | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 4 | 6.3 | 10 | 16 | 25 | 50 |
| Capacitance | 1.0µF (105) | | | D | D | D | I | | | | | | | | | | | |
| | 1.5µF (155) | | I | I | I | I | | | J | J | | | | | K | K | | |
| | 2.2µF (225) | | I | I | I | I | I | | J | J | P | P | | | K | K | | |
| | 3.3µF (335) | | I | I | I | I | | | P | P | P | | | | | | | |
| | 4.7µF (475) | | I | I | I | I | I | P | P | P | P | P | | | K | K | K | |
| | 6.8µF (685) | | | | | | | P | P | | | | | | | | | |
| | 10µF (106) | | I | I | I | I | I | P | P | P | P | P | | K | K | K | K | M |
| | 22µF (226) | | I* | I* | I* | | | P | P | P | P | | | M | M | M | M | |
| | 47µF (476) | | I* | I* | | | | P | P | | | | | M | M | M | | |
| | 100µF (107) | I* | | | | | | P* | | | | | | M* | M* | | | |
| | 220µF (227) | | | | | | | | | | | | M* | | | | | |

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with " * " mark is expressed product not in 10% (code "K") tolerance.

X6S Dielectric 0201, 0402, 0603, 0805, 1206, 1210 Sizes

| Dielectric | | X6S | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------|--------------|------|-----|------|----|----|------|----|-----|------|----|----|----|-----|------|----|----|----|-----|------|----|----|----|-----|----|----|----|----|--|
| Size | | 0201 | | 0402 | | | 0603 | | | 0805 | | | | | 1206 | | | | | 1210 | | | | | | | | | |
| Rated Voltage (V DC) | | 4 | 6.3 | 6.3 | 10 | 16 | 25 | 4 | 6.3 | 10 | 16 | 25 | 4 | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | 6.3 | 10 | 16 | 25 | 50 | |
| Capacitance | 0.10µF (104) | L | L | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0.15µF (154) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0.22µF (224) | | L | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0.33µF (334) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0.47µF (474) | | | N | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0.68µF (684) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1.0µF (105) | L* | | N | E | E | E | | | | | | | | | | | | | | | | | | | | | | |
| | 1.5µF (155) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2.2µF (225) | | | N | E | E | | | | | X | | | | | | | | | | | | | | | | | | |
| | 3.3µF (335) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 4.7µF (475) | | | | | | | | X | | X | X | | | | | | I | I | | | | | | | | | | |
| | 6.8µF (685) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10µF (106) | | | | | | | | X* | X* | X* | | I | I | I | I | I | | | | | G | | | | | | | |
| 22µF (226) | | | | | | | X* | X* | | | | | I* | I* | I* | | | | P | P* | | | | | | M | | | |
| 47µF (476) | | | | | | | | | | | | I* | | | | | | | P | | | M | M | M | | | | | |
| 100µF (107) | | | | | | | | | | | | | | | | | | | | | | M* | | | | | | | |

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with " * " mark is expressed product not in 10% (code "K") tolerance.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



Packaging Dimension And Quantity:

| Size | Thickness (mm)/Symbol | | Paper tape | | Plastic tape | |
|-------------|-----------------------|---|------------|----------|--------------|----------|
| | | | 7" reel | 13" reel | 7" reel | 13" reel |
| 0201 (0603) | 0.3 ±0.03 | L | 15,000 | 70,000 | - | - |
| | 0.3 ± 0.05 | L | 15,000 | - | - | - |
| | 0.3 ±0.09 | L | 15,000 | - | - | - |
| 0402 (1005) | 0.5 ±0.05 | N | 10,000 | 50,000 | - | - |
| | 0.5 +0.02/-0.05 | Q | 10,000 | 50,000 | - | - |
| | 0.5 ±0.2 | E | 10,000 | - | - | - |
| 0603 (1608) | 0.5 ±0.1 | H | 4,000 | - | - | - |
| | 0.8 ±0.07 | S | 4,000 | 15,000 | - | - |
| | 0.8 +0.15/-0.1 | X | 4,000 | 15,000 | - | - |
| 0805 (2012) | 0.5 ±0.1 | H | 4,000 | 15,000 | - | - |
| | 0.6 ±0.1 | A | 4,000 | 15,000 | - | - |
| | 0.8 ±0.1 | B | 4,000 | 15,000 | - | - |
| | 0.85 ±0.1 | T | 4,000 | 15,000 | - | - |
| | 1.25 ±0.1 | D | - | - | 3,000 | 10,000 |
| | 1.25 ±0.2 | I | - | - | 3,000 | 10,000 |
| 1206 (3216) | 0.8 ±0.1 | B | 4,000 | 15,000 | - | - |
| | 0.85 ±0.1 | T | 4,000 | 15,000 | - | - |
| | 0.95 ±0.1 | C | - | - | 3,000 | 10,000 |
| | 1.15 ±0.15 | J | - | - | 3,000 | 10,000 |
| | 1.25 ±0.1 | D | - | - | 3,000 | 10,000 |
| | 1.6 ±0.2 | G | - | - | 2,000 | 10,000 |
| | 1.6 +0.30/-0.10 | P | - | - | 2,000 | 9,000 |
| 1210 (3225) | 0.85 ±0.1 | T | - | - | 3,000 | 10,000 |
| | 0.95 ±0.1 | C | - | - | 3,000 | 10,000 |
| | 1.25 ±0.1 | D | - | - | 3,000 | 10,000 |
| | 1.6 ±0.2 | G | - | - | 2,000 | - |
| | 2 ±0.2 | K | - | - | 1,000 | 6,000 |
| | 2.5 ±0.3 | M | - | - | 1,000 | 6,000 |
| 1808 (4520) | 1.25 ±0.1 | D | - | - | 2,000 | 10,000 |
| | 1.1 ±0.15 | F | - | - | 2,000 | 10,000 |
| | 1.6 ±0.2 | G | - | - | 2,000 | 8,000 |
| | 2 ±0.2 | K | - | - | 1,000 | 6,000 |
| 1812 (4532) | 1.25 ±0.1 | D | - | - | 1,000 | 5,000 |
| | 1.6 ±0.2 | G | - | - | 1,000 | - |
| | 2 ±0.2 | K | - | - | 1,000 | - |
| | 2.5 ±0.3 | M | - | - | 500 | 3,000 |
| | 2.8 ±0.3 | U | - | - | 500 | - |

Unit : pieces

Reliability Test Conditions And Requirements:

| No | Item | Test Condition | Requirements |
|----|-----------------------|----------------|---|
| 1 | Visual and Mechanical | - | No remarkable defect. Dimensions to conform to individual specification sheet. |

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| No | Item | Test Condition | Requirements | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------------|------------------------------|---|---|------------|-------------|--------------------------|--|-------------|-------------|-----------|--------------------------|-----------|--|------------|-------------|-----------|--|-----------|-------------------------|------------|--|-----|-------------|------------|--|-----|-------------|-----------|---|-----------|---|------------|---|--------------|-----------------------|-----|-------------|-----------|---|------------|--|-----|-----------|------------|--|------------|--|------|------------|------------|---|------------|-------------------------|----|------------|---|---|------------|-------------|--------------------------|--|------------|----|----|--|-----|----|---|---|-----|----|----|--|----|--|-----------------------|----|----|---|-------|--------------------------|----------------------------|----|-------|--|-----|-------|-----|--------------------------|------|-----|---|---|
| 2 | Capacitance | | *Shall not exceed the limits given in the detailed spec. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <p>NPO: Cap\geq30pF, Q\geq1000; Cap$<$30pF, Q\geq400+20C X7R, X5R, X6S:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F. \leq</th> <th colspan="2">Exception of D.F. \leq</th> </tr> </thead> <tbody> <tr> <td rowspan="2">\geq100V</td> <td rowspan="2">\leq2.5%</td> <td>\leq3%</td> <td>1206\geq0.47μF</td> </tr> <tr> <td>\leq5%</td> <td>0805$>$0.1μF, 0603\geq0.068μF, 1206$>$1μF; TT series</td> </tr> <tr> <td rowspan="3">\geq50V</td> <td rowspan="3">\leq2.5%</td> <td>\leq3%</td> <td>0201(50V); 0603\geq0.047μF; 0805\geq0.18μF; 1206\geq0.47μF</td> </tr> <tr> <td>\leq5%</td> <td>1210\geq4.7μF</td> </tr> <tr> <td>\leq10%</td> <td>0402\geq0.1μF; 0603\geq1μF; 0805\geq1μF; 1206\geq4.7μF; 1210\geq10μF TT series</td> </tr> <tr> <td>35V</td> <td>\leq3.5%</td> <td>\leq10%</td> <td>0603\geq1μF; 0805\geq2.2μF; 1210\geq10μF</td> </tr> <tr> <td rowspan="4">25V</td> <td rowspan="4">\leq3.5%</td> <td>\leq5%</td> <td>0201\geq0.01μF; 0805\geq1μF; 1210\geq10μF</td> </tr> <tr> <td>\leq7%</td> <td>0603\geq0.33μF; 1206\geq4.7μF</td> </tr> <tr> <td>\leq10%</td> <td>0402\geq0.10μF; 0603\geq0.47μF; 0805\geq2.2μF; 1206\geq6.8μF; 1210\geq22μF; TT series</td> </tr> <tr> <td>\leq12.5%</td> <td>0402\geq1μF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">\leq3.5%</td> <td>\leq5%</td> <td>0201\geq0.01μF; 0402\geq0.033μF; 0805\geq0.68μF; 1206\geq2.2μF; 1210\geq4.7μF</td> </tr> <tr> <td>\leq10%</td> <td>0201\geq0.1μF; 0402\geq0.47μF; 0603\geq0.68μF; 0805\geq2.2μF; 1206\geq4.7μF; 1210\geq22μF; TT series</td> </tr> <tr> <td rowspan="2">10V</td> <td rowspan="2">\leq5%</td> <td>\leq10%</td> <td>0201\geq0.012μF; 0402\geq0.33μF (0402/X7R\geq0.22μF); TT series 0603\geq0.33μF; 0805\geq2.2μF; 1206\geq2.2μF; 1210\geq22μF</td> </tr> <tr> <td>\leq15%</td> <td>0201\geq0.1μF; 0402\geq1μF</td> </tr> <tr> <td rowspan="2">6.3V</td> <td rowspan="2">\leq10%</td> <td>\leq15%</td> <td>0201\geq0.1μF; 0402\geq1μF; 0603\geq10μF; 0805\geq4.7μF; 1206\geq47μF; 1210\geq100μF; TT series</td> </tr> <tr> <td>\leq20%</td> <td>0402\geq2.2μF</td> </tr> <tr> <td>4V</td> <td>\leq15%</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F. \leq</th> <th colspan="2">Exception of D.F. \leq</th> </tr> </thead> <tbody> <tr> <td>\geq50V</td> <td>5%</td> <td>7%</td> <td>0603\geq0.1μF; 0805\geq0.47μF; 1206\geq4.7μF</td> </tr> <tr> <td>35V</td> <td>7%</td> <td>-</td> <td>-</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">5%</td> <td>7%</td> <td>0402\geq0.047μF; 0603\geq0.1μF; 0805\geq0.33μF; 1206\geq1μF; 1210\geq4.7μF</td> </tr> <tr> <td>9%</td> <td>0402\geq0.068μF; 0603\geq0.47μF; 1206\geq4.7μF; 1210\geq22μF</td> </tr> <tr> <td rowspan="2">16V (C$<$1μF)</td> <td rowspan="2">7%</td> <td>9%</td> <td>0402\geq0.068μF; 0603\geq0.68μF</td> </tr> <tr> <td>12.5%</td> <td>0402\geq0.22μF</td> </tr> <tr> <td>16V (C\geq1.0μF)</td> <td>9%</td> <td>12.5%</td> <td>0603\geq2.2μF; 0805\geq3.3μF; 1206\geq10μF; 1210\geq22μF; 1812\geq47μF</td> </tr> <tr> <td>10V</td> <td>12.5%</td> <td>20%</td> <td>0402\geq0.47μF</td> </tr> <tr> <td>6.3V</td> <td>20%</td> <td>-</td> <td>-</td> </tr> </tbody> </table> | Rated vol. | D.F. \leq | Exception of D.F. \leq | | \geq 100V | \leq 2.5% | \leq 3% | 1206 \geq 0.47 μ F | \leq 5% | 0805 $>$ 0.1 μ F, 0603 \geq 0.068 μ F, 1206 $>$ 1 μ F; TT series | \geq 50V | \leq 2.5% | \leq 3% | 0201(50V); 0603 \geq 0.047 μ F; 0805 \geq 0.18 μ F; 1206 \geq 0.47 μ F | \leq 5% | 1210 \geq 4.7 μ F | \leq 10% | 0402 \geq 0.1 μ F; 0603 \geq 1 μ F; 0805 \geq 1 μ F; 1206 \geq 4.7 μ F; 1210 \geq 10 μ F TT series | 35V | \leq 3.5% | \leq 10% | 0603 \geq 1 μ F; 0805 \geq 2.2 μ F; 1210 \geq 10 μ F | 25V | \leq 3.5% | \leq 5% | 0201 \geq 0.01 μ F; 0805 \geq 1 μ F; 1210 \geq 10 μ F | \leq 7% | 0603 \geq 0.33 μ F; 1206 \geq 4.7 μ F | \leq 10% | 0402 \geq 0.10 μ F; 0603 \geq 0.47 μ F; 0805 \geq 2.2 μ F; 1206 \geq 6.8 μ F; 1210 \geq 22 μ F; TT series | \leq 12.5% | 0402 \geq 1 μ F | 16V | \leq 3.5% | \leq 5% | 0201 \geq 0.01 μ F; 0402 \geq 0.033 μ F; 0805 \geq 0.68 μ F; 1206 \geq 2.2 μ F; 1210 \geq 4.7 μ F | \leq 10% | 0201 \geq 0.1 μ F; 0402 \geq 0.47 μ F; 0603 \geq 0.68 μ F; 0805 \geq 2.2 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F; TT series | 10V | \leq 5% | \leq 10% | 0201 \geq 0.012 μ F; 0402 \geq 0.33 μ F (0402/X7R \geq 0.22 μ F); TT series 0603 \geq 0.33 μ F; 0805 \geq 2.2 μ F; 1206 \geq 2.2 μ F; 1210 \geq 22 μ F | \leq 15% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F | 6.3V | \leq 10% | \leq 15% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F; 0603 \geq 10 μ F; 0805 \geq 4.7 μ F; 1206 \geq 47 μ F; 1210 \geq 100 μ F; TT series | \leq 20% | 0402 \geq 2.2 μ F | 4V | \leq 15% | - | - | Rated vol. | D.F. \leq | Exception of D.F. \leq | | \geq 50V | 5% | 7% | 0603 \geq 0.1 μ F; 0805 \geq 0.47 μ F; 1206 \geq 4.7 μ F | 35V | 7% | - | - | 25V | 5% | 7% | 0402 \geq 0.047 μ F; 0603 \geq 0.1 μ F; 0805 \geq 0.33 μ F; 1206 \geq 1 μ F; 1210 \geq 4.7 μ F | 9% | 0402 \geq 0.068 μ F; 0603 \geq 0.47 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F | 16V (C $<$ 1 μ F) | 7% | 9% | 0402 \geq 0.068 μ F; 0603 \geq 0.68 μ F | 12.5% | 0402 \geq 0.22 μ F | 16V (C \geq 1.0 μ F) | 9% | 12.5% | 0603 \geq 2.2 μ F; 0805 \geq 3.3 μ F; 1206 \geq 10 μ F; 1210 \geq 22 μ F; 1812 \geq 47 μ F | 10V | 12.5% | 20% | 0402 \geq 0.47 μ F | 6.3V | 20% | - | - |
| Rated vol. | D.F. \leq | Exception of D.F. \leq | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \geq 100V | \leq 2.5% | \leq 3% | 1206 \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 5% | 0805 $>$ 0.1 μ F, 0603 \geq 0.068 μ F, 1206 $>$ 1 μ F; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \geq 50V | \leq 2.5% | \leq 3% | 0201(50V); 0603 \geq 0.047 μ F; 0805 \geq 0.18 μ F; 1206 \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 5% | 1210 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 10% | 0402 \geq 0.1 μ F; 0603 \geq 1 μ F; 0805 \geq 1 μ F; 1206 \geq 4.7 μ F; 1210 \geq 10 μ F TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35V | \leq 3.5% | \leq 10% | 0603 \geq 1 μ F; 0805 \geq 2.2 μ F; 1210 \geq 10 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25V | \leq 3.5% | \leq 5% | 0201 \geq 0.01 μ F; 0805 \geq 1 μ F; 1210 \geq 10 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 7% | 0603 \geq 0.33 μ F; 1206 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 10% | 0402 \geq 0.10 μ F; 0603 \geq 0.47 μ F; 0805 \geq 2.2 μ F; 1206 \geq 6.8 μ F; 1210 \geq 22 μ F; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 12.5% | 0402 \geq 1 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V | \leq 3.5% | \leq 5% | 0201 \geq 0.01 μ F; 0402 \geq 0.033 μ F; 0805 \geq 0.68 μ F; 1206 \geq 2.2 μ F; 1210 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 10% | 0201 \geq 0.1 μ F; 0402 \geq 0.47 μ F; 0603 \geq 0.68 μ F; 0805 \geq 2.2 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V | \leq 5% | \leq 10% | 0201 \geq 0.012 μ F; 0402 \geq 0.33 μ F (0402/X7R \geq 0.22 μ F); TT series 0603 \geq 0.33 μ F; 0805 \geq 2.2 μ F; 1206 \geq 2.2 μ F; 1210 \geq 22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 15% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V | \leq 10% | \leq 15% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F; 0603 \geq 10 μ F; 0805 \geq 4.7 μ F; 1206 \geq 47 μ F; 1210 \geq 100 μ F; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 20% | 0402 \geq 2.2 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4V | \leq 15% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rated vol. | D.F. \leq | Exception of D.F. \leq | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \geq 50V | 5% | 7% | 0603 \geq 0.1 μ F; 0805 \geq 0.47 μ F; 1206 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35V | 7% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25V | 5% | 7% | 0402 \geq 0.047 μ F; 0603 \geq 0.1 μ F; 0805 \geq 0.33 μ F; 1206 \geq 1 μ F; 1210 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 9% | 0402 \geq 0.068 μ F; 0603 \geq 0.47 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V (C $<$ 1 μ F) | 7% | 9% | 0402 \geq 0.068 μ F; 0603 \geq 0.68 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 12.5% | 0402 \geq 0.22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V (C \geq 1.0 μ F) | 9% | 12.5% | 0603 \geq 2.2 μ F; 0805 \geq 3.3 μ F; 1206 \geq 10 μ F; 1210 \geq 22 μ F; 1812 \geq 47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V | 12.5% | 20% | 0402 \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V | 20% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Q/ D.F. (Dissipation Factor) | <p>Class I: NPO Cap\leq1000pF 1.0\pm0.2Vrms, 1MHz\pm10% Cap$>$1000pF 1.0\pm0.2Vrms, 1KHz\pm10% Class II: X7R, X5R, X6S, Y5V Cap\leq10μF, 1.0\pm0.2Vrms, 1KHz\pm10% ** Cap$>$10μF, 0.5\pm0.2Vrms, 120Hz\pm20%</p> <p>** Test condition: 0.5\pm0.2Vrms, 1KHz\pm10% X7R: 0603\geq225(10V), 0805=106(6.3V&10V) X5R: 01R5\geq103, 0201\geq224 (6.3V, 10V), 0402\geq475 (6.3V), 0402\geq225(10V), 0603=106 (6.3V, 10V), TT18X \geq475(10V) , TT15X series X6S:0201\geq224 (6.3V), 0402\geq225 (6.3V),</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



**General Purpose Multilayer Ceramic Capacitors
4 to 100V (NPO, X5R, X7R & Y5V Dielectrics)**



| No | Item | Test Condition | Requirements | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|--|--|---------------|-----------------------|-----------|---|--|---|---|--|---|-------------------|---------------|--------------------------------|--|---------------------------|---|--------------------------|--|--|---|-------------------|-----|-------------------|-----|------------------|
| 4 | Dielectric Strength | To apply voltage ($\leq 100V$) 250%. Duration: 1 to 5 sec. Charge and discharge current less than 50mA. | No evidence of damage or flash over during test. | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | Insulation Resistance | To apply rated voltage for max. 120 sec. | <p>10GΩ or $RxC \geq 500\Omega \cdot F$ whichever is smaller. Class II (X7R, X5R, X6S, Y5V)</p> <table border="1"> <thead> <tr> <th>Rated voltage</th> <th>Insulation Resistance</th> </tr> </thead> <tbody> <tr> <td>100V: X7R</td> <td rowspan="7">10G or $RxC \geq 100\Omega \cdot F$ whichever is smaller.</td> </tr> <tr> <td>50V: 0603$\geq 1\mu F$; 0805$\geq 1\mu F$; 1206$\geq 4.7\mu F$; 1210$\geq 4.7\mu F$</td> </tr> <tr> <td>35V: 0805$\geq 2.2\mu F$; 1210$\geq 10\mu F$</td> </tr> <tr> <td>25V: 0402$\geq 1\mu F$; 0603$\geq 2.2\mu F$; 0805$\geq 2.2\mu F$; 1206$\geq 10\mu F$; 1210$\geq 10\mu F$</td> </tr> <tr> <td>16V: 0402$\geq 0.22\mu F$; 0603$\geq 1\mu F$; 0805$\geq 2.2\mu F$; 1206$\geq 10\mu F$; 1210$\geq 47\mu F$</td> </tr> <tr> <td>10V: 0201$\geq 47nF$; 0402$\geq 0.47\mu F$; 0603$\geq 0.47\mu F$; 0805$\geq 2.2\mu F$; 1206$\geq 4.7\mu F$; 1210$\geq 47\mu F$</td> </tr> <tr> <td>6.3V ; 4V</td> </tr> <tr> <td>All X6S items</td> <td rowspan="7">$RxC \geq 50 \Omega \cdot F$.</td> </tr> <tr> <td>50V: 0402$\geq 0.1\mu F$; 0603$\geq 2.2\mu F$; 0805$\geq 10\mu F$; 1206$\geq 10\mu F$</td> </tr> <tr> <td>35V: 0603$\geq 1\mu F$;</td> </tr> <tr> <td>25V: 0201$\geq 0.1\mu F$; 0402$\geq 0.22\mu F$; 0603$\geq 10\mu F$; 1206$\geq 22\mu F$</td> </tr> <tr> <td>16V: 0603$\geq 10\mu F$</td> </tr> <tr> <td>10V: 0201$> 0.1\mu F$; 0603$\geq 10\mu F$; 0805$\geq 47\mu F$</td> </tr> <tr> <td>6.3V: 0201$\geq 0.1\mu F$; 1206$\geq 10\mu F$</td> </tr> <tr> <td>4V: 0603$\geq 22\mu F$; 0805$\geq 47\mu F$</td> </tr> </tbody> </table> | Rated voltage | Insulation Resistance | 100V: X7R | 10G or $RxC \geq 100\Omega \cdot F$ whichever is smaller. | 50V: 0603 $\geq 1\mu F$; 0805 $\geq 1\mu F$; 1206 $\geq 4.7\mu F$; 1210 $\geq 4.7\mu F$ | 35V: 0805 $\geq 2.2\mu F$; 1210 $\geq 10\mu F$ | 25V: 0402 $\geq 1\mu F$; 0603 $\geq 2.2\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 10\mu F$; 1210 $\geq 10\mu F$ | 16V: 0402 $\geq 0.22\mu F$; 0603 $\geq 1\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 10\mu F$; 1210 $\geq 47\mu F$ | 10V: 0201 $\geq 47nF$; 0402 $\geq 0.47\mu F$; 0603 $\geq 0.47\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 4.7\mu F$; 1210 $\geq 47\mu F$ | 6.3V ; 4V | All X6S items | $RxC \geq 50 \Omega \cdot F$. | 50V: 0402 $\geq 0.1\mu F$; 0603 $\geq 2.2\mu F$; 0805 $\geq 10\mu F$; 1206 $\geq 10\mu F$ | 35V: 0603 $\geq 1\mu F$; | 25V: 0201 $\geq 0.1\mu F$; 0402 $\geq 0.22\mu F$; 0603 $\geq 10\mu F$; 1206 $\geq 22\mu F$ | 16V: 0603 $\geq 10\mu F$ | 10V: 0201 $> 0.1\mu F$; 0603 $\geq 10\mu F$; 0805 $\geq 47\mu F$ | 6.3V: 0201 $\geq 0.1\mu F$; 1206 $\geq 10\mu F$ | 4V: 0603 $\geq 22\mu F$; 0805 $\geq 47\mu F$ | | | | | |
| Rated voltage | Insulation Resistance | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100V: X7R | 10G or $RxC \geq 100\Omega \cdot F$ whichever is smaller. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50V: 0603 $\geq 1\mu F$; 0805 $\geq 1\mu F$; 1206 $\geq 4.7\mu F$; 1210 $\geq 4.7\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35V: 0805 $\geq 2.2\mu F$; 1210 $\geq 10\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25V: 0402 $\geq 1\mu F$; 0603 $\geq 2.2\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 10\mu F$; 1210 $\geq 10\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V: 0402 $\geq 0.22\mu F$; 0603 $\geq 1\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 10\mu F$; 1210 $\geq 47\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V: 0201 $\geq 47nF$; 0402 $\geq 0.47\mu F$; 0603 $\geq 0.47\mu F$; 0805 $\geq 2.2\mu F$; 1206 $\geq 4.7\mu F$; 1210 $\geq 47\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V ; 4V | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| All X6S items | $RxC \geq 50 \Omega \cdot F$. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50V: 0402 $\geq 0.1\mu F$; 0603 $\geq 2.2\mu F$; 0805 $\geq 10\mu F$; 1206 $\geq 10\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35V: 0603 $\geq 1\mu F$; | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25V: 0201 $\geq 0.1\mu F$; 0402 $\geq 0.22\mu F$; 0603 $\geq 10\mu F$; 1206 $\geq 22\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V: 0603 $\geq 10\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V: 0201 $> 0.1\mu F$; 0603 $\geq 10\mu F$; 0805 $\geq 47\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V: 0201 $\geq 0.1\mu F$; 1206 $\geq 10\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4V: 0603 $\geq 22\mu F$; 0805 $\geq 47\mu F$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | Temperature Coefficient | With no electrical load. | <table border="1"> <thead> <tr> <th>T.C.</th> <th>Operating Temp</th> <th>T.C.</th> <th>Capacitance Change</th> </tr> </thead> <tbody> <tr> <td>NPO</td> <td>-55~125°C at 25°C</td> <td>NPO</td> <td>Within $\pm 30ppm/^{\circ}C$</td> </tr> <tr> <td>X7R</td> <td>-55~125°C at 25°C</td> <td>X7R</td> <td>Within $\pm 15\%$</td> </tr> <tr> <td>X5R</td> <td>-55~ 85°C at 25°C</td> <td>X5R</td> <td>Within $\pm 15\%$</td> </tr> <tr> <td>X6S</td> <td>-55~105°C at 25°C</td> <td>X6S</td> <td>Within $\pm 22\%$</td> </tr> <tr> <td>Y5V</td> <td>-25~ 85°C at 20°C</td> <td>Y5V</td> <td>Within +30%/-80%</td> </tr> </tbody> </table> | T.C. | Operating Temp | T.C. | Capacitance Change | NPO | -55~125°C at 25°C | NPO | Within $\pm 30ppm/^{\circ}C$ | X7R | -55~125°C at 25°C | X7R | Within $\pm 15\%$ | X5R | -55~ 85°C at 25°C | X5R | Within $\pm 15\%$ | X6S | -55~105°C at 25°C | X6S | Within $\pm 22\%$ | Y5V | -25~ 85°C at 20°C | Y5V | Within +30%/-80% |
| T.C. | Operating Temp | T.C. | Capacitance Change | | | | | | | | | | | | | | | | | | | | | | | | |
| NPO | -55~125°C at 25°C | NPO | Within $\pm 30ppm/^{\circ}C$ | | | | | | | | | | | | | | | | | | | | | | | | |
| X7R | -55~125°C at 25°C | X7R | Within $\pm 15\%$ | | | | | | | | | | | | | | | | | | | | | | | | |
| X5R | -55~ 85°C at 25°C | X5R | Within $\pm 15\%$ | | | | | | | | | | | | | | | | | | | | | | | | |
| X6S | -55~105°C at 25°C | X6S | Within $\pm 22\%$ | | | | | | | | | | | | | | | | | | | | | | | | |
| Y5V | -25~ 85°C at 20°C | Y5V | Within +30%/-80% | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | Adhesive Strength of Termination | Pressurizing force: 1N (0201) and 5N (≤ 0603) and 10N (> 0603) * Test time: 10 \pm 1 sec. | No remarkable damage or removal of the terminations. | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | Vibration Resistance | Vibration frequency: 10~55 Hz/min. Total amplitude: 1.5mm Test time: 6 hrs. (Two hrs each in three mutually perpendicular directions.) Measurement to be made after keeping at room temp. for 24 \pm 2 hrs. | No remarkable damage. Cap change and Q/D.F.: To meet initial spec. | | | | | | | | | | | | | | | | | | | | | | | | |



| No | Item | Test Condition | Requirements | | | | | | | | | | | | | | | |
|------|------------------------------|---|---|------------|-------------|---|----------------------------|------|---|------------|-----|---|----------------------------|------|---|------------|-----|---|
| 9 | Solderability | Solder temperature: 235±5°C Dipping time: 2±0.5 sec. | 95% min. coverage of all metalized area. | | | | | | | | | | | | | | | |
| 10. | Bending Test | The middle part of substrate shall be pressurized by means of the pressurizing rod at a rate of about 1 mm per second until the deflection becomes 1 mm and then the pressure shall be maintained for 5±1 sec. Measurement to be made after keeping at room temp. for 24±2 hrs. | No remarkable damage. Cap change: NP0: within ±5% or 0.5pF whichever is larger X7R, X5R, X6S: within ±12.5% Y5V: within ±30% (This capacitance change means the change of capacitance under specified flexure of substrate from the capacitance measured before the test.) | | | | | | | | | | | | | | | |
| 11 | Resistance to Soldering Heat | Solder temperature: 260±5°C Dipping time: 10±1 sec Preheating: 120 to 150°C for 1 minute before immerse the capacitor in a eutectic solder. Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 24±2 hrs at room temp. Measurement to be made after keeping at room temp. for 24±2 hrs. | No remarkable damage. Cap change: NP0: within ±2.5% or 0.25pF whichever is larger X7R, X5R, X6S: within ±7.5% Y5V: within ±20% Q/D.F., I.R. and dielectric strength: To meet initial requirements. 25% max. leaching on each edge. | | | | | | | | | | | | | | | |
| 12 | Temperature Cycle | Conduct the five cycles according to the temperatures and time. <table border="1" style="margin-left: 20px;"> <thead> <tr> <th>Step</th> <th>Temp. (°C)</th> <th>Time (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Min. operating temp. +0/-3</td> <td>30±3</td> </tr> <tr> <td>2</td> <td>Room temp.</td> <td>2~3</td> </tr> <tr> <td>3</td> <td>Max. operating temp. +3/-0</td> <td>30±3</td> </tr> <tr> <td>4</td> <td>Room temp.</td> <td>2~3</td> </tr> </tbody> </table> Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 24±2 hrs at room temp. Measurement to be made after keeping at room temp. for 24±2 hrs. | Step | Temp. (°C) | Time (min.) | 1 | Min. operating temp. +0/-3 | 30±3 | 2 | Room temp. | 2~3 | 3 | Max. operating temp. +3/-0 | 30±3 | 4 | Room temp. | 2~3 | No remarkable damage. Cap change: NP0: within ±2.5% or 0.25pF whichever is larger X7R, X5R, X6S: within ±7.5% Y5V: within ±20% Q/D.F., I.R. and dielectric strength: To meet initial requirements. |
| Step | Temp. (°C) | Time (min.) | | | | | | | | | | | | | | | | |
| 1 | Min. operating temp. +0/-3 | 30±3 | | | | | | | | | | | | | | | | |
| 2 | Room temp. | 2~3 | | | | | | | | | | | | | | | | |
| 3 | Max. operating temp. +3/-0 | 30±3 | | | | | | | | | | | | | | | | |
| 4 | Room temp. | 2~3 | | | | | | | | | | | | | | | | |

| No | Item | Test Condition | Requirements | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------|---|---|--|------------|---------------------|---|--|-------|-----|-----|-------------|-------|--------------------------|------|-----|-----|--|------|------------|------|--|-----|-----|------|---------------------------------|-----|-----|------|---------------------------------|------|-------------------------|------|---|------|----------|-----|-----|------|--|------|---|-----|-------|------|--|------|--------------------------------|------|------|------|---|----|------|---|---|
| 13 | Humidity (Damp Heat) Steady State | Test temp.: 40±2°C Humidity: 90~95% RH Test time: 500+24/-0hrs. Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 24±2 hrs at room temp. Measurement to be made after keeping at room temp. for 24±2 hrs. | No remarkable damage. Cap change: NP0: within ±5% or 0.5pF whichever is larger X7R, X5R, X6S: ≥10V**, within ±12.5%; ≤6.3V within ±25%; TT series & C ≥ 1uF, within ±25% **10V: 0603≥4.7µF;0402≥1µF;0201≥0.1µF, within ±25%; Y5V: ≥10V, within ±30%; ≤6.3V, within +30/-40% Q/D.F. value: NP0: More than 30pF Q≥350, 10pF≤C≤30pF, Q≥275+2.5C Less than 10pF Q≥200+10C X7R, X5R, X6S: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.≤</th> <th colspan="2">Exception of D.F. ≤</th> </tr> </thead> <tbody> <tr> <td rowspan="2">≥100V</td> <td rowspan="2">≤3%</td> <td>≤6%</td> <td>1206≥0.47µF</td> </tr> <tr> <td>≤7.5%</td> <td>0805>0.1µF, 0603≥0.068µF</td> </tr> <tr> <td rowspan="3">≥50V</td> <td rowspan="3">≤3%</td> <td>≤6%</td> <td>0201(50V); 0603≥0.047µF; 0805≥0.18µF;1206≥0.47µF</td> </tr> <tr> <td>≤10%</td> <td>1210≥4.7µF</td> </tr> <tr> <td>≤20%</td> <td>0402≥0.1µF; 0603≥1µF; 0805≥1µF;1206≥4.7µF; 1210≥10µF TT series</td> </tr> <tr> <td>35V</td> <td>≤5%</td> <td>≤20%</td> <td>0603≥1µF; 0805≥2.2µF; 1210≥10µF</td> </tr> <tr> <td rowspan="4">25V</td> <td rowspan="4">≤5%</td> <td>≤10%</td> <td>0201≥0.01µF;0805≥1µF; 1210≥10µF</td> </tr> <tr> <td>≤14%</td> <td>0603≥0.33µF; 1206≥4.7µF</td> </tr> <tr> <td>≤15%</td> <td>0402≥0.10µF;0603≥0.47µF;0805≥2.2µF; 1206≥6.8µF ; 1210≥22µF; TT series</td> </tr> <tr> <td>≤20%</td> <td>0402≥1µF</td> </tr> <tr> <td rowspan="2">16V</td> <td rowspan="2">≤5%</td> <td>≤10%</td> <td>0201≥0.01µF; 0402≥0.033µF; 0805≥0.68µF;1206≥2.2µF;1210≥4.7µF</td> </tr> <tr> <td>≤15%</td> <td>0201≥0.1µF; 0402≥0.47µF; 0603≥0.68µF;0805≥2.2µF; 1206≥4.7µF; 1210≥22µF; TT series</td> </tr> <tr> <td rowspan="2">10V</td> <td rowspan="2">≤7.5%</td> <td>≤15%</td> <td>0201≥0.012µF 0402≥0.33µF; 0603≥0.33µF; 0805≥2.2µF; 1206≥2.2µF; 1210≥22µF</td> </tr> <tr> <td>≤20%</td> <td>0201≥0.1µF; 0402≥1µF TT series</td> </tr> <tr> <td>6.3V</td> <td>≤15%</td> <td>≤30%</td> <td>0201≥0.1µF;0402≥1µF;0603≥10µF; 0805≥4.7µF; 1206≥47µF :1210≥100µF; TT series</td> </tr> <tr> <td>4V</td> <td>≤20%</td> <td>-</td> <td>-</td> </tr> </tbody> </table> | Rated vol. | D.F.≤ | Exception of D.F. ≤ | | ≥100V | ≤3% | ≤6% | 1206≥0.47µF | ≤7.5% | 0805>0.1µF, 0603≥0.068µF | ≥50V | ≤3% | ≤6% | 0201(50V); 0603≥0.047µF; 0805≥0.18µF;1206≥0.47µF | ≤10% | 1210≥4.7µF | ≤20% | 0402≥0.1µF; 0603≥1µF; 0805≥1µF;1206≥4.7µF; 1210≥10µF TT series | 35V | ≤5% | ≤20% | 0603≥1µF; 0805≥2.2µF; 1210≥10µF | 25V | ≤5% | ≤10% | 0201≥0.01µF;0805≥1µF; 1210≥10µF | ≤14% | 0603≥0.33µF; 1206≥4.7µF | ≤15% | 0402≥0.10µF;0603≥0.47µF;0805≥2.2µF; 1206≥6.8µF ; 1210≥22µF; TT series | ≤20% | 0402≥1µF | 16V | ≤5% | ≤10% | 0201≥0.01µF; 0402≥0.033µF; 0805≥0.68µF;1206≥2.2µF;1210≥4.7µF | ≤15% | 0201≥0.1µF; 0402≥0.47µF; 0603≥0.68µF;0805≥2.2µF; 1206≥4.7µF; 1210≥22µF; TT series | 10V | ≤7.5% | ≤15% | 0201≥0.012µF 0402≥0.33µF; 0603≥0.33µF; 0805≥2.2µF; 1206≥2.2µF; 1210≥22µF | ≤20% | 0201≥0.1µF; 0402≥1µF TT series | 6.3V | ≤15% | ≤30% | 0201≥0.1µF;0402≥1µF;0603≥10µF; 0805≥4.7µF; 1206≥47µF :1210≥100µF; TT series | 4V | ≤20% | - | - |
| | | | Rated vol. | D.F.≤ | Exception of D.F. ≤ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | ≥100V | ≤3% | ≤6% | 1206≥0.47µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | ≤7.5% | 0805>0.1µF, 0603≥0.068µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | ≥50V | ≤3% | ≤6% | 0201(50V); 0603≥0.047µF; 0805≥0.18µF;1206≥0.47µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | ≤10% | 1210≥4.7µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | ≤20% | 0402≥0.1µF; 0603≥1µF; 0805≥1µF;1206≥4.7µF; 1210≥10µF TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 35V | ≤5% | ≤20% | 0603≥1µF; 0805≥2.2µF; 1210≥10µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 25V | ≤5% | ≤10% | 0201≥0.01µF;0805≥1µF; 1210≥10µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | ≤14% | 0603≥0.33µF; 1206≥4.7µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | ≤15% | 0402≥0.10µF;0603≥0.47µF;0805≥2.2µF; 1206≥6.8µF ; 1210≥22µF; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | ≤20% | 0402≥1µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V | ≤5% | ≤10% | 0201≥0.01µF; 0402≥0.033µF; 0805≥0.68µF;1206≥2.2µF;1210≥4.7µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ≤15% | 0201≥0.1µF; 0402≥0.47µF; 0603≥0.68µF;0805≥2.2µF; 1206≥4.7µF; 1210≥22µF; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V | ≤7.5% | ≤15% | 0201≥0.012µF 0402≥0.33µF; 0603≥0.33µF; 0805≥2.2µF; 1206≥2.2µF; 1210≥22µF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ≤20% | 0201≥0.1µF; 0402≥1µF TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V | ≤15% | ≤30% | 0201≥0.1µF;0402≥1µF;0603≥10µF; 0805≥4.7µF; 1206≥47µF :1210≥100µF; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4V | ≤20% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| No | Item | Test Condition | Requirements | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---|--|------------|--------|---------------------|--|------|------|-----|-------------------------------------|-----|-----|---|---|-----|------|-----|---|-----|--|----------------|-----|-------|---------------------------|-----|-------------|------------------|-------|-----|---|-----|-----|-----|-------------|------|-----|---|---|---------------|-----------------------|-----------|--|---|--------------------------------------|---|--|---|-----------------------|-----------|
| 13 | | | <p>Y5V:</p> <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F. ≤</th> <th colspan="2">Exception of D.F. ≤</th> </tr> </thead> <tbody> <tr> <td>≥50V</td> <td>7.5%</td> <td>10%</td> <td>0603≥0.1μF; 0805≥0.47μF; 1206≥4.7μF</td> </tr> <tr> <td>35V</td> <td>10%</td> <td>-</td> <td>-</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10%</td> <td>0402≥0.047μF; 0603≥0.1μF; 0805≥0.33μF; 1206≥1μF; 1210≥4.7μF</td> </tr> <tr> <td>15%</td> <td>0402≥0.068μF; 0603≥0.47μF; 1206≥4.7μF; 1210≥22μF</td> </tr> <tr> <td rowspan="2">16V (C<1μF)</td> <td rowspan="2">10%</td> <td>12.5%</td> <td>0402≥0.068μF; 0603≥0.68μF</td> </tr> <tr> <td>20%</td> <td>0402≥0.22μF</td> </tr> <tr> <td>16V (C≥1.0μF)</td> <td>12.5%</td> <td>20%</td> <td>0603≥2.2μF; 0805≥3.3μF; 1206≥10μF; 1210≥22μF; 1812≥47μF</td> </tr> <tr> <td>10V</td> <td>20%</td> <td>30%</td> <td>0402≥0.47μF</td> </tr> <tr> <td>6.3V</td> <td>30%</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>*I.R.: ≥10V, 1GΩ or 50 Ω-F whichever is smaller. Class II (X7R, X5R, X6S, Y5V)</p> <table border="1"> <thead> <tr> <th>Rated voltage</th> <th>Insulation Resistance</th> </tr> </thead> <tbody> <tr> <td>100V: X7R</td> <td rowspan="8">1GΩ or RxC≥10 Ω-F whichever is smaller.</td> </tr> <tr> <td>50V: 0402≥0.1μF; 0603≥1μF; 0805≥1μF; 1206≥4.7μF; 1210≥4.7μF</td> </tr> <tr> <td>35V: 0603≥1μF; 0805≥2.2μF; 1210≥10μF</td> </tr> <tr> <td>25V: 0402≥1μF; 0603≥2.2μF; 0805≥2.2μF; 1206≥10μF; 1210≥10μF</td> </tr> <tr> <td>16V: 0402≥0.22μF; 0603≥1μF; 0805≥2.2μF; 1206≥10μF; 1210≥47μF</td> </tr> <tr> <td>10V: 0201≥47nF; 0402≥0.47μF; 0603≥0.47μF; 0805≥2.2μF;</td> </tr> <tr> <td>1206≥4.7μF; 1210≥47μF</td> </tr> <tr> <td>6.3V ; 4V</td> </tr> </tbody> </table> | Rated vol. | D.F. ≤ | Exception of D.F. ≤ | | ≥50V | 7.5% | 10% | 0603≥0.1μF; 0805≥0.47μF; 1206≥4.7μF | 35V | 10% | - | - | 25V | 7.5% | 10% | 0402≥0.047μF; 0603≥0.1μF; 0805≥0.33μF; 1206≥1μF; 1210≥4.7μF | 15% | 0402≥0.068μF; 0603≥0.47μF; 1206≥4.7μF; 1210≥22μF | 16V (C<1μF) | 10% | 12.5% | 0402≥0.068μF; 0603≥0.68μF | 20% | 0402≥0.22μF | 16V (C≥1.0μF) | 12.5% | 20% | 0603≥2.2μF; 0805≥3.3μF; 1206≥10μF; 1210≥22μF; 1812≥47μF | 10V | 20% | 30% | 0402≥0.47μF | 6.3V | 30% | - | - | Rated voltage | Insulation Resistance | 100V: X7R | 1GΩ or RxC≥10 Ω-F whichever is smaller. | 50V: 0402≥0.1μF; 0603≥1μF; 0805≥1μF; 1206≥4.7μF; 1210≥4.7μF | 35V: 0603≥1μF; 0805≥2.2μF; 1210≥10μF | 25V: 0402≥1μF; 0603≥2.2μF; 0805≥2.2μF; 1206≥10μF; 1210≥10μF | 16V: 0402≥0.22μF; 0603≥1μF; 0805≥2.2μF; 1206≥10μF; 1210≥47μF | 10V: 0201≥47nF; 0402≥0.47μF; 0603≥0.47μF; 0805≥2.2μF; | 1206≥4.7μF; 1210≥47μF | 6.3V ; 4V |
| Rated vol. | D.F. ≤ | Exception of D.F. ≤ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ≥50V | 7.5% | 10% | 0603≥0.1μF; 0805≥0.47μF; 1206≥4.7μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35V | 10% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25V | 7.5% | 10% | 0402≥0.047μF; 0603≥0.1μF; 0805≥0.33μF; 1206≥1μF; 1210≥4.7μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 15% | 0402≥0.068μF; 0603≥0.47μF; 1206≥4.7μF; 1210≥22μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V (C<1μF) | 10% | 12.5% | 0402≥0.068μF; 0603≥0.68μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 20% | 0402≥0.22μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V (C≥1.0μF) | 12.5% | 20% | 0603≥2.2μF; 0805≥3.3μF; 1206≥10μF; 1210≥22μF; 1812≥47μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V | 20% | 30% | 0402≥0.47μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V | 30% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rated voltage | Insulation Resistance | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100V: X7R | 1GΩ or RxC≥10 Ω-F whichever is smaller. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50V: 0402≥0.1μF; 0603≥1μF; 0805≥1μF; 1206≥4.7μF; 1210≥4.7μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35V: 0603≥1μF; 0805≥2.2μF; 1210≥10μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25V: 0402≥1μF; 0603≥2.2μF; 0805≥2.2μF; 1206≥10μF; 1210≥10μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V: 0402≥0.22μF; 0603≥1μF; 0805≥2.2μF; 1206≥10μF; 1210≥47μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V: 0201≥47nF; 0402≥0.47μF; 0603≥0.47μF; 0805≥2.2μF; | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1206≥4.7μF; 1210≥47μF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V ; 4V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | Humidity (Damp Heat) Load | <p>Test temp.: 40±2°C Humidity: 90~95%RH Test time: 500+24/-0 hrs. To apply voltage : rated voltage. Before initial measurement (Class II only): To apply test voltage for 1hr at 40°C and then set for 24±2 hrs at room temp. Measurement to be made after keeping at room temp. for 24±2 hrs.</p> | <p>No remarkable damage. Cap change: NPO: ±7.5% or 0.75pF whichever is larger. X7R, X5R, X6S: ≥10V**, within ±12.5%; ≤6.3V within ±25%; TT series & C≥ 1uF, within ±25% **10V: 0603≥4.7μF; 0402≥1μF; 0201≥0.1μF, within ±25%; Y5V: ≥10V, within ±30%; ≤6.3V, within +30/-40% Q/D.F. value: NPO: C≥30pF, Q≥200; C<30pF, Q≥100+10/3C</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| No | Item | Test Condition | Requirements | | | |
|--------------------|---------------------------------|----------------|--|---------------|----------------------------|---|
| 14 | Humidity (Damp Heat) Load | | X7R, X5R, X6S: | | | |
| | | | Rated vol. | D.F. ≤ | Exception of D.F. ≤ | |
| | | | ≥100V | ≤3% | ≤6% | 1206 ≥ 0.47μF |
| | | | | | ≤7.5% | 0805 > 0.1μF; 0603 ≥ 0.068μF |
| | | | ≥50V | ≤3% | ≤6% | 0201(50V); 0603 ≥ 0.047μF; 0805 ≥ 0.18μF; 1206 ≥ 0.47μF |
| | | | | | ≤10% | 1210 ≥ 4.7μF |
| | | | | | ≤20% | 0402 ≥ 0.1μF; 0603 ≥ 1μF; 0805 ≥ 1μF; 1206 ≥ 4.7μF; 1210 ≥ 10μF TT series |
| | | | 35V | ≤5% | ≤20% | 0603 ≥ 1μF; 0805 ≥ 2.2μF; 1210 ≥ 10μF |
| | | | 25V | ≤5% | ≤10% | 0201 ≥ 0.01μF; 0805 ≥ 1μF; 1210 ≥ 10μF |
| | | | | | ≤14% | 0603 ≥ 0.33μF; 1206 ≥ 4.7μF |
| | | | | | ≤15% | 0402 ≥ 0.10μF; 0603 ≥ 0.47μF; 0805 ≥ 2.2 μF; 1206 ≥ 6.8μF ; 1210 ≥ 22μF; TT series |
| | | | | | ≤20% | 0402 ≥ 1μF |
| | | | 16V | ≤5% | ≤10% | 0201 ≥ 0.01μF; 0402 ≥ 0.033μF; 0805 ≥ 0.68μF; 1206 ≥ 2.2μF; 1210 ≥ 4.7μF |
| | | | | | ≤15% | 0201 ≥ 0.1μF; 0402 ≥ 0.47μF; 0603 ≥ 0.68μF; 0805 ≥ 2.2μF; 1206 ≥ 4.7μF; 1210 ≥ 22μF; TT series |
| | | | 10V | ≤7.5% | ≤15% | 0201 ≥ 0.012μF; 0402 ≥ 0.33μF; (0402/ X7R ≥ 0.22μF); 0603 ≥ 0.33μF; 0805 ≥ 2.2μF; 1206 ≥ 2.2μF; 1210 ≥ 22μF |
| | | | | | ≤20% | 0201 ≥ 0.1μF; 0402 ≥ 1μF; TT series |
| | | | 6.3V | ≤15% | ≤30% | 0201 ≥ 0.1μF; 0402 ≥ 1μF; 0603 ≥ 10μF; 0805 ≥ 4.7μF; 1206 ≥ 47μF ; 1210 ≥ 100μF; TT series |
| | | | 4V | ≤20% | - | - |
| | | | Y5V: | | | |
| | | | Rated vol. | D.F. ≤ | Exception of D.F. ≤ | |
| | | | ≥50V | 7.5% | 10% | 0603 ≥ 0.1μF; 0805 ≥ 0.47μF; 1206 ≥ 4.7μF |
| 35V | 10% | - | - | | | |
| 25V | 7.5% | 10% | 0402 ≥ 0.047μF; 0603 ≥ 0.1μF; 0805 ≥ 0.33μF; 1206 ≥ 1μF; 1210 ≥ 4.7μF | | | |
| | | 15% | 0402 ≥ 0.068μF; 0603 ≥ 0.47μF; 1206 ≥ 4.7μF; 1210 ≥ 22μF | | | |
| 16V (C < 1μF) | 10% | 12.5% | 0402 ≥ 0.068μF; 0603 ≥ 0.68μF | | | |
| | | 20% | 0402 ≥ 0.22μF | | | |
| 16V (C ≥ 1.0μF) | 12.5% | 20% | 0603 ≥ 2.2μF; 0805 ≥ 3.3μF; 1206 ≥ 10μF; 1210 ≥ 22μF; 1812 ≥ 47μF | | | |
| 10V | 20% | 30% | 0402 ≥ 0.47μF | | | |
| 6.3V | 30% | - | - | | | |


| No | Item | Test Condition | Requirements | |
|---------------------------------------|--|---|---|--|
| 14 | Humidity (Damp Heat) Load | | *I.R.: $\geq 10V$, $500M\Omega$ or $25 \Omega\text{-F}$ whichever is smaller. Class II (X7R, X5R, X6S, Y5V) | |
| | | | Rated voltage | Insulation Resistance |
| | | | 100V: X7R | 500G Ω or RxC $\geq 5 \Omega\text{-F}$ whichever is smaller. |
| | | | 50V: 0402 $\geq 0.1\mu\text{F}$; 0603 $\geq 1\mu\text{F}$; 0805 $\geq 1\mu\text{F}$; 1206 $\geq 4.7\mu\text{F}$; 1210 $\geq 4.7\mu\text{F}$ | |
| | | | 35V: 0603 $\geq 1\mu\text{F}$; 0805 $\geq 2.2\mu\text{F}$; 1210 $\geq 10\mu\text{F}$ | |
| | | | 25V: 0402 $\geq 1\mu\text{F}$; 0603 $\geq 2.2\mu\text{F}$; 0805 $\geq 2.2\mu\text{F}$; 1206 $\geq 10\mu\text{F}$; 1210 $\geq 10\mu\text{F}$ | |
| | | | 16V: 0402 $\geq 0.22\mu\text{F}$; 0603 $\geq 1\mu\text{F}$; 0805 $\geq 2.2\mu\text{F}$; 1206 $\geq 10\mu\text{F}$; 1210 $\geq 47\mu\text{F}$ | |
| | | | 10V: 0201 $\geq 47\text{nF}$; 0402 $\geq 0.47\mu\text{F}$; 0603 ≥ 0.47 μF ; 0805 $\geq 2.2\mu\text{F}$; 1206 $\geq 4.7\mu\text{F}$; 1210 $\geq 47\mu\text{F}$ | |
| 6.3V ; 4V ; TT series ; All X6S items | | | | |
| 15. | High Temperature Load (Endurance) | *Test temp.: NP0, X7R/X7E: $125\pm 3^\circ\text{C}$ X6S: $105\pm 3^\circ\text{C}$ X5R, Y5V: $85\pm 3^\circ\text{C}$ *Test time: 1000+24/-0 hrs. *To apply voltage: 1) \leq % of rated voltage. 2) $10V \leq U_r < 500V$: 200% of rated voltage. 3) 500V: 150% of rated voltage. 4) $U_r \geq 630V$: 120% of rated voltage. | No remarkable damage. Cap change: NP0: $\pm 3.0\%$ or $\pm 0.3\text{pF}$ whichever is larger X7R, X5R, X6S: $\geq 10V^{**}$, within $\pm 12.5\%$; $\leq 6.3V$ within $\pm 25\%$; TT series & C $\geq 1\mu\text{F}$, within $\pm 25\%$ **10V: 0603$\geq 4.7\mu\text{F}$; 0402$\geq 1\mu\text{F}$; 0201$\geq 0.1\mu\text{F}$, within $\pm 25\%$; Y5V: $\geq 10V$, within $\pm 30\%$; $\leq 6.3V$, within $+30/-40\%$ Q/D.F. value: NP0: More than 30pF, Q ≥ 350 10pF $\leq C < 30\text{pF}$, Q $\geq 275+2.5C$ Less than 10pF, Q $\geq 200+10C$ | |

| No | Item | Test Condition | Requirements | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---|---|--|--------------------------|--|-------------------|------|-------------|----------|----------------------|------|-------------|----------|----------------------|---------|-----------------------|------|---------------------|----------|-----------------------|---------|----------------------|------|-------------|--------|----------------------|------|---------------------|----------------------|----------|-----------------------|---------------------|-----|----------------------|----------------|------|------|----------------------|---|------------|-------------|--------------------------|---------------------|------------|------|------|--|---|------------|-------------|--------------------------|-----|-------------|-----------|--|--------------------------|--|---|------------|-----------|---|--|--------------------------|----------------------------|------------|--|--|-----------|--------------------------|--|-----|-----------|--------------------------|---|------------|---|------------|---|-----|-----------|------------|-----------------------|------------|---|------------|--|-----|-------------|------------|--|------------|--|------|------------|------------|---|----|------------|---|---|
| 15 | High Temperature Load (Endurance) | 5) 100% of rated voltage for below range. | X7R, X5R, X6S: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table border="1"> <thead> <tr> <th>Size</th> <th>Dielectric</th> <th>Rated voltage</th> <th>Capacitance range</th> </tr> </thead> <tbody> <tr> <td>0201</td> <td>X5R/X7R/X6S</td> <td>6.3V,10V</td> <td>C\geq0.1μF</td> </tr> <tr> <td>0402</td> <td>X5R/X7R/X6S</td> <td>6.3V,10V</td> <td>C\geq1.0μF</td> </tr> <tr> <td rowspan="3">0603</td> <td rowspan="3">X5R/X7R/X6S</td> <td>4V</td> <td>C\geq22μF</td> </tr> <tr> <td>6.3V,10V</td> <td>C\geq4.7μF</td> </tr> <tr> <td>35V</td> <td>C\geq1.0μF</td> </tr> <tr> <td rowspan="2">0805</td> <td rowspan="2">X5R/X7R/X6S</td> <td>4V</td> <td>C\geq47μF</td> </tr> <tr> <td>6.3V</td> <td>C\geq22μF</td> </tr> <tr> <td rowspan="2">1206</td> <td>X5R/X7R/</td> <td>6.3V</td> <td>C\geq47μF</td> </tr> <tr> <td>NPO</td> <td>3,000V</td> <td>C\geq1.5pF</td> </tr> <tr> <td>TT18</td> <td>Y5V</td> <td>6.3V,10</td> <td>C\geq2.2μF</td> </tr> <tr> <td>TT21</td> <td>Y5V</td> <td>6.3V</td> <td>C\geq10μF</td> </tr> <tr> <td>TT31</td> <td>Y5V</td> <td>6.3V</td> <td>C\geq22μF</td> </tr> </tbody> </table> | Size | Dielectric | Rated voltage | Capacitance range | 0201 | X5R/X7R/X6S | 6.3V,10V | C \geq 0.1 μ F | 0402 | X5R/X7R/X6S | 6.3V,10V | C \geq 1.0 μ F | 0603 | X5R/X7R/X6S | 4V | C \geq 22 μ F | 6.3V,10V | C \geq 4.7 μ F | 35V | C \geq 1.0 μ F | 0805 | X5R/X7R/X6S | 4V | C \geq 47 μ F | 6.3V | C \geq 22 μ F | 1206 | X5R/X7R/ | 6.3V | C \geq 47 μ F | NPO | 3,000V | C \geq 1.5pF | TT18 | Y5V | 6.3V,10 | C \geq 2.2 μ F | TT21 | Y5V | 6.3V | C \geq 10 μ F | TT31 | Y5V | 6.3V | C \geq 22 μ F | <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.\leq</th> <th colspan="2">Exception of D.F. \leq</th> </tr> </thead> <tbody> <tr> <td rowspan="2">\geq100V</td> <td rowspan="2">\leq3%</td> <td>\leq6%</td> <td>1206\geq0.47μF</td> </tr> <tr> <td>\leq7.5%</td> <td>0805$>$0.1μF; 0603\geq0.068μF</td> </tr> <tr> <td rowspan="3">\geq50V</td> <td rowspan="3">\leq3%</td> <td>\leq6%</td> <td>0201(50V); 0603\geq0.047μF; 0805\geq0.18μF; 1206\geq0.47μF</td> </tr> <tr> <td>\leq10%</td> <td>1210\geq4.7μF</td> </tr> <tr> <td>\leq20%</td> <td>0402\geq0.1μF; 0603\geq1μF; 0805\geq1μF; 1206\geq4.7μF; 1210\geq10μF TT series</td> </tr> <tr> <td>35V</td> <td>\leq5%</td> <td>\leq20%</td> <td>0603\geq1μF; 0805\geq2.2μF; 1210\geq10μF</td> </tr> <tr> <td rowspan="3">25V</td> <td rowspan="3">\leq5%</td> <td>\leq10%</td> <td>0201\geq0.01μF; 0805\geq1μF; 1210\geq10μF</td> </tr> <tr> <td>\leq14%</td> <td>0603\geq0.33μF; 1206\geq4.7μF</td> </tr> <tr> <td>\leq15%</td> <td>0402\geq0.10μF; 0603\geq0.47μF; 0805\geq2.2μF; 1206\geq6.8μF; 1210\geq22μF; TT series</td> </tr> <tr> <td rowspan="3">16V</td> <td rowspan="3">\leq5%</td> <td>\leq20%</td> <td>0402\geq1μF</td> </tr> <tr> <td>\leq10%</td> <td>0201\geq0.01μF; 0402\geq0.033μF; 0805\geq0.68μF; 1206\geq2.2μF; 1210\geq4.7μF</td> </tr> <tr> <td>\leq15%</td> <td>0201\geq0.1μF; 0402\geq0.47μF; 0603\geq0.68μF; 0805\geq2.2μF; 1206\geq4.7μF; 1210\geq22μF; TT series</td> </tr> <tr> <td rowspan="2">10V</td> <td rowspan="2">\leq7.5%</td> <td>\leq15%</td> <td>0201\geq0.012μF; 0402\geq0.33μF; 0603\geq0.33μF; 0805\geq2.2μF; 1206\geq2.2μF; 1210\geq22μF;</td> </tr> <tr> <td>\leq20%</td> <td>0201\geq0.1μF; 0402\geq1μF</td> </tr> <tr> <td>6.3V</td> <td>\leq15%</td> <td>\leq30%</td> <td>0201\geq0.1μF; 0402\geq1μF; 0603\geq10μF; 0805\geq4.7μF; 1206\geq47μF; 1210\geq100μF; TT series</td> </tr> <tr> <td>4V</td> <td>\leq20%</td> <td>-</td> <td>-</td> </tr> </tbody> </table> | Rated vol. | D.F. \leq | Exception of D.F. \leq | | \geq 100V | \leq 3% | \leq 6% | 1206 \geq 0.47 μ F | \leq 7.5% | 0805 $>$ 0.1 μ F; 0603 \geq 0.068 μ F | \geq 50V | \leq 3% | \leq 6% | 0201(50V); 0603 \geq 0.047 μ F; 0805 \geq 0.18 μ F; 1206 \geq 0.47 μ F | \leq 10% | 1210 \geq 4.7 μ F | \leq 20% | 0402 \geq 0.1 μ F; 0603 \geq 1 μ F; 0805 \geq 1 μ F; 1206 \geq 4.7 μ F; 1210 \geq 10 μ F TT series | 35V | \leq 5% | \leq 20% | 0603 \geq 1 μ F; 0805 \geq 2.2 μ F; 1210 \geq 10 μ F | 25V | \leq 5% | \leq 10% | 0201 \geq 0.01 μ F; 0805 \geq 1 μ F; 1210 \geq 10 μ F | \leq 14% | 0603 \geq 0.33 μ F; 1206 \geq 4.7 μ F | \leq 15% | 0402 \geq 0.10 μ F; 0603 \geq 0.47 μ F; 0805 \geq 2.2 μ F; 1206 \geq 6.8 μ F; 1210 \geq 22 μ F; TT series | 16V | \leq 5% | \leq 20% | 0402 \geq 1 μ F | \leq 10% | 0201 \geq 0.01 μ F; 0402 \geq 0.033 μ F; 0805 \geq 0.68 μ F; 1206 \geq 2.2 μ F; 1210 \geq 4.7 μ F | \leq 15% | 0201 \geq 0.1 μ F; 0402 \geq 0.47 μ F; 0603 \geq 0.68 μ F; 0805 \geq 2.2 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F; TT series | 10V | \leq 7.5% | \leq 15% | 0201 \geq 0.012 μ F; 0402 \geq 0.33 μ F; 0603 \geq 0.33 μ F; 0805 \geq 2.2 μ F; 1206 \geq 2.2 μ F; 1210 \geq 22 μ F; | \leq 20% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F | 6.3V | \leq 15% | \leq 30% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F; 0603 \geq 10 μ F; 0805 \geq 4.7 μ F; 1206 \geq 47 μ F; 1210 \geq 100 μ F; TT series | 4V | \leq 20% | - | - |
| | | Size | Dielectric | Rated voltage | Capacitance range | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0201 | X5R/X7R/X6S | 6.3V,10V | C \geq 0.1 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0402 | X5R/X7R/X6S | 6.3V,10V | C \geq 1.0 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0603 | X5R/X7R/X6S | 4V | C \geq 22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 6.3V,10V | C \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 35V | C \geq 1.0 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0805 | X5R/X7R/X6S | 4V | C \geq 47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 6.3V | C \geq 22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 1206 | X5R/X7R/ | 6.3V | C \geq 47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | NPO | 3,000V | C \geq 1.5pF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | TT18 | Y5V | 6.3V,10 | C \geq 2.2 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | TT21 | Y5V | 6.3V | C \geq 10 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | TT31 | Y5V | 6.3V | C \geq 22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Rated vol. | D.F. \leq | Exception of D.F. \leq | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \geq 100V | \leq 3% | \leq 6% | 1206 \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | \leq 7.5% | 0805 $>$ 0.1 μ F; 0603 \geq 0.068 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \geq 50V | \leq 3% | \leq 6% | 0201(50V); 0603 \geq 0.047 μ F; 0805 \geq 0.18 μ F; 1206 \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | \leq 10% | 1210 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | \leq 20% | 0402 \geq 0.1 μ F; 0603 \geq 1 μ F; 0805 \geq 1 μ F; 1206 \geq 4.7 μ F; 1210 \geq 10 μ F TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 35V | \leq 5% | \leq 20% | 0603 \geq 1 μ F; 0805 \geq 2.2 μ F; 1210 \geq 10 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 25V | \leq 5% | \leq 10% | 0201 \geq 0.01 μ F; 0805 \geq 1 μ F; 1210 \geq 10 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | \leq 14% | 0603 \geq 0.33 μ F; 1206 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \leq 15% | 0402 \geq 0.10 μ F; 0603 \geq 0.47 μ F; 0805 \geq 2.2 μ F; 1206 \geq 6.8 μ F; 1210 \geq 22 μ F; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V | \leq 5% | \leq 20% | 0402 \geq 1 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 10% | 0201 \geq 0.01 μ F; 0402 \geq 0.033 μ F; 0805 \geq 0.68 μ F; 1206 \geq 2.2 μ F; 1210 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 15% | 0201 \geq 0.1 μ F; 0402 \geq 0.47 μ F; 0603 \geq 0.68 μ F; 0805 \geq 2.2 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V | \leq 7.5% | \leq 15% | 0201 \geq 0.012 μ F; 0402 \geq 0.33 μ F; 0603 \geq 0.33 μ F; 0805 \geq 2.2 μ F; 1206 \geq 2.2 μ F; 1210 \geq 22 μ F; | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | \leq 20% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V | \leq 15% | \leq 30% | 0201 \geq 0.1 μ F; 0402 \geq 1 μ F; 0603 \geq 10 μ F; 0805 \geq 4.7 μ F; 1206 \geq 47 μ F; 1210 \geq 100 μ F; TT series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4V | \leq 20% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | (6) 150% of rated voltage for below range. | Y5V: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table border="1"> <thead> <tr> <th>Size</th> <th>Dielectric</th> <th>Rated voltage</th> <th>Capacitance range</th> </tr> </thead> <tbody> <tr> <td>0201</td> <td>X5R/X7R/X6S</td> <td>16V</td> <td>C\geq0.1μF</td> </tr> <tr> <td rowspan="2">0402</td> <td rowspan="2">X5R/X7R/X6S</td> <td>50V</td> <td>C\geq0.1μF</td> </tr> <tr> <td>10V~25V</td> <td>C\geq0.22μF</td> </tr> <tr> <td rowspan="2">0603</td> <td rowspan="2">Y5V</td> <td>16V</td> <td>C\geq0.47μF</td> </tr> <tr> <td>10V,50V</td> <td>C\geq1.0μF</td> </tr> <tr> <td rowspan="3">0805</td> <td rowspan="3">X5R/X7R/X6S</td> <td>10~50V</td> <td>C\geq4.7μF</td> </tr> <tr> <td rowspan="2">X7R</td> <td>50V</td> <td>C\geq2.2μF</td> </tr> <tr> <td>100V</td> <td>C\geq0.47μF</td> </tr> <tr> <td>Y5V</td> <td>16V</td> <td>C\geq4.7μF</td> </tr> <tr> <td>2220</td> <td>X7R</td> <td>100V</td> <td>C\geq6.8μF</td> </tr> </tbody> </table> | Size | Dielectric | Rated voltage | Capacitance range | 0201 | X5R/X7R/X6S | 16V | C \geq 0.1 μ F | 0402 | X5R/X7R/X6S | 50V | C \geq 0.1 μ F | 10V~25V | C \geq 0.22 μ F | 0603 | Y5V | 16V | C \geq 0.47 μ F | 10V,50V | C \geq 1.0 μ F | 0805 | X5R/X7R/X6S | 10~50V | C \geq 4.7 μ F | X7R | 50V | C \geq 2.2 μ F | 100V | C \geq 0.47 μ F | Y5V | 16V | C \geq 4.7 μ F | 2220 | X7R | 100V | C \geq 6.8 μ F | <table border="1"> <thead> <tr> <th>Rated vol.</th> <th>D.F.\leq</th> <th colspan="2">Exception of D.F. \leq</th> </tr> </thead> <tbody> <tr> <td>\geq50V</td> <td>7.5%</td> <td>10%</td> <td>0603\geq0.1μF; 0805\geq0.47μF; 1206\geq4.7μF</td> </tr> <tr> <td>35V</td> <td>10%</td> <td>-</td> <td>-</td> </tr> <tr> <td rowspan="2">25V</td> <td rowspan="2">7.5%</td> <td>10%</td> <td>0402\geq0.047μF; 0603\geq0.1μF; 0805\geq0.33μF; 1206\geq1μF; 1210\geq4.7μF</td> </tr> <tr> <td>15%</td> <td>0402\geq0.068μF; 0603\geq0.47μF; 1206\geq4.7μF; 1210\geq22μF</td> </tr> <tr> <td rowspan="2">16V (C$<$1μF)</td> <td rowspan="2">10%</td> <td>12.5%</td> <td>0402\geq0.068μF; 0603\geq0.68μF</td> </tr> <tr> <td>20%</td> <td>0402\geq0.22μF</td> </tr> <tr> <td rowspan="2">16V (C\geq1.0μF)</td> <td rowspan="2">12.5%</td> <td>20%</td> <td>0603\geq2.2μF; 0805\geq3.3μF; 1206\geq10μF; 1210\geq22μF; 1812\geq47μF</td> </tr> <tr> <td>30%</td> <td>0402\geq0.47μF</td> </tr> <tr> <td>10V</td> <td>20%</td> <td>30%</td> <td>0402\geq0.47μF</td> </tr> <tr> <td>6.3V</td> <td>30%</td> <td>-</td> <td>-</td> </tr> </tbody> </table> | Rated vol. | D.F. \leq | Exception of D.F. \leq | | \geq 50V | 7.5% | 10% | 0603 \geq 0.1 μ F; 0805 \geq 0.47 μ F; 1206 \geq 4.7 μ F | 35V | 10% | - | - | 25V | 7.5% | 10% | 0402 \geq 0.047 μ F; 0603 \geq 0.1 μ F; 0805 \geq 0.33 μ F; 1206 \geq 1 μ F; 1210 \geq 4.7 μ F | 15% | 0402 \geq 0.068 μ F; 0603 \geq 0.47 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F | 16V (C $<$ 1 μ F) | 10% | 12.5% | 0402 \geq 0.068 μ F; 0603 \geq 0.68 μ F | 20% | 0402 \geq 0.22 μ F | 16V (C \geq 1.0 μ F) | 12.5% | 20% | 0603 \geq 2.2 μ F; 0805 \geq 3.3 μ F; 1206 \geq 10 μ F; 1210 \geq 22 μ F; 1812 \geq 47 μ F | 30% | 0402 \geq 0.47 μ F | 10V | 20% | 30% | 0402 \geq 0.47 μ F | 6.3V | 30% | - | - | | | | | | | | | | | | | | | | | | | | | | | |
| Size | Dielectric | Rated voltage | Capacitance range | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0201 | X5R/X7R/X6S | 16V | C \geq 0.1 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0402 | X5R/X7R/X6S | 50V | C \geq 0.1 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 10V~25V | C \geq 0.22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603 | Y5V | 16V | C \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 10V,50V | C \geq 1.0 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0805 | X5R/X7R/X6S | 10~50V | C \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X7R | 50V | C \geq 2.2 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 100V | C \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Y5V | 16V | C \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2220 | X7R | 100V | C \geq 6.8 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rated vol. | D.F. \leq | Exception of D.F. \leq | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \geq 50V | 7.5% | 10% | 0603 \geq 0.1 μ F; 0805 \geq 0.47 μ F; 1206 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 35V | 10% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25V | 7.5% | 10% | 0402 \geq 0.047 μ F; 0603 \geq 0.1 μ F; 0805 \geq 0.33 μ F; 1206 \geq 1 μ F; 1210 \geq 4.7 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 15% | 0402 \geq 0.068 μ F; 0603 \geq 0.47 μ F; 1206 \geq 4.7 μ F; 1210 \geq 22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V (C $<$ 1 μ F) | 10% | 12.5% | 0402 \geq 0.068 μ F; 0603 \geq 0.68 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 20% | 0402 \geq 0.22 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16V (C \geq 1.0 μ F) | 12.5% | 20% | 0603 \geq 2.2 μ F; 0805 \geq 3.3 μ F; 1206 \geq 10 μ F; 1210 \geq 22 μ F; 1812 \geq 47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 30% | 0402 \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10V | 20% | 30% | 0402 \geq 0.47 μ F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.3V | 30% | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| No | Item | Test Condition | Requirements | | | | | | | | | | | |
|--|---|---|---|---------------|-----------------------|-----------|---|---|--|---|--|---|---------------------------------------|--|
| 15 | High Temperature Load (Endurance) | <p>*Before initial measurement (Class II only): To apply test voltage for 1hr at test temp. and then set for 24±2 hrs at room temp.</p> <p>*Measurement to be made after keeping at room temp. for 24±2 hrs</p> | <p>*I.R.: ≥10V, 1GΩ or 50 Ω-F whichever is smaller. Class II (X7R, X5R, X6S, Y5V)</p> <table border="1"> <thead> <tr> <th>Rated voltage</th> <th>Insulation Resistance</th> </tr> </thead> <tbody> <tr> <td>100V: X7R</td> <td rowspan="6">1GΩ or RxC ≥ 10 Ω-F whichever is smaller.</td> </tr> <tr> <td>50V: 0402 ≥ 0.1μF; 0603 ≥ 1μF; 0805 ≥ 1μF; 1206 ≥ 4.7μF; 1210 ≥ 4.7μF</td> </tr> <tr> <td>35V: 0603 ≥ 1μF; 0805 ≥ 2.2μF; 1210 ≥ 10μF</td> </tr> <tr> <td>25V: 0402 ≥ 1μF; 0603 ≥ 2.2μF; 0805 ≥ 2.2μF; 1206 ≥ 10μF; 1210 ≥ 10μF</td> </tr> <tr> <td>16V: 0402 ≥ 0.22μF; 0603 ≥ 1μF; 0805 ≥ 2.2μF; 1206 ≥ 10μF; 1210 ≥ 47μF</td> </tr> <tr> <td>10V: 0201 ≥ 47nF; 0402 ≥ 0.47μF; 0603 ≥ 0.47μF; 0805 ≥ 2.2μF;</td> </tr> <tr> <td colspan="2">6.3V ; 4V ; TT series ; All X6S items</td> </tr> </tbody> </table> | Rated voltage | Insulation Resistance | 100V: X7R | 1GΩ or RxC ≥ 10 Ω-F whichever is smaller. | 50V: 0402 ≥ 0.1μF; 0603 ≥ 1μF; 0805 ≥ 1μF; 1206 ≥ 4.7μF; 1210 ≥ 4.7μF | 35V: 0603 ≥ 1μF; 0805 ≥ 2.2μF; 1210 ≥ 10μF | 25V: 0402 ≥ 1μF; 0603 ≥ 2.2μF; 0805 ≥ 2.2μF; 1206 ≥ 10μF; 1210 ≥ 10μF | 16V: 0402 ≥ 0.22μF; 0603 ≥ 1μF; 0805 ≥ 2.2μF; 1206 ≥ 10μF; 1210 ≥ 47μF | 10V: 0201 ≥ 47nF; 0402 ≥ 0.47μF; 0603 ≥ 0.47μF; 0805 ≥ 2.2μF; | 6.3V ; 4V ; TT series ; All X6S items | |
| Rated voltage | Insulation Resistance | | | | | | | | | | | | | |
| 100V: X7R | 1GΩ or RxC ≥ 10 Ω-F whichever is smaller. | | | | | | | | | | | | | |
| 50V: 0402 ≥ 0.1μF; 0603 ≥ 1μF; 0805 ≥ 1μF; 1206 ≥ 4.7μF; 1210 ≥ 4.7μF | | | | | | | | | | | | | | |
| 35V: 0603 ≥ 1μF; 0805 ≥ 2.2μF; 1210 ≥ 10μF | | | | | | | | | | | | | | |
| 25V: 0402 ≥ 1μF; 0603 ≥ 2.2μF; 0805 ≥ 2.2μF; 1206 ≥ 10μF; 1210 ≥ 10μF | | | | | | | | | | | | | | |
| 16V: 0402 ≥ 0.22μF; 0603 ≥ 1μF; 0805 ≥ 2.2μF; 1206 ≥ 10μF; 1210 ≥ 47μF | | | | | | | | | | | | | | |
| 10V: 0201 ≥ 47nF; 0402 ≥ 0.47μF; 0603 ≥ 0.47μF; 0805 ≥ 2.2μF; | | | | | | | | | | | | | | |
| 6.3V ; 4V ; TT series ; All X6S items | | | | | | | | | | | | | | |

Appendixes

Tape & Reel Dimensions




The dimension of paper tape



The dimension of plastic tape


| Size | 0201 | 0402 | 0603 | 0805 | 1206 | | | 1210 | | | 1812 | | | | | |
|------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Thick-ness | L | N | E | S, X | A | B | C, D, I | B | C, J, D | G, P | C, D | G, K | M | D, K | M | U |
| A0 | 0.38±0.05 | 0.62±0.05 | 0.7±0.1 | 1.02±0.05 | 1.5±0.1 | 1.5±0.1 | <1.57 | 2±0.1 | <1.85 | <1.95 | <2.97 | <2.97 | <2.97 | <3.81 | <3.81 | <3.9 |
| B0 | 0.68±0.05 | 1.12±0.05 | 1.2±0.1 | 1.8±0.05 | 2.3±0.1 | 2.3±0.1 | <2.40 | 3.5±0.1 | <3.46 | <3.67 | <3.73 | <3.73 | <3.73 | <5.3 | <5.3 | <5.3 |
| T | 0.42±0.05 | 0.6±0.05 | 0.7±0.1 | 0.95±0.05 | 0.75±0.05 | 0.95±0.05 | 0.23±0.05 | 0.95±0.05 | 0.23±0.05 | 0.23±0.05 | 0.23±0.05 | 0.23±0.05 | 0.23±0.05 | 0.25±0.05 | 0.25±0.05 | 0.25±0.05 |
| K0 | - | - | - | - | - | - | <2.5 | - | <2.5 | <2.5 | <2.5 | <2.5 | <3 | <2.5 | <3 | <3.5 |
| W | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 8±0.1 | 12±0.2 | 12±0.2 | 12±0.2 |
| P0 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 |
| 10xP0 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.1 | 40±0.2 |
| P1 | 2±0.05 | 2±0.05 | 2±0.05 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.1 | 4±0.10 | 4±0.1 | 8±0.1 | 8±0.1 | 8±0.1 |
| P2 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 | 2±0.05 |
| D0 | 1.55±0.05 | 1.55±0.05 | 1.55±0.05 | 1.55±0.05 | 1.55±0.05 | 1.55±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.05 | 1.5±0.1 |
| D1 | - | - | - | - | - | - | 1±0.1 | - | 1±0.1 | 1±0.1 | 1±0.1 | 1±0.1 | 1±0.1 | 1.5±0.1 | 1.5±0.1 | 1.5±0.1 |
| E | 1.75±0.05 | 1.75±0.05 | 1.75±0.05 | 1.75±0.05 | 1.75±0.05 | 1.75±0.05 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 | 1.75±0.1 |
| F | 3.50±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 3.5±0.05 | 5.5±0.05 | 5.5±0.05 | 5.5±0.05 |



The dimension of reel

| Size | 0201, 0402, 0603, 0805, 1206, 1210 | | | 1812 |
|-----------|------------------------------------|--------------|--------------|--------------|
| Reel size | 7" | 10" | 13" | 7" |
| C | 13 +0.5/-0.2 | 13 +0.5/-0.2 | 13 +0.5/-0.2 | 13 +0.5/-0.2 |
| W1 | 8.4 +1.5/-0 | 8.4+1.5/-0 | 8.4 +1.5/-0 | 12.4+2.0/-0 |
| A | 178 ±0.1 | 250 ±1 | 330 ±1 | 178 ±0.1 |
| N | 60 +1/-0 | 100 ±1 | 100 ±1 | 60 +1/-0 |

Constructions:



| No. | Name | NPO, X7R, X5R, X6S, Y5V |
|-----|------------------|--------------------------|
| 1 | Ceramic material | BaTiO ₃ based |
| 2 | Inner electrode | Ni |
| 3 | Termination | Inner layer |
| 4 | | Middle layer |
| 5 | | Outer layer |

Storage and handling conditions


- (1) To store products at 5°C to 40°C ambient temperature and 20 to 70% related humidity conditions.
- (2) The product is recommended to be used within one year after shipment. Check solderability in case of shelf life extension is needed.

Cautions:


- a. The corrosive gas reacts on the terminal electrodes of capacitors, and results in the poor solderability. Do not store the capacitors in the ambience of corrosive gas (e.g., hydrogen sulfide, sulfur dioxide, chlorine, ammonia gas etc.)
- b. In corrosive atmosphere, solderability might be degraded, and silver migration might occur to cause low reliability.
- c. Due to the dewing by rapid humidity change, or the photochemical change of the terminal electrode by direct sunlight, the solderability and electrical performance may deteriorate. Do not store capacitors under direct sunlight or dewing condition. To store products on the shelf and avoid exposure to moisture.

Recommended Soldering Conditions:

The lead-free termination MLCCs are not only to be used on SMT against lead-free solder paste, but also suitable against lead-containing solder paste. If the optimized solder joint is requested, increasing soldering time, temperature and concentration of N₂ within oven are recommended.



Recommended reflow soldering profile for SMT process with SnAgCu series solder paste.



Recommended wave soldering profile for SMT process with SnAgCu series solder.

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.