



Main

Range	New Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Studio
Number of gangs	2 gangs
Installation direction	Horizontal/vertical
Type of frame	Double
Number of modules	2 x 2 modules
Fixing mode	Clip-in
Colour tint	Anthracite (RAL 7021)

Complementary

Material	Thermoplastic ABS-UV stabilised: cover frame
Standards	IEC 60884-1 IEC 60669-1
Width	156 mm
Height	85 mm
Depth	10 mm
Product weight	0.021 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment


IK degree of protection	IK04
IP degree of protection	IP21D

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1 cm
Package 1 Width	8.6 cm
Package 1 Length	16 cm
Package 1 Weight	26 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	6.7 cm
Package 2 Width	12.3 cm
Package 2 Length	18.5 cm
Package 2 Weight	184 g
Unit Type of Package 3	S04
Number of Units in Package 3	180

Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	7.34 kg

Offer Sustainability

Cradle to Cradle	 Bronze
EU RoHS Directive	Not applicable, out of EU RoHS legal scope