



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

NEMA Size	0
Rated Current	18 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phases
Type of Overload	Melting alloy 3 Thermal Units
Horsepower Rating	3 HP at 200 V AC 3 HP at 230 V AC 5 HP at 460 V AC 5 HP at 575 V AC
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Terminal Type	Screw clamp terminals
Height	172.96 mm
Width	88.90 mm
Depth	107.19 mm

Environment

Enclosure Type	Not rated (open device)
Certifications	UL listed[RETURN]CSA[RETURN]NEMA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.192 cm
Package 1 Width	14.732 cm
Package 1 Length	20.32 cm
Package 1 Weight	1.814 kg
Unit Type of Package 2	PAL

Number of Units in Package 2	175
Package 2 Height	101.6 cm
Package 2 Width	101.6 cm
Package 2 Length	121.92 cm
Package 2 Weight	318.422 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------