



## Main

|                                |   |
|--------------------------------|---|
| Range                          | TeSys<br>TeSys Deca   |
| Range of product               | TeSys Deca  |
| Product or component type      | Contacteur  |
| Device short name              | LC1D  |
| Contacteur application         | Motor control<br>Resistive load   |
| Utilisation category           | AC-4<br>AC-1<br>AC-3<br>AC-3e   |
| Poles description              | 3P  |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 300 V DC  |
| [Ie] rated operational current | 60 A (at <60 °C) at <= 440 V AC AC-1 for power circuit<br>40 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>40 A (at <60 °C) at <= 440 V AC AC-3e for power circuit |
| [Uc] control circuit voltage   | 230 V AC 50/60 Hz   |

## Complementary

|   |   |
|---|---|
| Motor power kW                              | 18.5 kW at 380...400 V AC 50/60 Hz (AC-3)<br>11 kW at 220...230 V AC 50/60 Hz (AC-3)<br>22 kW at 415...440 V AC 50/60 Hz (AC-3)<br>22 kW at 500 V AC 50/60 Hz (AC-3)<br>30 kW at 660...690 V AC 50/60 Hz (AC-3)<br>9 kW at 400 V AC 50/60 Hz (AC-4)<br>18.5 kW at 380...400 V AC 50/60 Hz (AC-3e)<br>11 kW at 220...230 V AC 50/60 Hz (AC-3e)<br>22 kW at 415...440 V AC 50/60 Hz (AC-3e)<br>22 kW at 500 V AC 50/60 Hz (AC-3e)<br>30 kW at 660...690 V AC 50/60 Hz (AC-3e) |
| Motor power hp                              | 5 Hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>10 Hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>30 Hp at 575/600 V AC 50/60 Hz for 3 phases motors<br>10 Hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>3 Hp at 115 V AC 50/60 Hz for 1 phase motors<br>30 hp at 460/480 V AC 50/60 Hz for 3 phases motors  |
| Compatibility code                          | LC1D  |
| Pole contact composition                    | 3 NO  |
| Contact compatibility                       | M2  |
| Protective cover                            | With  |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>60 A (at 60 °C) for power circuit   |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>800 A at 440 V for power circuit conforming to IEC 60947  |
| Rated breaking capacity                     | 800 A at 440 V for power circuit conforming to IEC 60947  |

|   |  |
|---|--|
| [I <sub>cw</sub> ] rated short-time withstand current | 320 A 40 °C - 10 s for power circuit<br>720 A 40 °C - 1 s for power circuit<br>72 A 40 °C - 10 min for power circuit<br>165 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit  |
| Associated fuse rating                                | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>80 A gG at ≤ 690 V coordination type 1 for power circuit<br>80 A gG at ≤ 690 V coordination type 2 for power circuit   |
| Average impedance                                     | 1.5 mOhm - Ith 60 A 50 Hz for power circuit  |
| Power dissipation per pole                            | 2.4 W AC-3<br>5.4 W AC-1<br>2.4 W AC-3e  |
| [U <sub>i</sub> ] rated insulation voltage            | Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified<br>Power circuit: 690 V conforming to IEC 60947-4-1  |
| Overvoltage category                                  | III  |
| Pollution degree                                      | 3  |
| [U <sub>imp</sub> ] rated impulse withstand voltage   | 6 kV conforming to IEC 60947   |
| Safety reliability level                              | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1   |
| Mechanical durability                                 | 6 Mcycles  |
| Electrical durability                                 | 1.4 Mcycles 60 A AC-1 at U <sub>e</sub> ≤ 440 V<br>1.5 Mcycles 40 A AC-3 at U <sub>e</sub> ≤ 440 V<br>1.5 Mcycles 40 A AC-3e at U <sub>e</sub> ≤ 440 V   |
| Control circuit type                                  | AC at 50/60 Hz standard  |
| Coil technology                                       | Without built-in suppressor module   |
| Control circuit voltage limits                        | 0.3...0.6 U <sub>c</sub> (-40...70 °C):drop-out AC 50/60 Hz<br>0.8...1.1 U <sub>c</sub> (-40...60 °C):operational AC 50 Hz<br>0.85...1.1 U <sub>c</sub> (-40...60 °C):operational AC 60 Hz<br>1...1.1 U <sub>c</sub> (60...70 °C):operational AC 50/60 Hz  |
| Inrush power in VA                                    | 140 VA 60 Hz cos phi 0.75 (at 20 °C)<br>160 VA 50 Hz cos phi 0.75 (at 20 °C)   |
| Hold-in power consumption in VA                       | 13 VA 60 Hz cos phi 0.3 (at 20 °C)<br>15 VA 50 Hz cos phi 0.3 (at 20 °C)   |
| Heat dissipation                                      | 4...5 W at 50/60 Hz  |
| Operating time  | 4...19 ms opening<br>12...26 ms closing  |
| Maximum operating rate                                | 3600 cyc/h 60 °C   |
| Connections - terminals                               | Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Power circuit: screw connection 1 1...35 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: screw connection 2 1...25 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: screw connection 1 1...35 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw connection 2 1...25 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw connection 1 1...35 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Power circuit: screw connection 2 1...25 mm <sup>2</sup> - cable stiffness: solid without cable end |

|                               |  |
|-------------------------------|--|
| Tightening torque             | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 8 N.m - on EverLink BTR screw connectors - cable 25...35 mm <sup>2</sup><br>hexagonal screw head 4 mm<br>Power circuit: 5 N.m - on EverLink BTR screw connectors - cable 1...25 mm <sup>2</sup><br>hexagonal screw head 4 mm<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2<br>Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |
| Auxiliary contact composition | 1 NO + 1 NC  |
| Auxiliary contacts type       | Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>Type mirror contact 1 NC conforming to IEC 60947-4-1   |
| Signalling circuit frequency  | 25...400 Hz  |
| Minimum switching voltage     | 17 V for signalling circuit  |
| Minimum switching current     | 5 mA for signalling circuit  |
| Insulation resistance         | > 10 MOhm for signalling circuit   |
| Non-overlap time              | 1.5 Ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact  |
| Mounting support              | Rail<br>Plate  |

## Environment

|   |  |
|---|--|
| Standards   | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508<br>IEC 60335-1   |
| Product certifications                                | CCC<br>CSA<br>GOST<br>UL   |
| IP degree of protection                               | IP20 front face conforming to IEC 60529  |
| Protective treatment                                  | TH conforming to IEC 60068-2-30  |
| Climatic withstand                                    | Conforming to IACS E10 exposure to damp heat<br>Conforming to IEC 60947-1 Annex Q category D exposure to damp heat   |
| Permissible ambient air temperature around the device | -40...60 °C<br>60...70 °C with derating  |
| Operating altitude                                    | 0...3000 m   |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1   |
| Flame retardance                                      | V1 conforming to UL 94   |
| Mechanical robustness                                 | Vibrations contactor open (2 Gn, 5...300 Hz)<br>Vibrations contactor closed (4 Gn, 5...300 Hz)<br>Shocks contactor closed (15 Gn for 11 ms)<br>Shocks contactor open (10 Gn for 11 ms) |
| Height  | 122 mm   |
| Width   | 55 mm  |
| Depth   | 120 mm   |
| Net weight  | 0.85 kg  |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 6.3 cm  |
| Package 1 Width              | 13.8 cm |
| Package 1 Length             | 15.4 cm |
| Package 1 Weight             | 920.0 g |
| Unit Type of Package 2       | S02     |
| Number of Units in Package 2 | 10      |
| Package 2 Height             | 15.0 cm |
| Package 2 Width              | 30.0 cm |
| Package 2 Length             | 40.0 cm |

|                              |           |
|------------------------------|-----------|
| Package 2 Weight             | 9.9 kg    |
| Unit Type of Package 3       | P06       |
| Number of Units in Package 3 | 160       |
| Package 3 Height             | 77.0 cm   |
| Package 3 Width              | 80.0 cm   |
| Package 3 Length             | 60.0 cm   |
| Package 3 Weight             | 166.82 kg |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free                   | Yes   |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions



(1) Minimum electrical clearance

| LC1 |                                    | D40A...D65A |
|-----|------------------------------------|-------------|
| a   |                                    | 55          |
| b1  | with LA4 D•2                       | –           |
|     | with LA4 DB3 or LAD 4BB3           | 136         |
|     | with LA4 DF, DT                    | 157         |
|     | with LA4 DM, DW, DL                | 166         |
| c   | without cover or add-on blocks     | 118         |
|     | with cover, without add-on blocks  | 120         |
| c1  | with LAD N (1 contact)             | –           |
|     | with LAD N or C (2 or 4 contacts)  | 150         |
| c2  | with LA6 DK10, LAD 6DK             | 163         |
| c3  | with LAD T, R, S                   | 171         |
|     | with LAD T, R, S and sealing cover | 175         |

## Wiring

