



Main

Range of product	ComPact NSX100...250
Product or component type	Rotary handle
Accessory / separate part type	Control accessories
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle mounting style	Extended

Complementary

Rotary handle padlocking	1 to 3 padlocks Padlock in OFF position
Rotary handle mounting location	Front
Range compatibility	ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPact NSX250 PowerPact PowerPact Multistandard

Environment

IP degree of protection	IP55
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.000 cm
Package 1 Width	10.400 cm
Package 1 Length	49.200 cm
Package 1 Weight	690.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	5.250 kg
Unit Type of Package 3	P12
Number of Units in Package 3	72
Package 3 Height	105.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	50.976 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------