



Instruction Data sheet

ENGLISH

DIGITAL PROCESS INDICATOR

Stock Number: 1981166



77 x 35 DIN Size Digital Process Indicator

- 4 Digits Display
- Easily adjustable from front panel
- Between -1999 and 9999 display adjustment scale
- Adjustable decimal point
- Selectable universal process Input
(0-10V $\overline{\text{---}}$, 0-1V $\overline{\text{---}}$, 0-60mV $\overline{\text{---}}$, 0-20mA $\overline{\text{---}}$, 4-20mA $\overline{\text{---}}$)
- Adjustable input filter
- Minimum and maximum measured values in the memory storage
- Maximum or minimum measurement value can be shown continuously on the display
- User can be adjust device's reading value for selected input type
- Alarm output
- Relay or SSR driver output (It must be determined in order.)
- Adjustable alarm set value from front panel
- Programming mode password protection



Specifications

Input

Configurable Universal process input (V, mA)

Output

None

Environmental Rating and Physical Specification

Storage / Operating Temperature: $-40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$ / $0\text{ }^{\circ}\text{C}$ to $+50\text{ }^{\circ}\text{C}$

Storage / Operating Humidity: 90 % max. (None condensing)

Protection Class : IP65 at front, IP20 at rear.

Supply Voltage

10 - 30 Vdc

Dimensions

77x35mm

Electrical Wirings

