



Main

Range	Thalassa
Accessory / separate part category	Fixing accessory
Product or component type	Wall fixing support
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	Top and bottom, on rear of the enclosure
Range compatibility	Thalassa Thalassa PLM
Device composition	Fixing screws 4 lug

Complementary

Material	Stainless steel
Fixing mode	Screwed - from the outside location
Permanent permissible load	100 Kg horizontal position 200 kg vertical position
Height	40 mm
Width	155 mm
Depth	80 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	8.000 cm
Package 1 Length	15.000 cm
Package 1 Weight	377.500 g
Unit Type of Package 2	S04
Number of Units in Package 2	50
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	19.241 kg
Unit Type of Package 3	P12
Number of Units in Package 3	200
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	88.964 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------