

## FEATURES

- Available in either 25m or 100m length
- Flame retardant
- Single core cable design
- Meets BS6231 standards

## RS PRO Black Single Core x 4.0sqmm (Class 5 PCW), PVC Insulated, 600/1000V, Type BK, 25m

RS Stock No.: 811-4466



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

**Product Description**

From RS PRO, comes a range of high quality and great value Tri-rated cables. Manufactured with a premium copper conductor and insulated with PVC (Polyvinyl Chloride), these Tri-rated cables are a fantastic solution for use in control panels and other types of electrical equipment.

**General Specifications**

Type	BK
Tri-rated	Yes
Sheath Colour	Black
Fire Behaviour	Flame Retardant
Application	Electrical cabinets, Industrial electrical installations, Small electronic devices, Relay and instrumentation panels, Control metering, Motor starters

**Electrical Specifications**

Voltage Rating	1000V
Conductor Material	Copper
Insulation Material	PVC
Conductor Resistance	See datasheet

**Mechanical Specifications**

Length	25m
Cross Sectional Area	4mm <sup>2</sup>
Outer Diameter	4.8mm
American Wire Gauge	11
Core Strands	56/0.3 mm
Size of Strands	0.3mm
Insulation Wall Thickness	0.80mm (Nominal)
Minimum Bend Radius	6 x Overall Diameter
Weight	49.90kg/km
Diameter Over Insulation	Lower Limit: 3.90mm ; Upper Limit: 4.80mm

**Operation Environment Specifications**

HYa dYfUi fYFUb[ Y	ËÍ Á ÁË €Ö
--------------------	------------

**Approvals**

Standards Met	ÒÙÀ GFKGÉÍ Á
---------------	--------------

AWM Size	Area mm <sup>2</sup>	Wire Type	UL Style	Nominal R/T (mm)	Nominal Diam (mm)	Current Rating (A)	Weight Kg/Km
22	0.5	16/0.2	1015	0.80	2.6	11	1
20	0.75	24/0.2	1015	0.80	2.8	14	14
18	1.0	32/0.2	1015	0.80	3.0	17	17
16	1.5	30/0.25	1015	0.80	3.3	21	22
14	2.5	50/0.25	1015	0.80	3.7	30	33
12	4.0	56/0.3	1015	0.80	4.3	41	49
10	6.0	84/0.3	1015	0.80	5.1	53	71
8	10	80/0.4	1028	1.20	6.8	75	124
6	16	126/0.4	1283	1.58	9.2	100	199
4	25	196/0.4	1283	1.58	10.6	136	290
2	35	276/0.4	1283	1.58	11.6	167	387
1	50	396/0.4	1284	2.10	14.4	190	570
2/0	70	360/0.5	1284	2.10	16.5	240	781
3/0	95	475/0.5	1284	2.10	18.7	300	1025
4/0	120	608/0.5	1284	2.10	20.0	340	1280