## **BNC Adaptor**







## **Specifications**

Normal Impedance :  $50\Omega$ Frequency Range : 0 - 1 GHz
Operating Voltage : 500V rms
Max. Contact Resistance :  $3m\Omega$  (gold)
Dielectric Withstanding Voltage : 1,500 V rms
Min. Insulation Resistance :  $5,000M\Omega$ Mating / Unmating : 500 cycles
Temperature Range :  $-50^{\circ}$ C to  $+85^{\circ}$ C

## Diagram





No.	Description	Material	
1	Body	100μ″ Min. Nickel Plating over Zinc Alloy	
2	Coupling Nut		
3	Outer Contact	Nickel Plating Over Copper Strip	
4	Male Contact	Gold Plating Over Brass	
5	Female Contact	Gold Plating Over High Strength Copper	
6	Retention Washer	Nickel Plating Over Copper Strip	
7	Insulators	POM	
8	Spring Washer	Beryllium Copper	
9	Gasket	Silicone Rubber	
10	Spacer	PTFE	

## Part Number Table

Description	Part Number
BNC Adapter, Plug, BNC, Jack, Y Adapter, 50Ω	MP-13-39-5

Dimensions: Millimetres (Inches)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

