



ENGLISH

Datasheet

RS PRO Black Hook, 20mm x 5m

RS Stock No: **890-4161**



Product Details

RS PRO hook tape has rubber adhesive to provide an ultimate bonding with regular loop tape for higher strength applications that require minimal opening and closing.

Features and Benefits

- Hook type adhesive tape
- Provides an high strength bonding with regular loop tape
- Measures 20 mm x 5 m



ENGLISH

Specifications:

Colour	Black
Format	Strip
Hook Type	Hook Tape
Length	5 m
Width	20 mm



Rubber Adhesive Strips

An adhesive backed premium hook & loop system comprising of a synthetic rubber and resin system adhesive coating to the back of the hook & loop tape, giving a strong instant bond.

Adhesive colour: Light Yellow

Performance: A strong instant bond

Typical Application: Immediate adhesion to a variety of surfaces including paper, wood, polythene, metal, glass, plastic etc. (excluding plasticised PVC)

<u>Item</u>	<u>Properties</u>	<u>Unit</u>	<u>Standard</u>		<u>Test method</u>
WDS4	Tape Test- Adhesive Holding Power	Minutes	646	686	PSTC-7
WDS4	Tape Test- Shear Adhesion Temperature Fail Level	°C	60	60	PSTC-7
WDS4	180°C Peeling Adhesion	Kg/cm	1.34	1.38	PSTC-1
WDS4	Shear Strength	Kg/cm ²	0.85		CNS 12649 L3227
WDS4	Peel Strength	g/cm	200		CNS 12649 L3227
WDS4	Tearing Strength	Kg	2		ASTM D2261

Not recommended for direct exposure to sunlight & U.V.

Application Guide: To be avoided on surfaces of humidity, dust, oil etc.

Application and performance temperature from +5 to +40 degree C.

Customer Attention: The above points are suggestions and are not to be considered guarantees. All tapes should be tested in working conditions before long term use.