

FEATURES

- Panel mounting
- Supply voltage range of 4 V DC to 28 V DC
- 97 dB sound level
- Internal drive
- Diameter of 43 mm
- Height of 20 mm
- Operating temperature range of -20°C to +60°C
- Supply current of 8 mA
- Minimum frequency of 2.3 kHz
- Maximum frequency of 3.3 kHz

RS PRO 97dB, Panel Mount Continuous Internal Piezo Buzzer

RS Stock No.: 724-3172



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

These versatile piezo buzzers offer a broad voltage range, a loud and continuous tone as well as low power consumption. As part of our tried-and-tested RS PRO series, they emit a crisp and clear sound.

The buzzers draw only an 8 mA current and operate at between 4 V DC and 28 V DC. As a result, they're very energy efficient and compatible with most consumer appliances. With a continuous 97 dB tone, they can be heard clearly from a distance – even in noisy conditions. The buzzers are simple to install, as they're simply panel mounted. Thanks to their handy screw terminals, wires can be connected to them without the need for soldering.

General Specifications

Mounting Type	Panel Mount
Sound Level	97dB
Drive Type	Internal
Tone Type	Continuous
Colour	Black
Housing Material	ABS
Application	Alarms or warning systems, communications equipment and electronic cash registers.

Electrical Specifications

Minimum Supply Voltage	4Vdc
Maximum Supply Voltage	28Vdc
Maximum Frequency	3.3kHz
Minimum Frequency	2300Hz
Supply Current	8mA

Mechanical Specifications

Diameter	43mm
Length	45.5mm
Height	20mm
Dimensions	43mm (Dia.) x 20mm
Weight	43g

Operation Environment Specifications

Minimum Operating Temperature	-20°C
Maximum Operating Temperature	60°C

Approvals

Compliance/Certifications	ANSI/ESD S20.20:2014, BS EN 61340-5-1:2007
----------------------------------	--





Dimensions(mm):

