

# 1KG · 2KG · 3KG

## Multipurpose Dry Chemical Powder Fire Extinguisher

### CLASS AB



MODEL	FT01-01A-00	FT01-02A-00	FT01-03A-00
Capacity	1KG	2KG	3KG
Extinguishing Agent	Multipurpose Dry Chemical Powder		
Propellant	Nitrogen		
Operation Method	STORED PRESSURE		
Test Standard	SS EN3, BS EN3		
Discharge Distance	> 3M	> 3M	> 3.5M
Discharge Time	7 Sec	11 Sec	11 Sec
Body Diameter	85 MM	110 MM	130 MM
Total Height	334 MM	363 MM	363 MM
Total Weight	2 KG	3.4 KG	4.7 KG
Operating Temperature	-20°C to 60°C		
Working Pressure	15 BAR		
Test Pressure	30 BAR		
Fire Rating	8A : 34B	13A : 55B	21A : 70B
Pack Dimension(mm)	215x320x360 (6 per box)	240x350x380 (6 per box)	285x285x380 (4 per box)
PART NO	FEL-FT-D01	FEL-FT-D02	FEL-FT-D03



EN3



SETSCO SG  
APPROVED

#### Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. **P**ull out safety pin.

3. **A**im.

4. **S**queeze handle.

5. **S**weep.

## Accessories

Default for 1KG



Default for  
2KG & 3KG



Wire Bracket

L Bracket

Due to constant improvements, product dimensions may differ slightly.

# HERCULES

## 4KG · 6KG · 9KG · 12KG Multipurpose Dry Chemical Powder Fire Extinguisher CLASS AB



MODEL	FT01-04A-00	FT01-06A-00	FT01-09A-00	FT01-12A-00
Capacity	4KG	6KG	9KG	12KG
Extinguishing Agent	Multipurpose Dry Chemical Powder			
Propellant	Nitrogen			
Operation Method	STORED PRESSURE			
Test Standard	SS EN3, BS EN3			
Discharge Distance	> 3.5M	> 4M	> 5M	> 5M
Discharge Time	12 Sec	12 Sec	14 Sec	31 Sec
Body Diameter	138 MM	160 MM	185 MM	190 MM
Total Height	447 MM	520 MM	540 MM	590 MM
Total Weight	6.6 KG	9.4 KG	13.4 KG	16.6 KG
Operating Temperature	-20°C to 60°C			
Working Pressure	15 BAR			
Test Pressure	30 BAR			
Fire Rating	27A : 113B	34A : 183B	43A : 183B	55A : 233B
Pack Dimension(mm)	155x290x470 (2 per box)	165x175x535 (1 per box)	195x195x555 (1 per box)	200x200x610 (1 per box)
PART NO	FEL-FT-D04	FEL-FT-D06	FEL-FT-D09	FEL-FT-D12



EN3



SETSCO SG  
APPROVED

### Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. **P**ull out safety pin.

3. **A**im.

4. **S**queeze handle.

5. **S**weep.

## Accessories

(Default)



L Bracket

Heavy Duty Bracket

Foot 4/6/9KG


Due to constant improvements, product dimensions may differ slightly.

# 2KG · 5 KG

## Carbon Dioxide Fire Extinguisher



MODEL	FT02-02F-00	FT02-03D-00
Capacity	2KG	5KG
Extinguishing Agent	Carbon Dioxide	
Propellant	Carbon Dioxide	
Operation Method	STORED PRESSURE	
Test Standards	SS EN3, BS EN3	
Cylinder Diameter	103 MM	135.8 MM
Total Height	565 MM	755 MM
Total Weight	6.4 KG	13.5 KG
OperateTemp	-30°C to 60°C	
Working Pressure	56 BAR	
Test Pressure	250 BAR	
Fire Rating	21B	89B
Pack Dimension(mm)	125x160x600 (1 per box)	145x180x775 (1 per box)
PART NO	FEL-FT-C02	FEL-FT-C05



EN3



SETSCO SG  
APPROVED

### Information

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquefiable solids.

Effective against **electric fires**. Note that before attempting to fight electric fires, the electricity must be turned off.

Carbon dioxide is a **clean agent** that leaves no residue upon discharge.

### Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. **P**ull out safety pin.

3. **A**im.

4. **S**queeze handle.

5. **S**weep.

## Accessories

(Default)



L Bracket



HeavyDuty Bracket

Due to constant improvements, product dimensions may differ slightly.

# 9 LITRE Foam Fire Extinguisher



MODEL	FT01-09A-00 CE1
Capacity	9 Litre
Extinguishing Agent	3% AFFF FOAM
Propellant	Nitrogen
Operation Method	Stored Pressure
Test Standard	SS EN3, BS EN3
Cylinder Diameter	185 MM
Total Height	585 MM
Total Weight	13.9 KG
Operating Temperature	5°C to 60°C
Test Pressure	25 BAR
Fire Rating	21A : 233B
Packing Dimension(mm)	200x195x620 (1per box)
PART NO	FEL-FT-F09



EN3



SETSCO SG  
APPROVED

## Information

Effective against **class A fires** involving ordinary combustible materials like wood, paper, cloth, furning, plastics, rubber, etc, usually of an organic nature, in which combustion normally takes places with the formation of glowing embers.

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquefiable solids.

## Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. **P**ull out safety pin.

3. **A**im.

4. **S**queeze handle.

5. **S**weep.

## Accessories

(Default)



L Bracket

HeavyDuty Bracket

Due to constant improvements, product dimensions may differ slightly.

# 6 LITRE Wet Chemical Kitchen Fire Extinguisher



MODEL	FT01-06A (Rev 4)-00
Capacity	6 Litre
Extinguishing Agent	Wet Chemical Foam
Propellant	Nitrogen
Operation Method	Stored Pressure
Test Standard	SS EN3, BS EN3
Cylinder Diameter	160mm
Extinguisher Height	510mm
Total Height (Incl Hose)	630mm
Total Weight	10.16KG
Operating Temperature	5°C to 60°C
Working Pressure	15 BAR
Test Pressure	27 BAR
Fire Rating	13A 75F
Packing Dimensions(mm)	170x170x535 (1per box)
PART NO	FEL-RH-K06

## Information

Effective against **kitchen fires** especially those involving **deep fryers and grease**.

To prevent splashing of the oil, these extinguishers are equipped with an applicator lance. This provides a degree of safety to the person operating the extinguisher.

The unique lance applicator is designed to allow the wet chemical agent to disperse gently over the fire to prevent burning material from spreading.

## Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. Pull out safety pin.

3. Apply the wet chemical agent over the burning fire, keeping out of the smoke.

4. Ensure that extinguisher is located close to the work area and operators are trained in the use of extinguishers.



EN3



SETSCO SG  
APPROVED

## Accessories

(Default)



L Bracket

HeavyDuty Bracket

Due to constant improvements, product dimensions may differ slightly.



EN3



SETSCO SG  
APPROVED



Name	1KG	2KG	3KG	4KG	6KG	9KG	12KG	2KG CO2	5KG CO2	9L FOAM	6L Wet
Extinguish Agent	Multi Purpose Dry Chemical Powder Class AB										
Propellant	N2										
Cylinder Diameter	85	110	130	138	160	185	190	103	135.8	185	160
Total Height	334	363	363	447	520	540	590	565	755	585	630
ApproxTotal Weight	2KG	3.4KG	4.7KG	6.6KG	9.4KG	13.4KG	16.6	6.4KG	13.5KG	13.9	10.2
Operating Temp.	-30°C to 60°C										
Working Pressure	15BAR										
Test Pressure	30 BAR										
Fire Rating	8A:21B	13A:55B	21A:70B	27A:89B	34A 183B	43A:183B	55A:233B	21B	89B	21A:233B	27BAR
APPROVAL	SS EN3, BS EN3										

Due to constant improvements, actual product may slightly differ.  
 The use of Setesco marks and logo shall not be allowed, including any expression that may be direct or indirect without prior approval from Setesco Services Pte Ltd