# SAFETY DATA SHEET



#### according to Workplace Safety and Health Regulations Singapore

Flex 310 M Crystal MS-Polymer Presspack

### Section 1. Identification

**Product identifier** : Flex 310 M Crystal MS-Polymer Presspack

**Product code** : 133521

Relevant identified uses of the substance or mixture and uses advised against

Adhesives-Sealants

Elasticizer

: WEICON GmbH & Co. KG Supplier's details

> Königsberger Str. 255 48157 Münster

Germany

Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de

e-mail address of person responsible for this SDS

: msds@weicon.de

**Emergency telephone** 

number

: EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333

(English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44

1865 407333 (English)

### Section 2. Hazards identification

Classification of the : AEROSOLS - Category 3

SKIN SENSITIZATION - Category 1 substance or mixture

#### GHS label elements, including precautionary statements

Hazard pictograms



Signal word : Warning

**Hazard statements** : H229 - Pressurized container: may burst if heated.

H317 - May cause an allergic skin reaction.

**Precautionary statements** 

Prevention : P280 - Wear protective gloves.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 - Avoid breathing dust or mist.

P251 - Do not pierce or burn, even after use.

: P362 + P364 - Take off contaminated clothing and wash it before reuse. Response

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50

°C/122 °F.

**Disposal** : P501 - Dispose of waste according to applicable legislation.

Other hazards which do not : None known.

result in classification

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
1,3,3,3-Tetrafluoropropylene	≤5	1645-83-6
trimethoxyvinylsilane	<1	2768-02-7
N-(3-(trimethoxysilyl)propyl)ethylenediamine	<1	1760-24-3
decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester, mixt. with 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) decanedioate	≤0.3	1065336-91-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Chemical formula : Not applicable.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

**Skin contact**: Wash with plenty of soap and water. Remove contaminated clothing and shoes.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before

reuse. Clean shoes thoroughly before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. If material has been

swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

irritation redness

Date of issue/Date of revision: 9/16/2021Date of previous issue: 9/16/2021Version: 2.012/11

Flex 310 M Crystal MS-Polymer Presspack

### Section 4. First aid measures

**Inhalation**: Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing media

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

: Use an extinguishing agent suitable for the surrounding fire.

carbon dioxide carbon monoxide halogenated compounds

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01 3/11

### Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

#### Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Section 7. Handling and storage

#### Precautions for safe handling

#### Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

#### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

**Conditions for safe storage,** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
	[Air contaminant - Curing] Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 200 ppm 8 hours. PEL (long term): 262 mg/m³ 8 hours. PEL (short term): 328 mg/m³ 15 minutes. PEL (short term): 250 ppm 15 minutes.

#### Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version: 2.01

# Section 8. Exposure controls/personal protection

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended: 1 - 4 hours (breakthrough time): nitrile rubber 4 - 8 hours (breakthrough time): Viton®/butyl

rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapor (Type AX) and particulate filter

# Section 9. Physical and chemical properties

#### **Appearance**

Flash point

Physical state : Aerosol.

Color : Colorless.

Odor : Characteristic.

Odor threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not available.

Boiling point, initial boiling : Not available.

point, and boiling range

: Closed cup: >93.3°C (>199.9°F)

Fire point : 420°C (788°F)
Evaporation rate : Not available.

**Flammability** : Flammable in the presence of the following materials or conditions: open flames,

sparks and static discharge.

Slightly flammable in the presence of the following materials or conditions: heat.

Lower and upper explosion limit/flammability limit

: Lower: 0.4% Upper: 2.9%

Vapor pressure :

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01 5/11

# Section 9. Physical and chemical properties

	Vapor Pressure at 20°C		Va	por pressur	e at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
1,3,3,3-Tetrafluoropropylene	3202.8	427				
trimethoxyvinylsilane	8.93	1.2	EU A.4			

Relative vapor density : Not available. Relative density : Not available.

: 1.05 g/cm³ [20°C (68°F)] **Density** 

Solubility(ies)

Not available.

Solubility in water : Not available.

Miscible with water : No

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not applicable. **Decomposition temperature Viscosity** 

: Not available. : Not available. : Not available.

Flow time (ISO 2431) **Particle characteristics** 

Median particle size

: Not applicable.

Aerosol product

Type of aerosol : Spray

### Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

**SADT** : Not available.

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Oral	Rat	2413 mg/kg	-

#### **Irritation/Corrosion**

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
trimethoxyvinylsilane	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
	Skin - Mild irritant	Rabbit	-	mg 24 hours 500	-
N-(3-(trimethoxysilyl)propyl) ethylenediamine	Eyes - Severe irritant	Rabbit	-	mg 15 mg	-
oury or out and the	Skin - Mild irritant	Rabbit	-	500 mg	_

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

irritation redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01 7/11

# **Section 11. Toxicological information**

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
trimethoxyvinylsilane	N/A	N/A	N/A	11	N/A
N-(3-(trimethoxysilyl)propyl)ethylenediamine	2413	N/A	N/A	N/A	N/A

#### **Acute toxicity estimates**

	ATE value
Not available.	

# Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence/degradability

Not available.

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision: 9/16/2021Date of previous issue: 9/16/2021Version: 2.018/11

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

# **Section 14. Transport information**

	UN	IMDG	IATA	ADR/RID
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, non- flammable	AEROSOLS
Transport hazard class(es)	2.2	2.2	2.2	2
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

#### **Additional information**

UN : **Special provisions** 63, 190, 277, 327, 344, 381

**IMDG** : Emergency schedules F-D, S-U

**Special provisions** 63, 190, 277, 327, 344, 381, 959

**IATA** : Quantity limitation Passenger and Cargo Aircraft: 75 kg. Packaging instructions:

203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities -

Passenger Aircraft: 30 kg. Packaging instructions: Y203.

Special provisions A98, A145, A167, A802

ADR/RID : Limited quantity 1 L

**Special provisions** 190, 327, 625, 344

Tunnel code (E)

**ADR Classification Code:** 5A

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

# Section 15. Regulatory information

#### Singapore - hazardous chemicals under government control

Ingredient name	Status
hydrofluorocarbons, including any mixture containing any such hydrofluorocarbons	Listed

#### **International regulations**

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01

# Section 15. Regulatory information

#### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Australia : Not determined.
Canada : Not determined.
China : Not determined.

**Eurasian Economic Union**: Russian Federation inventory: All components are listed or exempted.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

**New Zealand** : Not determined. **Philippines** : Not determined. Republic of Korea : Not determined. **Taiwan** : Not determined. **Thailand** : Not determined. Turkey : Not determined. **United States** : Not determined. **Viet Nam** : Not determined.

#### Section 16. Other information

<u>History</u>

Date of printing : 5/14/2023 Date of issue/Date of : 9/16/2021

revision

**Date of previous issue** : 9/16/2021 **Version** : 2.01

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
AEROSOLS - Category 3 SKIN SENSITIZATION - Category 1	On basis of test data Calculation method

**References**: Not available.

Indicates information that has changed from previously issued version.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01 10/11

Flex 310 M Crystal MS-Polymer Presspack

# Section 16. Other information

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 9/16/2021 Date of previous issue : 9/16/2021 Version : 2.01 11/11