

**GPO****GP1****GP3****GP2****BGRP****VARIANTS**

**GPO**  
For use with 12.5 kg pails.  
Suction tube length 17-5/16"  
(440 mm)

**GP1**  
For use with  
25-50 lbs / 20 kg / 5 gal. pails.  
Suction tube length 17-5/16"  
(440 mm)

**GP2**  
For use with  
120 lbs / 50 kg / 16 gal. pails.  
Suction tube length 28-3/4"  
(730 mm)

**GP3**  
For use with  
400 lbs / 180 kg drums.  
Suction tube length 37-3/8"  
(950 mm)



**BGRP/15**  
Portable grease pump  
with built-in  
15 kg grease bucket

**BGRP/30**  
Portable grease pump  
with built-in  
30 kg grease bucket

**BGRP/50**  
Portable grease pump  
with built-in  
50 kg grease bucket

**ORDERING INFORMATION**

CAT NR.	ORD NR.	BUCKET CAPACITY	BOX QTY.
		(KG)	
<b>PORTABLE AIR OPERATED GREASE PUMPS</b>			
BGRP/15	45432	15	1
* BGRP/30	45430	30	1
BGRP/50	45431	50	1

\* Best Seller

**WARNING**

Pump must be supplied with clean & dry compressed air via an FR unit

# 68

## Air Operated Grease Ratio Pumps 50:1

World-class Industrial High Pressure Grease pumps with guaranteed performance & hassle free operation

Pump dispenses grease at pressures upto 50 times the air inlet pressure

Designed to work in tough conditions - these are ideal for use in Industry, Workshop, Farm, Construction or as part of the Mobile Grease System

All metal construction, fully CNC machined with hardened wear resistant moving parts

Reciprocating piston operated 2-1/2" (63 mm) dia. air motor

Fitted with strainer at suction tube inlet for clean grease to the bearing

Supplied complete with drum cover, rubber lined follower plate, 7' (84") of high pressure grease hose, Z swivel & professional grease control valve

Portable version available with built-in steel drum, complete with wheels & pull handle

### WETTED COMPONENTS

Steel, Brass, Aluminium, Polyurethane & Nitrile Rubber

### RECOMMENDED USE

With light and self collapsing grease up to NLGI No. 2

### SPECIFICATIONS

WORKING PRESSURE	30 to 150 PSI (2-10 BAR)
MAXIMUM AIR PRESSURE	150 PSI (10 BAR)
MAXIMUM OUTLET PRESSURE	7,500 PSI (500 BAR)
AIR INLET CONNECTION	1/4" BSP (F) / 1/4" NPT (F)
PUMP OUTLET CONNECTION	1/4" BSP (F) / 1/4" NPT (F)
AIR CONSUMPTION	230 LPM (61 GPM)
GREASE OUTPUT (NLGI NO. 2 GREASE)	1.10 kg/min. (2.42 lbs/min.)
NOISE LEVEL	81 db

### ORDERING INFORMATION

CAT NR.	ORD NR.	CAT NR.	ORD NR.	FITS	DRUM COVER DIAMETER		FOLLOWER PLATE DIMENSIONS						BOX QTY.
							O.D. STEEL END		O.D. PLATE		I.D. GROMMET		
BSP THREADS		NPT THREADS			(INCH)	(MM)	(INCH)	(MM)	(INCH)	(MM)	(INCH)	(MM)	
<b>PUMP ASSEMBLY</b>													
GP0/ST/501/BSP	45409	-	-	12.5 kg drums	11	284	9-3/64	230	10-1/8	257	1.16	29.5	3
GP1/ST/501/BSP	45410	* GP1/ST/501/N	45415	25-50 lb / 5 gal. / 20-30 kg pails	12	310	9-1/2	241	11-11/32	288	1.16	29.5	3
GP2/ST/501/BSP	45411	* GP2/ST/501/N	45416	120 lb / 16 gal. / 50-60 kg pails	15	381	12-11/16	322	15	380	1.16	29.5	3
GP3/ST/501/BSP	45412	GP3/ST/501/N	45417	400lb / 180 kg drums	24-1/2	612	21-5/8	550	23-11/16	602	1.16	29.5	2

\* Best Seller

