



REV	DESCRIPTION	DATE
-----	-------------	------

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : $\frac{\text{A.W.G. } 16 \mid 14}{\text{AMP. } 10 \mid 15}$
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : NYLON
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : BRASS
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. NEMA TAB : 0.032 inch * 0.250 inch (0.8 mm * 6.35 mm)
 8. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
 9. TERMINAL SURFACE TREATMENT : TIN PLATED
 10. TERMINAL THICKNESS : 0.40 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° ° REF ±
18 > 30 mm ± 0.40	° ° ±
30 > 75 mm ± 0.50	° ° ±

NAME	NYLON-INSULATED DOUBLE CRIMP PIGGY BACK DISCONNECTORS			UNIT	
PART NO.	PBDNYD2-250	MATERIAL	-----	APPROVE	
NUMBER	KA-94347-C	SCALE	SHEET PAGE	CHECKED	
DATE	2007/08/28	3/1	1-0 10F2	DRAWN	吳金賢

