



Main

Range	New Unica
Product or component type	Push-button
Device presentation	Mechanism with fixing frame
Bus type	KNX
Colour tint	White (RAL 9003)
Provided equipment	User manual Fixing frame Set of 20 symbols

Complementary

Range compatibility	KNX
Device mounting	Flush
Technology type	Electronic
Function available	Pulse edges with 2-byte telegrams Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams
Number of modules	2 modules
Number of rocker	2
Transmission support medium	Twisted pair
Number of FUNCTION keys	4
Control type	Rocker
Cover type	Label holder
Operating mode	KNX bus system
Local signalling	4 blue LED
Fixing mode	Screws
Material	Plastic glossy
Height	74.6 mm
Width	74.6 mm
Depth	37.5 mm
Embedding depth	24 mm
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	9.5 cm
Package 1 Length	9.5 cm
Package 1 Weight	122 g
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.414 kg
Package 3 Height	91 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins