



Main

| | |
|---------------------------|---|
| Range | ZENcolo |
| Product or component type | Switch |
| Load type | Fluorescent lamp Resistive Inductive Incandescent lamp |
| Colour tint | Silver satin |
| Cover frame colour tint | Silver satin |

Complementary

| | |
|-------------------------|---|
| Device mounting | Flush Surface |
| Switch function | 2-way |
| Rated current | 20 A at 250 V AC 50/60 Hz 16 AX |
| Local signalling | Mechanical indicator (amber) |
| Number of gangs | 3 gangs |
| Material | Polycarbonate + GF 20 %: grid plate Polycarbonate: base Polycarbonate: cover Polycarbonate: surround |
| Connections - terminals | Brass rod terminals |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 31 mm |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -5...35 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | No UV resistant |
| Operating altitude | 2000 m |
| Standards | MS IEC 60669-1 IEC 60669-1 GB 16915.1 SS 227-1 EN 60669-1 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 134.5 g |
| Package 1 Height | 3.5 cm |
| Package 1 Width | 8.7 cm |
| Package 1 Length | 8.7 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |