

# Datasheet

## AT4004 Class B 130 °C Polyester Tape

RS Stock No: 4089502  
4089489  
4089495



### NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

### STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

### General Description

A single-sided polyester tape with a rubber thermosetting adhesive.

- High temperature resistance.
- High electrical strength.
- Good resistance to solvents

### Specification

Recognised by UL.

### Technical Details

Typical Values

Thickness	0.06mm
Breaking Load	45 N/cm
Elongation	90%
Adhesion to steel	4.5 N/cm
RoHS Compliant	Yes
Breakdown Voltage	4.5kV
Service Temperature	0 °C to +130 °C
Application Temp.	+10 °C to +40 °C

\*Standard charge for certificate: £25.00.