Product datasheet Characteristics

E8233L1F_LS

16AX 250V 3 Gang 1 Way Switch with Fluorescent Locator, Lavendar Silver





Main

Range	Pieno	
Product or component type	Switch	
Switch application	Switch	
Load type	Resistive Fluorescent	
Cover frame colour tint	Lavender silver	-

Complementary

Main		
Range	Pieno	
Product or component type	Switch	
Switch application	Switch	
Load type	Resistive Fluorescent	
Cover frame colour tint	Lavender silver	
Complementary Device mounting	Flush	
•	Surface	
Wiring device mounting	Surface Flush	
Switch function	1-way	
Rated current	16 AX at 250 V AC 50 Hz	
Local signalling	Fluorescent (white)	
Number of gangs	3 gangs	
Material	Polycarbonate: surround Polycarbonate: grid plate	
Connections - terminals	Pillar terminals	
Clamping connection capacity	2 x 1.5 mm² for stranded cable(s) 2 x 2.5 mm² for solid cable(s)	
Embedding depth	23 mm	
Width	87 mm	
Height	87 mm	
Depth	23 mm	
Environment		
Ambient air temperature for operation	-540 °C	

Environment

mbient air temperature for operation -540 °C
--

Relative humidity	095 %	
Standards	MS IEC 60669-1 IEC 60669-1	
	GB 16915.1	
	SS 227-1	
	BS EN 60669-1	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

	Warranty	18 months
--	----------	-----------