IP65 3P Power Connectors Multicomp PRO











RoHS **Compliant**




Receptacle





Plug





Material and specification

Coupling : Bayonet

Shell material : Plug: Nylon PA66 Socket: PC Insert material : PPS. max temperature 260°C Contact material : Brass with silver plating

Rated current (A) : 20 : 250 Rated voltage (AC. V) Test voltage (AC.V) 1 min : 2500 Insulation resistance (MΩ) : 2000 : 1000 Mating cycle

Temperature range : -40°C to +85°C

: IP65 IP rating

Cable Outer Diameter Range : 9mm to 13mm

Termination : Receptacle: 3/16" flat tab terminals Plug: screw

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



IP65 3P Power Connectors multicomp



Part Number Table

Description	Part Number
Power Connector, 3P, Receptacle, Blue, Quick Connect	MP004797
Power Connector, 3P, Plug, Blue, Screw	MP004798
Power Connector, 3P, Receptacle, Grey, Quick Connect	MP004799
Power Connector, 3P, Plug, Grey, Screw	MP004800

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

