





Color Palettes

## **Acision PTC7300 Pocket Thermal Camera**

Acision PTC7300 is equipped with a high-resolution 256 x 192 (49,152 pixels) detector, a high-resolution configurable 2MP, 5MP, 8 MP optical lens, and a 8.89 cm LCD touch screen.


The 3 level/span modes (manual, auto, 1-tap) improve the image contrast and help the user locate faults faster and more efficiently, and to measure temperatures more accurately. The wide temperature range of -20 °C to 400 °C is ideal for building inspections, HVAC, electrical, and mechanical equipment maintenance.

## **Key Features:**

- 256x192 thermal resolution (NETD < 40 mK) ultra high resolution</li>
- Multiple image modes Thermal, Fusion, PIP, Optical
- · Measurement presets center spot, hot spot, cold spot, off
- · Portable design fits easily into pocket and tool bag
- IP54 rating and 2-meter drop test protection suitable for industrial use
- 3.5in color LCD Touch Screen display; 640x480 resolution; 1x to 4x digital zoom
- Level and span modes (Auto, Manual, 1-tap touchscreen)
- High-temperature alarm audio/visual alerts to high temperatures
- LED work light work safely in dark environments
- 7 Color palettes white hot, black hot, rainbow, iron bow, red hot, fusion, rain
- 25 Hz fast image frequency smooth video, measurements if panning scenes, moving targets
- 4hrs continuous running battery life
- Field of View 50° x 37.2°
- Storage 16GB internal; 60K images, 10hrs video, radiometric JPEG with measurement data









Contact your authorised distributor at:

| 1 <u> </u> |  |  |
|------------|--|--|
| ſ          |  |  |
|            |  |  |
|            |  |  |
|            |  |  |
|            |  |  |
|            |  |  |
|            |  |  |
|            |  |  |
|            |  |  |
|            |  |  |
| Į.         |  |  |



**ACISION** 

## PTC7300 Pocket Thermal Camera

| Detector Size                     | 256 x 192 Sensor     |
|-----------------------------------|----------------------|
| Thermal Sensitivity               | 40 mK (NETD)         |
| Temperature Range Max             | 400 C                |
| Temperature Range Min             | -20 C                |
| Image Frequency                   | 25 Hz                |
| Field of View                     | 50x37.5 Degrees      |
| Screen Size                       | 8.89 cm              |
| IR/Overlay Fusion Image           | Yes                  |
| Video Output                      | Yes                  |
| Focus                             | Fixed                |
| Laser Spot                        | Yes                  |
| Picture in Picture                | Yes                  |
| Video Recording                   | Yes                  |
| Touch Screen Display              | Yes                  |
| Minimum Focus Distance            | 0.3 M                |
| Accuracy                          | Max. (+/- 2C, +/-2%) |
| Battery operating time Continuous | 4 HR                 |
| Camera Light                      | Yes                  |
| IR Digital Zoom                   | Yes                  |
| Voice Annotation                  | Yes                  |

| Warranty              | 2 YEARS         |
|-----------------------|-----------------|
| Safety Approval       | RoHS            |
| IP Rating             | IP54            |
| Product Weight        | 218grams        |
| Product Height        | 13.85cm         |
| Product Length        | 8.51cm          |
| Product Width         | 2.36cm          |
| HTS/Schedule B Number | 9027.50.4020    |
| ECCN Number           | 6A003.b.4.b     |
| Power Supply Voltage  | Battery Powered |

## Items comes with:

- Compact Thermal Imaging Camera
- USB Cable
- Wrist Strap
- Quick Start Guide
- Carrying Pouch



Contact your authorised distributor at: