## SB 18 LTX Impuls (602192500) Cordless hammer drill 18V 2x4Ah Li-Power; Charger ASC 55 (220-240 V / 50 - 60 Hz); metaBOX 145 L



Product may differ from Image







- Robust cordless hammer drill with maximum power for very demanding applications
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Robust, durable gear housing made from aluminium die-cast
- Spindle with magnetic hexagon recess for screwdriver bits for working without chuck
- Powerful Metabo 4-pole motor for fast drilling and screwdriving
- High-performance impact mechanism for optimum drilling performance
- Euro collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- With handy belt hook and bit case which can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage

## metabo

Technical data	
Characteristics	
Type of battery pack	Li-Power
Battery voltage	18 V
Battery pack capacity	2 x 4 Ah
Maximum torque, soft	55 Nm / 487 in-lbs
Pulse torque	60 Nm / 531 in-lbs
Maximum torque, hard	110 Nm / 974 in-lbs
Adjustable torque	1.5 - 24 Nm // 13 - 212 in-lbs
Drill-Ø masonry	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	65 mm / 2 1/2 "
No-load speed	0 - 500 / 0 - 1700 rpm
Maximum impact rate	32300 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 m / 1 11/16 "
Weight without battery pack	1.8 kg / 4 lbs
Weight with battery pack	2.5 kg / 5.5 lbs
Vibration	
Drilling in metal	2.5 m/s²
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Impact drilling concrete	13 m/s²
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Screwdriving without impact	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	80 dB(A)
Sound power level (LwA)	91 dB(A)
Uncertainty of measurement K	3 dB(A)