

FEATURES

- Latching contact
- Thermoplastic body
- Compact

RS RS PRO Push-Button Latching Contact Blocks – 1NO

RS Stock No.: 2398161



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Push Button Accessories



Hook-up electrical contact to be used in combination with the 2398162 and 2398174 support bases.

General Specifications

Casing Material	Thermoplastic		
Operator	Contact element 2398161		
Color	Green Arrow		
Microswitch	1NO		
Connecting Terminals	Screw with captive cable clamp		
Connecting Cables Dimensions [mm ²]	1 or 2 conductors - 0.5 2.5		
Fixing	Hooking		

Mechanical Specifications

Operating Temperatures [°C]	-25 / +70
Stock Temperatures [°C]	-40 / +80
Mechanical durability (Millions of operations)	1
B10d (million of operations)	2
Max. switching frequency [Cicli/h]	3600

Electrical Specifications

Protection against electrical shocks	Class II - Double insulation
Rated Insulating Voltage Ui [V]	690
Pollution Degree	3
Contact rating secondo UL508	A 600 Q 300
Rated impulsive voltage [kV]	8
Conventional thermal current in air free lth (θ min 40 ° C) [A (θ	10



Push Button Accessories



Short circuit protection (EU min 500Vac - fuses type gG (gl)) [A]	10
Rated Operational Current le - AC-15 (50-60 Hz) [Vac - A]	24V - 10A / 240V - 6A / 400V - 4A
Rated Operational Current DC-13 [Vdc - A]	24V - 2,8A / 125V - 0.55A / 250V - 0.27A
Resistance Between Contacts $[m\Omega]$	25

Protection Category		
IP Degree of Protection	20	

Additional Information	
EAN	8000126233360
Custom Tariff Number	85371098

Classification

eCl@ss (Version)	
UNSPSC (Version)	

Approvals	
Declarations	CE – UKCA
Standards Met	EN 60947-5-1 and UL 508

Similar Products

Stock No.	Brand	Product Name	Attribute 1	Attribute 2	Attribute 3
XXX-XXXX	RS PRO				
XXX-XXXX	RS PRO				



Connection Diagrams / Assembly Diagrams / Illustrations / Accessories