

Datasheet

RS Pro Flat Ribbon Cable Interface Module, DIN Rail Mount, Male, 34 Pole, 125 V ac/dc, 1A, 96mm

RS Stock No: **665-9661**



Product Details

RS Pro flat ribbon cable interface module has a male plug with 34 contacts to support 14 to 22 AWG flat ribbon cable connection of EN 60 603-13/DIN 41651 specification. This module features a compact design with clear termination labelling and simple assembly. It features an ejector mechanism for cable removal. The module has an insulating stripping length of 7 mm. It is the best alternative to pure individual wire approach. It measures 47 x 96 x 61 mm.

Features and Benefits

- Screw clamp connection
- Male plug - flat ribbon cable connection EN 60 603-13/DIN 41651
- DIN EN 50178; DIN VDE 0110, pollution degree 2
- Ejector mechanism
- Compact design, clear terminal labelling and simple assembly
- Insulating stripping length 7 mm
- Alternative to pure individual wire approach

**Specifications:**

| | |
|-------------------------------|----------------------------|
| Cable CSA | 0.2 to 2.5 mm ² |
| Connector Type | Flat Ribbon Cable |
| Current Rating | 1 A |
| Depth | 47 mm |
| Dimensions | 96 x 61 x 47 mm |
| Gender | Male |
| Length | 96 mm |
| Maximum Operating Temperature | +50°C |
| Minimum Operating Temperature | -20°C |
| Mounting Type | DIN Rail Mount |
| Number of Contacts | 34 |
| Test Proof Voltage | 0.67 kV ac |
| Voltage Rating | 125 V ac/dc |
| Width | 61 mm |
| Wire Size | 22 to 14 AWG |
| Number of Poles | 34 |
| | |