

SRTL3KRM1UIC

APC Smart-UPS Ultra On-Line, 3000VA, Lithium-ion, Rack/Tower 1U, 230V, 3x C13, 2x C19 IEC outlets, SmartConnect, Extended runtime, W/rail kit



Overview

Presentation	Ultra high density on-line power protection with scalable runtime supported by Lithium-Ion batteries.
Lead time	Usually in Stock



Main

Main Input Voltage	230 V
Other Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	230 V
Rated power in W	3000 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Output connection type	3 IEC 60320 C13 2 IEC 60320 C19
Number of rack unit	1U
Cable length	2.44 m
Number of cables	1
Battery type	Li-Ion (Lithium-Ion)
Provided equipment	RJ45 cable USB cable Safety guide Rack mounting brackets Rack mounting support rails Wall mounting brackets Stabilization feet Screws

Complementary

Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use
------------------	---

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Batteries & Runtime

Battery recharge time	1.5 h
Number of battery replacement quantity	1
Battery voltage	50 V
Battery charger power	448 W
Battery design life	8...10 year(s)
Battery life	8...10 year(s)
Extended runtime	1

General

Product web sub-family	High density
Redundant	No

Physical

Colour	Silver grey
Height	43 mm
Width	432 mm
Depth	560 mm
Net weight	15.9 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit Tower-mounted with kit
Two post mountable	1
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Network frequency	50/60 Hz auto-sensing
Input voltage limits	160...275 V adjustable (half load)

Output

Maximum configurable power in W	3000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	On-Line
Wave type	Sine wave
Output harmonic distortion	< 2% at 100% linear load and < 5% at 100% non-linear load
Bypass type	Internal bypass (automatic and manual)
Efficiency	98 %
Maximum configurable power in VA	3000 VA

Conformance

Product certifications	CE[RETURN]UKCA
Marking	CE Mark UKCA
Standards	EN/IEC 62040-1 EN/IEC 61000-4-8 EN/IEC 61000-4-6 level 3 EN/IEC 61000-4-2 level 3 EN/IEC 61000-4-3 level 3

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dB
Heat dissipation	325 Btu/h
IP degree of protection	IP20

Communications & Management

Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use RJ45: port monitoring USB: port monitoring


Surge Protection and Filtering

Surge energy rate	1600 J
-------------------	--------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.8 cm
Package 1 Width	56.4 cm
Package 1 Length	76.4 cm
Package 1 Weight	24.2 kg

Offer Sustainability

RECh Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	5 years repair or replace
----------	---------------------------