



Main

| | |
|---------------------------|---|
| Range | ClimaSys |
| Product name | ClimaSys CV |
| Product or component type | Fan |
| Type of filter | Standard |
| Flow rate | Free flow rate with standard filter: 80 m ³ /h |
| [Us] rated supply voltage | 10...27.6 V |
| Input voltage | 24 V DC |

Complementary

| | |
|---------------------------------------|---|
| Absorbed power | 7.6 W |
| [In] rated current | 0.3 A |
| Noise level < at | 46...49 dB |
| Bearing type | Ball |
| Height | 170 mm external: |
| Width | 150 mm external: |
| Depth | 62 mm external: |
| Cut-out dimensions | 125 x 125 mm |
| Net weight | 0.48 kg |
| Material | Outlet grille: injected thermoplastic (ASA PC) |
| Colour | Outlet grille: grey (RAL 7035) |
| Ambient air temperature for operation | -10...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Maximum pressure | 50 Pa flow rate 0 m ³ /h |
| Connections - terminals | Cable |
| IP degree of protection | IP54 |
| Device composition | 1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template 1 power cord |
| Condition of use | Overfrequent filter replacement should be avoided Outside temperature must be 5 °C lower than inside temperature Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Flow rates depends on the work point, see ProClima software |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.5 cm |
| Package 1 Width | 15.5 cm |
| Package 1 Length | 17.5 cm |
| Package 1 Weight | 540 g |
| Unit Type of Package 2 | P12 |

| | |
|------------------------------|--------|
| Number of Units in Package 2 | 320 |
| Package 2 Height | 120 cm |
| Package 2 Width | 80 cm |
| Package 2 Length | 116 cm |
| Package 2 Weight | 190 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|