

BESTLIGHT1 OB

Ultra-light, universal clog

Upper	Expanded EVA
Lining	N/A
Footbed	SJ Basic 2
Outsole	EVA/Rubber
Safety standard	OB / SRC
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.197 kg
Norms	EN ISO 20347:2012























Chemically & UV sterilizeable This shoe is chemically and UV



Washable 30°C These shoes can be washed in a washing machine at 30°C.





Industries:

Catering, Chemical, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347		
Upper	Expanded EVA					
	Upper: permeability to water vapor	mg/cm²/h	N/A	≥ 0.8		
	Upper: water vapor coefficient	mg/cm²	N/A	≥ 15		
Lining	N/A					
	Lining: permeability to water vapor	mg/cm²/h	N/A	≥ 2		
	Lining: water vapor coefficient	mg/cm²	N/A	≥ 20		
Footbed	SJ Basic 2					
	Footbed: abrasion resistance	cycles	N/A	≥ 400		
Outsole	EVA/Rubber					
	Outsole abrasion resistance (volume loss)	mm³	83.0	≤ 150		
	Outsole slip resistance SRA: heel	friction	0.45	≥ 0.28		
	Outsole slip resistance SRA: flat	friction	0.46	≥ 0.32		
	Outsole slip resistance SRB: heel	friction	0.22	≥ 0.13		
	Outsole slip resistance SRB: flat	friction	0.32	≥ 0.18		
	Antistatic value	MegaOhm	N/A	0.1 - 1000		
	ESD value	MegaOhm	N/A	0.1 - 100		
	Heel energy absorption	J	N/A	≥ 20		

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and maynot be used or reproduced in any format, without written consent from us.



