



**Cable and Fibre Type**

Grade of the cable: LSZH

Fibre type (ISO/IEC 11801-2002)		Outer Sheath Colour
62.5/125	OM1	Orange
50/125	OM2	Orange
50/125	OM3	Purple
09/125	OS1	Yellow

**Optical Performance (IEC 61300-3-4):**

**Multimode (@ 1300nm)**

MTRJ: Max. IL - 0.50dB Typical: 0.30dB

ST : Max. IL - 0.30dB Typical: 0.20dB

**Singlemode: (@1310nm and/or 1550nm)**

MTRJ: Max. IL - 0.50dB Typical: 0.30dB Return Loss: >40dB

ST : Max. IL - 0.30dB Typical: 0.20dB Return Loss: >50dB

**RoHS Compliant**

**Coiling Diameter:** Coiling Diameter of the patchcord shall be greater than 200mm

**Packing:** Each product shall be individually bagged and identified with a unique number printed on an ID label affixed to the product. Also, each product will be supplied with a Test Certificate.

Id No.	Description	Ea
1.	ST Connector	2
2.	ST Boots	2
3.	MTRJ Connector	1
4.	MTRJ Boot	1
5.	Identification Label	1
6.	1.6mm Duplex Cable (L m)	1
7.	Black Tape	1



REV	DESCRIPTION	DATE	DRN	APD	REV	DESCRIPTION (REVISION RECORD)	DATE	DRN	APD
MATERIAL		SIZE	TITLE		DGN				
FINISH		TOLERANCES UNLESS OTHERWISE SPECIFIED:	PART NO.		DWC/REF NO.		DRN		
SCALE		0 PLC ± TOL0	REV		CHD		QA		
ALL DIMENSIONS IN MM		1 PLC ± TOL1	SHEET		APD		VER		
		2 PLC ± TOL2	1 OF 1		SIGNATURE		DATE		
		3 PLC ± TOL3							
		4 PLC ± TOL4							
		ANGLES ± ANG							