



HUSQVARNA 365

Husqvarna 365 is a saw for typical professional use. It has been developed in close cooperation with professional users working in the most demanding conditions. The low weight and high power are combined with a rugged engine, making this saw exceptionally versatile and suited for a wide variety of applications.




Adjustable oil pump

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.



Air Injection

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



Magnesium crankcase

Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.



Side-mounted chain tensioner

Side-mounted chain tensioner makes chain adjustment quick and easy.



FEATURES

- Magnesium crankcase designed for professional use
 - Less filter cleanings with Air Injection
 - Adjustable chain oil pump
- Quick and easy chain adjustment
 - Ergonomic grip with angled front handle
 - Quick-release air filter

Technical specifications	
DIMENSIONS	
Weight (excl. cutting equipment)	6.4 kg
ENGINE	
Cylinder displacement	65.1 cm³
Electrode gap	0.5 mm
Fuel tank volume	0.77 l
Idling speed	2700 rpm
Maximum power speed	9300 rpm
Power output	3.4 kW
Spark plug	Champion RCJ7Y, NGK BPMR7A
EQUIPMENT	
Bar mount	Large
Chain speed at max power	20.7 m/s
Chain speed at 133% of maximum engine power speed	27.5 m/s
Pitch	3/8"
Recommended bar length, max	70 cm
Recommended bar length, min	38 cm
Sprocket type	Rim 7
LUBRICANT	
Oil pump capacity Max	20 ml/min
Oil pump capacity Min	4 ml/min
Oil pump type	Automatic
Oil tank volume	0.4 l
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	114 dB(A)
Sound power level, measured	111 dB(A)
Sound pressure level at operators ear	102.5 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) front handle	5.7 m/s²
Equivalent vibration level (ahv, eq) rear handle	8.0 m/s²
Material content, other plastics	0.017 kg
Material content, PBT	0.018 kg
Material content, PE	0.192 kg
Material content, PP	0.023 kg
Material content, POM	0.12 kg
Material content, silicone rubber	0.001 kg
Material content, nitrile rubber	0.0012 kg
Material content, hydrogenated nitrile rubber	0.009 kg
Material content, fluorosilicone rubber	0.0001 kg
Material content, fluorocarbon rubber	0.026 kg

PXM_SPAREPARTS

AIRFILTER-NYLON 80
575 26 91-01

AIRFILTER-NYLON 44M
575 26 91-02

AIRFILTER-FELT
575 26 91-03

SPARK PLUG RCJ7Y
503 23 51-08





503 78 72-01



503 43 29-02

503 85 95-01

537 01 55-01



FUEL FILTER FOR MOST OF OUR
HANDHELD PRODUCTS
503 44 32-01

503 22 00-01



537 04 41-02




501 68 68-01



ANTIVIBRATION STANDARD
503 63 76-01



ANTIVIBRATION STANDARD
503 89 56-01



502 52 92-01



REPL. RIM 3/8"X7T
501 59 80-02



REPL. RIM 3/8"X8T
505 30 36-61



503 52 13-03

503 74 44-01



503 75 22-02



503 28 90-15

503 81 80-05



503 63 75-02



SPUR SYSTEM 3/8"X7T
503 86 17-03

503 81 80-06