



Cable entry set, IP66, Consisting of: 1 x KDS-SR 1-4 BK, 1 x KDS-Inlay 4 BK

RAL: 9005

Business data

Abez 3 - product description	Cable Entry
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	45.5
Weight per piece (including packaging)	64.5
Unit of weight	G
Customs number	39259020
Country of origin	DE

Datasheet

RS Stock no. 1856068



Technical Data

Dimensions

Length	81 mm
Length of wall cutout	46 mm
Width	70 mm
Width of wall cutout	46 mm
Height	19.6 mm
Installation height	19.6 mm
Diameter of the screw holes	5.5 mm

Materials

Material	Polyamide 6.6
Glass-fibre reinforced	✓
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Sealing material	Polyurethane-based
Type of seal	Sealing and moulded flexible foam
Halogen-free	✓
Silicone-free	✓

Datasheet

RS Stock no. 1856068



Technical Data

Further technical data

Mounting type	Screws
Protection	IP66
NEMA Type	4x
Number of screw holes	4
Fixing screws	M 5 (ISO 4762 / DIN 912)
Torque of the fixing screws	3 Nm

Datasheet

RS Stock no. 1856068



Approvals

cUL approval

cUL approval	C22.2 No. 14-95
--------------	-----------------

cUL approval granted	✓
----------------------	---

UL approval

UL approval	UL 508
-------------	--------

UL approval granted	✓
---------------------	---

Datasheet

RS Stock no. 1856068



Media

