

## FEATURES

- **Material:** UL approved Nylon 66, 94V-2
- **Color:** Grey (RAL7035) available in other colors.
- **Suit a variety of applications, and diverse industries.**
- **Function :** Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal, and then tighten up the nut to hold cables in position.
- **Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.**

## RS PRO Cable Gland

RS Stock No.: 214-1073



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

### Product Description

- Material: UL approved Nylon 66, 94V-2
- Color: Grey(RAL7035), available in other colors.
- Suit a variety of applications, and diverse industries.
- Function :Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal,and then tighten up the nut to hold cables in position.
- Feature : Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.
- Available to order the accessories separately. Follow the drawing and add the letter to the suffix part number,L for locknut, W for washer, B for gland body, S for seal, N for nut.

### General Specifications

<b>Series</b>	Metric Thread
<b>Type</b>	Cable Gland
<b>Colour</b>	Grey(RAL7035)
<b>Material</b>	Nylon 66
<b>Finish</b>	
<b>Application</b>	
<b>Resistant To</b>	
<b>UV Resistant</b>	No
<b>Minimum Operating Temperature</b>	-40°C
<b>Maximum Operating Temperature</b>	85°C
<b>Fire Behaviour</b>	Self-Extinguishing
<b>Quantity</b>	5pc

### Mechanical Specifications

<b>Thread</b>	<b>M12/16 x P1.5</b>
<b>Mounting Hole</b>	
<b>Cable Range</b>	

### Protection Category

<b>IP Rating</b>	IP68 (only if the locknut and washer are assembled)
------------------	---

**Approvals**

<b>Declarations</b>	
<b>Standards Met</b>	RoHS, CE, HF



RS Article	Thread	Mounting Hole	D1	D2	B1	L1	L2	L3	Cable Range	Packing
2141073	M12xP1.5	12.0~12.3	12	7.3	6.5	8	20	13	3 ~ 6.5	5PCS

\*\* IP68 (only if the locknut and washer are assembled)

