



Semi-Electric Stacker PM Series

Semi-Electric Stacker

Capacity: 1000, 1500KG



PM1025

Model			PM1016	PM1025	PM1029	PM1031	PM1033
			PM1516	PM1525	PM1529	PM1531	PM1533
Load Capacity	Q	(kg)	1000/1500				
Load Center	C	(mm)	600				
Overall Length	L1	(mm)	1807				
Overall Width	W	(mm)	810	810	810	910	910
Min. Overall Height	H1	(mm)	2100	1775	2000	2100	2200
Fork Dimension	L×b×m	(mm)	1150×160×56				
Outside Width of Forks	D	(mm)	560/660				
Base Distance	L0	(mm)	1170				
Front Wheel Size		(mm)	Ø82×80/Ø78×70				
Steering Wheel Size		(mm)	Ø180×50				
Min. Steering Radius	Wa	(mm)	1435				
Min. Width of Aisle		(mm)	≥2370				
Max. Height of Forks	H	(mm)	1600	2450	2900	3100	3300
Max. Overall Height	H2	(mm)	2172	3022	3472	3672	3872
Min. Height of Forks	H3	(mm)	90				
Lift Motor		(Kw)	1.6				
Battery Capacity		(Ah/V)	120/12				
Net Weight (with battery)		(kg)	398	438	458	468	478
		(kg)	402	442	462	472	482

Semi-Electric Stacker

with straddle leg



PM1025W

Model			PM1016W	PM1025W	PM1029W	PM1031W	PM1033W
			PM1516W	PM1525W	PM1529W	PM1531W	PM1533W
Load Capacity	Q	(kg)	1000/1500				
Load Center	C	(mm)	600				
Overall Length	L1	(mm)	1645				
Overall Width	W	(mm)	1510				
Min. Overall Height	H1	(mm)	2100	1775	2000	2100	2200
Fork Dimension	L×b×m	(mm)	1000×100×35				
Outside Width of Forks	D	(mm)	220-790				
Base Distance	L0	(mm)	1170				
Front Wheel Size		(mm)	Ø82×80/Ø78×70				
Steering Wheel Size		(mm)	Ø180×50				
Min. Steering Radius	Wa	(mm)	1435				
Min. Width of Aisle		(mm)	≥2370				
Max. Height of Forks	H	(mm)	1600	2450	2900	3100	3300
Max. Overall Height	H2	(mm)	2175	3025	3475	3675	3875
Min. Height of Forks	H3	(mm)	65				
Lift Motor		(Kw)	1.6				
Battery Capacity		(Ah/V)	120/12				
Net Weight (with battery)		(kg)	442	487	507	517	527
		(kg)	447	492	512	522	532