



Main

Range	PowerLogic
Device short name	VLT
Product or component type	Voltmeter
Range compatibility	Prisma Prisma P door Prisma Prisma G door
Scale	0-500 V
Technology type	Ferromagnetic
Scale type	80 mm over 90°
Mounting support	Front face

Complementary

Type of measurement	Voltage
Accuracy class	Class 1.5
Power consumption in VA	3 VA
Power consumption in VA	3 VA
Overload withstand	1.2 Un, permanently 2 Un, 5 s
Device mounting	Flush
Operating position	30°/vertical
Width	96 mm
Height	96 mm
Depth	75 mm
Temperature drift	+/- 0.003 %/°C

Environment

Standards	IEC 61000-4 IEC 60051-1 IEC 61010-1
IP degree of protection	IP52
Ambient air temperature for operation	-25...50 °C
Reference temperature	23 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.5 cm
Package 1 Width	11.0 cm
Package 1 Length	11.5 cm
Package 1 Weight	282.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.83 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------