



ENGLISH

Datasheet

**RS Pro Red SPDT Rocker Switch, (On)-Off-(On), 5 A @ 250 V ac +85°C -30°C 15.7mm 12.7mm**

RS Stock No: **734-6861**



## Product Details

RS Pro SPDT rocker switch features silver plated brass contacts with a mechanical life of 40000 make and break cycles. This panel mount switch in red colour, performs on-off-on operation. It has nickel plated brass bushings and stainless steel housing for added durability.

## Features and Benefits

- SPDT configuration
- Mechanical life of 40000 make and break cycles
- Brass bushing
- Stainless steel housing

**Specifications:**

AC Voltage Rating	125 V, 250 V
Actuator Colour	Red
Case Material	Diallyl Phthalate
Contact Configuration	SPDT
Contact Current Rating	5 A at 120 V ac, 2 A at 250 V ac
Contact Material	Silver Plated Brass
Contact Resistance	10 mΩ
Maximum Operating Temperature	+85°C
Mechanical Life	40000 cycles
Minimum Operating Temperature	-30°C
Mounting Type	Panel Mount
Operating Temperature Range	-30 to +85°C
Panel Cut Out Height	12.7 mm
Panel Cut Out Size	12.7 x 15.7 mm
Panel Cut Out Width	15.7 mm
Switch Operation	(On)-Off- (On)
Terminal Type	Solder
Dielectric Strength	1000 V rms
Insulation Resistance	1000 MΩ
Standards Met	RoHS Compliant