

## FEATURES

- Three poles
- Three-phase starter
- Automatic motor starter functionality
- Disconnect switch included
- DOL motor starter type
- Range available with and without isolator
- Power rating of 7.5kW
- Voltage rating of 400VAC
- Current rating of 13A to 18A

# RS PRO 7.5 kW DOL Starter, 400 V ac, 3 Phase, IP65

RS Stock No.: 725-5531



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

This DOL starter is a 7.5 kW automatic 3-phase starter. You might like to fit it with an overload protection device that will help prevent problems from short-circuiting or overheating. This model doesn't include an overload, so you would need to select one from the RF38 series – for example, stock no. 685-130 – to match the full-load current of your motor.

## General Specifications

<b>Motor Starter Type</b>	DOL
<b>Motor Starter Functionality</b>	Automatic
<b>Number of Poles</b>	3P
<b>Motor Supporting Range</b>	5.5kW to 11kW
<b>Reversibility</b>	No
<b>Enclosure</b>	Yes
<b>Material</b>	Plastic
<b>Additional Features</b>	Disconnect Switch Included
<b>Applications</b>	Workshop machinery, large fans and water pumps

## Electrical Specifications

<b>Phase</b>	3
<b>Power Rating</b>	7.5kW
<b>Voltage Rating</b>	400VAC
<b>Current Rating</b>	13A to 18A
<b>Maximum Allowed Motor Current</b>	18A

## Mechanical Specifications

Overall Length	225mm
Overall Width	110mm
Overall Depth	148mm

## Operation Environment Specifications

Operating Temperature	-25°C to 60°C
-----------------------	---------------

## Protection Category

IP Rating	IP65
-----------	------

## Approvals

Compliance/Certifications	CE
Standards Met	RoHS Compliant; IEC/EN 60947-1; IEC/EN 60947-4-1

