Blue Gizmo Infrared Thermometer with K-Type thermocouple built-in-jack BG 55







Type-K thermocouple is available upon request.



Features

- High / Low Alarm
- MIN, MAX, AVG functions
- Adjustable Emissivity
- Compact and easy to carry
- Large LCD Display
- Built-in K-Type thermocouple socket
- Circle Laser
- Point and Shoot Concept

Applications

- Electrical troubleshooting
- Automotive repair and maintenance
- Air conditioner
- Science experiment
- Manufacturing processes of semiconductor technology
- Food safety and processing
- Perform HVAC energy audits

SPECIFICATIONS

Measurement Range

Accuracy (Tamb = 23°C)

Accuracy (Tobj = 15~35°C, Tamb = 23°C)

IR Scan Function

-60 to 500 °C (-76 to 932 °F)

±1.0 °C (1.8 °F)

 $T_{obj} = >0$: ±2% of reading or 2°C

whichever is greater

 $T_{obj} = -60 \sim 0 : \pm (2 + 0.05/deg) \circ C$

Thermocouple Probe Function

-64 to 1400 °C (-83.2 to 1999 °F)

±1% of reading or 1°C whichever is greater (Test under Tamb = 23 ±6°C

Emissivity Range Adjustable 0.1 to 1 step .01 (Default 0.95)

Spectral Response 8 ~ 14 μm spectrum Operating Range 0 to 50 °C (32 to 122 °F)

Response Time (90%) 1 sec Distance : Spot 12 : 1

Battery Life Typ. 180 min, 140 hours continuous use (Alkaline, without laser)

Dimension 141.45 x 134.41 x 41.97 mm

Weight 170g including batteries (AAA x 2pcs)

**Note: Under the electromagnetic field of 3V/m from 200 to 600 MHz, the max error is 10°C (18°F)

MODEL

BG55 Infrared thermometer with K-type thermocouple built-in jack

K-type thermocouple Available upon request