

## FEATURES

- Tachometer output options, for sensing and speed control
- PBT UL94V-0 thermoplastic impeller.
- supporting excellent performance and life expectancy

## RS PRO, 12 V dc, DC Axial Fan, 40 x 40 x 10mm, 11.9m<sup>3</sup>/h, 1.2W

RS Stock No.: 619-7037



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

Brought to you by RS Pro brand, a wide range of DC ball bearing axial fans offering a cost effective cooling solution without sacrificing on quality or reliability. With a brushless, auto restart, impedance and polarity protected motor these fans are ideal for a multitude of applications. All models are highly reliable and excellent quality.

## General Specifications

<b>Air Flow</b>	6CFM
<b>Fan Speed</b>	6000rpm
<b>Static Pressure</b>	0.10in/H2O
<b>Noise Level</b>	30.5dB
<b>Direction of Curve</b>	Backwards
<b>Frame</b>	PBT UL94V-0 Plastic
<b>Impeller</b>	PBT UL94V-0 Plastic
<b>Alarm Function</b>	No
<b>Special Features</b>	Dual Ball Bearing
<b>IP Rating</b>	IP44
<b>Applications</b>	Server racks, Electrical cabinets and enclosures; Production Lines, Ceiling fan/ventilation Desktop computers, Motor engines (radiator in a car), Generators, Air compressors

### Electrical Specifications

<b>Motor</b>	Brushless DC Motor, Polarity Protected
<b>AC or DC Operation</b>	DC
<b>Power Consumption</b>	1.2W
<b>Supply Voltage</b>	12VDC
<b>Rated Voltage</b>	12VDC
<b>Maximum Current</b>	100mA
<b>Dielectric Strength</b>	500VAC/min < 1mA
<b>Insulation Resistance</b>	100M ohm between lead wire and frame (500VDC)

### Mechanical Specifications

<b>Dimensions</b>	40mm x 40mm x10mm
<b>Height</b>	40mm
<b>Width</b>	40mm
<b>Depth</b>	10mm
<b>Bearing Type</b>	Ball
<b>Weight</b>	0.017Kg (0.02 lbs)
<b>Life Expectancy</b>	70,000 hours (L10 at 40°C)

### Operation Environment Specifications

<b>Operating Temperature</b>	-20°C to 70°C
<b>Storage Temperature</b>	-45°C to 70°C

### Approvals

<b>Compliance/Certifications</b>	UL, cUL, TUV, CE, UL94-V0
----------------------------------	---------------------------

# Axial Fans



LEAD WIRES : UL 1007, 26 AWG, L = 300 ± 10 mm  
Red = Positive ; Black = Negative.  
White = Tach

