KB31BPB_WE_G2

Vivace, 10A 250V Bell Press Switch with Bell Icon, white





Main

Range	Vivace
Product or component type	Bell press switch
Device short name	KB31
Device application	Control
Additional switch application	Bell switch
Switch function	1-way

Complementary

Complementary	
Device presentation	Complete mechanism
Actuator	Rocker
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	10 A at 250 V AC, inductive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L1 L2 COM
Tightening torque	0.4 N.m
Clamping connection capacity	1.5 mm²
Width	87 mm
Height	87 mm

Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1	
Ambient air temperature for operation	-540 °C	
Relative humidity	095 %	
Environmental characteristic	Indoor use	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.2 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	71 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	640 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	31 cm
Package 3 Length	50 cm
Package 3 Weight	6400 g

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€ Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty