



Main

Range	Mureva
Product or component type	Wander socket
Device short name	Mureva socket
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

Complementary

Plug, socket, control station shape	Straight	
[In] rated current	125 A	
[Ue] rated operational voltage	380415 V	
Network frequency	50/60 Hz	
Ground lug clockwise position	6 h	
Plug, socket material	Housing: self-extinguishing engineering polymer	
Contacts material	Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel	
Connections - terminals	Captive screws	
Cable cross section	1670 mm²	
Cable outer diameter	2648 mm	
Cable entry	Cable gland	
Thread type	Pg 48	
Net weight	1.72 kg	
Height	131 mm	
Width	131 mm	
Depth	325 mm	
Colour	Grey (RAL 7035)	
Voltage colour	Red	

Environment

Standards	IEC 60309-2	
	IEC 60309-1	
IP degree of protection	IP67 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 62262	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Relative humidity	50 % at 40 °C	
	70 % at 30 °C	
	90 % at 20 °C	
Ambient air temperature for operation	35 °C (86400 s)	
	-2540 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.5 cm
Package 1 Width	12.5 cm
Package 1 Length	32.6 cm
Package 1 Weight	1.773 kg
Unit Type of Package 2	S03
Number of Units in Package 2	5
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.353 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	